



Sikafloor® Proguard™ Duracover™ Installed Floor Protection

Proguard Duracover is a multi-ply, textured floor protection membrane laminated with a non-woven polypropylene geotextile. It is available in 6' x 150' rolls and may be cut to fit using scissors or a utility knife. Proguard Duracover can be removed easily at the completion of the project, needing minimal clean up.

- Protect installed resinous, terrazzo, polished concrete, tile, wood or composite floor systems
- Highly durable surface protection suited for heavy traffic and aggressive use
- Oil and impact resistant
- Suitable for interior use
- Easy to install and remove



Sikafloor® Proguard™ Duracover™

Sikafloor® Proguard™ Duracover™ is a tough, durable composite material that will protect flooring from harsh construction environments both before and after installation. Proguard Duracover is flexible, and easy to place and remove at the completion of the project, requiring minimal clean up.

Size:

- Rolls are 6 feet wide by 150 feet long. Material is 18 mils thick.
- Sikafloor Proguard Duracover Seaming Tape (roll) is 4 inches wide by 150 feet long.

Weight:

- Approximately 45 lbs. per roll.

Installation:

- Use on concrete that is a minimum of 3 days old.
- Use with shiny side up.
- When laying Proguard Duracover, overlap the edges by at least 2 inches.
- Use Sikafloor Proguard Duracover Seaming Tape to tape overlapped seams.
- DO NOT APPLY SEAMING TAPE TO THE FLOOR ITSELF. IT WILL PERMANENTLY DAMAGE THE FLOOR.

Removal:

- Use scissors or a utility knife to cut, making sure that the utility knife does not scar the floor that is being protected.
- Discard following local regulations for disposal.

Keys to success:

- Tape down all seams with Sikafloor Proguard Duracover Seaming Tape.
- DO NOT APPLY THE TAPE TO THE FLOOR ITSELF.
- Use only on fully cured coatings, consult the coating manufacturer's tech data bulletin for cure times before covering.
- Wipe up all spills immediately. Unrolling can develop static electric sparks. Ensure all flammable vapors from coating or flooring applications have dissipated prior to installation.

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any



Your Partner in Concrete Protection



SIKA CORPORATION • FLOORING

201 Polito Avenue
Lyndhurst, NJ 07071
Tel: 844-529-7101
www.SikaFloorUSA.com

BUILDING TRUST

