

PRODUCT DATA SHEET

Sikafloor®-103 IN Pronto

(formerly MTop SRS 103IN)

ADDITIVES FOR SIKAFLOOR PRONTO METHYL-METHACRYLATE COATINGS AND OVERLAYS

PRODUCT DESCRIPTION

Additive for select Sikafloor® Pronto methyl-methacrylate (MMA) primer resins that promotes curing and adhesion to properly prepared concrete surfaces. Sikafloor®-103 IN Pronto can be used with Sikafloor®-41 P Pronto and Sikafloor®-51 P Pronto primers.

USES

Use on concrete substrates in the following areas:

- Pharmaceutical processing and research areas
- Commercial kitchens and restaurants
- Grocery stores
- Food processing plants
- Hospitals and medical research facilities
- Stadiums

Substrate

- Properly prepared concrete substrates

CHARACTERISTICS / ADVANTAGES

- Promotes adhesion to concrete surfaces

PRODUCT INFORMATION

Packaging	4.5 gallon (17 L) pail 47.5 gallon (180 L) drum
Shelf Life	1 year when properly stored
Storage Conditions	Store in original, unopened container. The container must not be exposed to direct sunlight. Maximum storage temperature is 85° F (27° C).
Color	Amber
Viscosity	Low viscosity liquid

APPLICATION INFORMATION

Application Time	Pot Life: 5 - 10 minutes Cure Time: 45 - 60 minutes
-------------------------	--

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

For Best Performance

- Make certain the most current versions of product data sheet and SDS are being used; visit usa.sika.com to verify the most current versions.
- Proper application is the responsibility of the user. Field visits by Sika personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the job site.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

MIXING

The substrate needs to be clean and dry before applying primer. Refer to mixing chart for exact Sikafloor®-103 IN Pronto, primer resin and Sikafloor®-100 HD Pronto amounts. For any further instructions and questions on the use of Sikafloor®-103 IN Pronto, please contact Sika Technical Support.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT**

OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Sikafloor®-103 IN Pronto
September 2024, Version 03.01
020816220010000031

Sikafloor-103INPronto-en-US-(09-2024)-3-1.pdf

