PIGMENT RED OXIDE 8881045F



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/16/2020

 1.1
 11/15/2021
 000000268956
 Date of first issue: 10/16/2020

SECTION 1. IDENTIFICATION

Product name : PIGMENT RED OXIDE 8881045F

Product code : 00000000056434653

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity :

- repeated exposure

Category 2 (Kidney)

GHS label elements

Hazard pictograms

Signal Word : Warning

Hazard Statements : H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure.

Precautionary Statements : Prevention:

P260 Do not breathe dust.

Response:

P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

PIGMENT RED OXIDE 8881045F



Version Revision Date: SDS Number: Date of last issue: 10/16/2020 1.1 11/15/2021 000000268956 Date of first issue: 10/16/2020

Additional Labeling

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 5.29 %

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
ethylene glycol	107-21-1	>= 10 - < 20
triiron tetraoxide	1317-61-9	>= 1 - < 5
Diethylene glycol	111-46-6	>= 1 - < 5
Benzenesulfonic acid, dodecyl-, branched, compd. with 2- propanamine	90218-35-2	>= 1 - < 5
talc	14807-96-6	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

PIGMENT RED OXIDE 8881045F



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/16/2020

 1.1
 11/15/2021
 000000268956
 Date of first issue: 10/16/2020

Most important symptoms and effects, both acute and

delayed

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides

fumes/smoke carbon black

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

PIGMENT RED OXIDE 8881045F



Version Revision Date: SDS Number: Date of last issue: 10/16/2020 1.1 11/15/2021 000000268956 Date of first issue: 10/16/2020

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, well-ventilated

place.

Protect from direct sunlight.
Store protected against freezing.

Materials to avoid : No applicable information available.

Further information on stor-

age stability

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
		exposure)	concentration	
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Va-	50 ppm	ACGIH
		por)		
		STEL (Inhal-	10 mg/m3	ACGIH
		able fraction,		
		Aerosol only)		
		С	50 ppm	OSHA P0
			125 mg/m3	
talc	14807-96-6	TWA (Dust)	20 Million parti-	OSHA Z-3
			cles per cubic foot	
		TWA (respir-	2 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA (Res-	2 mg/m3	NIOSH REL
		pirable)		
		TWA	0.1 fibres per	ACGIH
			cubic centimeter	
		TWA (Res-	2 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		

Engineering measures : No applicable information available.

PIGMENT RED OXIDE 8881045F



Version Revision Date: SDS Number: Date of last issue: 10/16/2020 1.1 11/15/2021 000000268956 Date of first issue: 10/16/2020

Personal protective equipment

Respiratory protection : No applicable information available.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

No special measures necessary if stored and handled cor-

rectly.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : red

Odor : of glycol

Odor Threshold : No data available

pH : approx. 8.6

Melting point : No applicable information available.

Boiling point : $> 212 \, ^{\circ}\text{F} \, / > 100 \, ^{\circ}\text{C}$

Flash point : No data available

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper

flammability limit

No applicable information available.

PIGMENT RED OXIDE 8881045F



Version Revision Date: SDS Number: Date of last issue: 10/16/2020 1.1 11/15/2021 000000268956 Date of first issue: 10/16/2020

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No data available.

Relative vapor density : No applicable information available.

Relative density : 2.05

Density : 2 g/cm3 (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : emulsifiable

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No data available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : not fire-propagating

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

PIGMENT RED OXIDE 8881045F



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/16/2020

 1.1
 11/15/2021
 000000268956
 Date of first issue: 10/16/2020

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No data available.

Acute toxicity estimate: 2,475 mg/kg

Method: Calculation method

Acute inhalation toxicity : Remarks: No data available.

Acute dermal toxicity : Remarks: No data available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

PIGMENT RED OXIDE 8881045F



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/16/2020

 1.1
 11/15/2021
 000000268956
 Date of first issue: 10/16/2020

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Benzenesulfonic acid, dodecyl-, branched, compd. with 2-propanamine:

Partition coefficient: noctanol/water

: Pow: approx. 6.18
Method: other

Remarks: Based on data from similar materials

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

PIGMENT RED OXIDE 8881045F



Version Revision Date: SDS Number: Date of last issue: 10/16/2020 1.1 11/15/2021 000000268956 Date of first issue: 10/16/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
ethylene glycol	107-21-1	5000	30940

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

PIGMENT RED OXIDE 8881045F



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/16/2020

 1.1
 11/15/2021
 000000268956
 Date of first issue: 10/16/2020

ethylene glycol 107-21-1

Nonylphenol,

68412-54-4

branched, ethox-

ylated

Diethylene glycol 111-46-6

2-butoxyethanol 111-76-2

US State Regulations

Pennsylvania Right To Know

1332-37-2
107-21-1
7732-18-5
68412-54-4
1317-61-9
111-46-6
14807-96-6
1310-58-3
7664-38-2

New Jersey Right To Know

Iron oxide	1332-37-2
ethylene glycol	107-21-1
water	7732-18-5
Nonylphenol, branched, ethoxylated	68412-54-4
triiron tetraoxide	1317-61-9
Diethylene glycol	111-46-6
talc	14807-96-6

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO2), which is/are known to the State of California to cause cancer, and

ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : This product contains one or more components listed on the

Canadian NDSL. All other components are on the Canadian

DSL.

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

PIGMENT RED OXIDE 8881045F




Version Revision Date: SDS Number: Date of last issue: 10/16/2020 1.1 11/15/2021 000000268956 Date of first issue: 10/16/2020

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average

OSHA P0 / C : Ceiling limit

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -

PIGMENT RED OXIDE 8881045F



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/16/2020

 1.1
 11/15/2021
 000000268956
 Date of first issue: 10/16/2020

Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/15/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN