BUILDING TRUST

PRODUCT DATA SHEET

Hydrotech® Splice Tape Primer

Solvent-based, fast-drying, VOC-compliant lap and seam primer

PRODUCT DESCRIPTION

Hydrotech® Splice Tape Primer is a solvent-based, fast-drying, VOC-compliant lap and seam primer that improves the adhesion of butyl tape to Flex-Falsh UN.

USES

- Prepares Flex-Flash UN uncured neoprene flashing surfaces for Splice Tape installation.
- Designed for use with Hydrotech® Splice Tape
- Splice Tape and Splice Tape Primer shall not be used in applications where Flex Flash UN is embedded into MM6125
- Splice Tape Primer should only to be used in exposed conditions.

CHARACTERISTICS / ADVANTAGES

- Fast drying
- VOC compliant
- Improves butyl tape adhesion

PRODUCT INFORMATION

Chemical Base	Solvent-based primer
Packaging	1 gal (3.8 L)
Shelf Life	12 months
Storage Conditions	Store in original container. Store in dry, cool, well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at 60 °F to 80 °F (16 °C to 27 °C). If stored below 40 °F (4 °C), condition the primer at room temperature above 60 °F (16 °C) for at least 3 days before use.
Flash Point	16 °F (-9 °C) (TCC)
Volatile organic compound (VOC) content	Please see the product's Safety Data Sheet

APPLICATION INFORMATION

Coverage	350 - 400 ft²/gal (8.6 to 9.8 m²/L) One gallon treats both mating surfaces for approximately six rolls of Splice Tape or 600 linear ft (183 m)
Ambient Air Temperature	≥ 40 °F (4 °C) Application below 40 °F (4 °C) will increase drying time.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

USES

If condensation forms on freshly applied primer, stop application, allow the area to dry, and reapply a thin coat of primer before continuing.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

NOTES ON INSTALLATION

- Clean mating surfaces and remove the polyethylene release sheet before priming.
- Stir thoroughly before and during use.
- Apply using a brush or roller.
- Allow primer to dry until it does not stick to a dry finger.
- Install Splice Tape immediately after primer dries.

LEGAL DISCLAIMER

- **KEEP CONTAINER TIGHTLY CLOSED**
- **KEEP OUT OF REACH OF CHILDREN**
- **NOT FOR INTERNAL CONSUMPTION**
- **FOR INDUSTRIAL USE ONLY**
- **FOR PROFESSIONAL USE ONLY**

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/about-us/terms-conditions-of-sale.html or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com