

NOTES:

- 1) NAILERS SHALL BE SECURELY ANCHORED TO THE DECK TO RESIST A MINIMUM FORCE OF 300 POUNDS PER LINEAR FOOT. FOLLOW FACTORY MUTUAL LOSS PREVENTION DATA SHEET 1-49 RECOMMENDATIONS.
- 2) THE THICKNESS OF THE NAILER SHALL MATCH THE HEIGHT OF THE INSULATION OR SURFACE TO WHICH THE MEMBRANE IS TO BE APPLIED.
- 3) VAPOR RETARDER SHALL BE SEALED AT EDGES.
- 4) CONTINUOUS CLEAT IS REQUIRED IF FACE DIMENSION OF FASCIA EXCEEDS 3 INCHES.
- 5) FACE DIMENSION OF FASCIA SHALL BE A MINIMUM OF 3 INCHES OR AS OTHERWISE REQUIRED TO EXTEND A MINIMUM OF 1-1/2 INCHES BELOW BOTTOM OF WOOD NAILER.
- 6) THE HORIZONTAL FLANGE OF FASCIA SHALL BE A MINIMUM OF 4 INCHES WIDE.
- 7) FASCIA MAY BE FORMED WITH AN OPTIONAL WATER DAM/GRAVEL STOP.
- 8) NAILS USED TO ATTACH EITHER THE CONTINUOUS CLEAT OR FASCIA SHALL PENETRATE THE NAILER A MINIMUM OF 1-1/2 INCHES. SCREWS SHALL PENETRATE A MINIMUM OF 1 INCH.
- 9) ONLY TO BE USED ON SIKAPLAN PROJECTS TO BE WARRANTED FOR 10 YEARS OR LESS.
- 10) THIS DETAIL ONLY QUALIFIES FOR SIKAPLAN SYSTEM WARRANTIES

ROOF EDGE DETAIL

