

PRODUCT DATA SHEET

SikaProof® Fix Tape-50

Double Sided SELF-ADHESIVE TAPE FOR DETAILING SIKAPROOF A WATERPROOFING SYSTEM

PRODUCT DESCRIPTION

SikaProof® Fix Tape-50 is a double-sided, self-adhesive tape, consisting of a butyl rubber adhesive that is covered with a release liner.

USES

SikaProof® Fix Tape-50 may only be used by experienced professionals.

- Waterproofing various detailing configurations within the SikaProof® A Waterproofing System.

CHARACTERISTICS / ADVANTAGES

- Good adhesion of the butyl rubber adhesive
- Good durability
- Self adhesion allows easy and fast installation

PRODUCT INFORMATION

Packaging	5 rolls packed in one box
Appearance / Color	White release liner over black butyl rubber adhesive.
Shelf Life	24 months from date of production
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Always refer to packaging.
Dimensions	
Length	20 m (65.6 ft)
Width	50 mm (2 in)
Diameter	
Thickness	1.50 mm (0.06 in)

SYSTEM INFORMATION

System Structure SikaProof® Fix Tape-50 must be used with the following:

APPLICATION INFORMATION

Ambient Air Temperature +40 °F min. / +95 °F max.

Substrate Temperature +40 °F min. / +95 °F max.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surfaces of the membrane must be dry, clean and free of materials that could impair adhesion.

APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Reference must be made to the Sika® Method Statement: SikaProof® A membrane

AVAILABILITY/WARRANTY

- Sika® Method Statement: SikaProof® A membrane
- System Data Sheet: SikaProof® A membrane

LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- SikaProof® Fix Tape-50 is not UV stabilised and must not be installed on structures that permanently exposes the membrane to UV light and weathering.
- Do not apply the SikaProof® Fix Tape-50 during continuous or prolonged rainfall.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

A Material Safety Data Sheet following EC- Regulation 1907/2006, Article 31 is not required to bring this product to the market, to transport, or to use it. The product does not damage the environment when used as specified.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

SikaProof® Fix Tape-50
October 2019, Version 01.01
020720308000000004

SikaProofFixTape-50-en-US-(10-2019)-1-1.pdf

