

# PRODUCT DATA SHEET

## G459 FLASHING MEMBRANE

G459 Flashing Membrane can be adhered directly to asphalt or other contaminated surfaces. It is formulated for direct exposure to the weather, is heat-weldable and produced with an integral fiberglass mat reinforcement for dimensional stability. G459 Flashing Membrane is used to flash roof penetrations within Sarnafil® and Sikaplan® roofing and waterproofing flashing details.

### PRODUCT INFORMATION

#### USES

For Sarnafil and Sikaplan roofing and waterproofing flashing details where contaminated surfaces may be present.

#### AREAS OF APPLICATION

- Flashing pipes
- Inside/outside corners
- Parapet walls

#### FEATURES / BENEFITS

- Back side resistant to asphalt
- Glass reinforced for dimensional stability and durability
- Lacquer coated top surface to reduce dirt pick up
- Convenient pre-cut rolls

#### CODES / APPROVALS

- Underwriters Laboratories
- Underwriters Laboratories of Canada
- FM Global
- Miami-Dade County
- Florida Building Code

### PRODUCT DATA

#### FORM

#### COMPOSITION

G459 Flashing Membrane is a 60 mil high-quality product containing PVC resin, pigments, stabilizers, ultraviolet absorbers, and a fiberglass carrier sheet. The standard color is white on tan. The tan side of the membrane must be the side exposed to the contamination.

#### COLORS

Top Side: White

Bottom Side: Tan

#### PACKAGING

6.5 ft x 65 ft (2 m x 20 m) roll, 163 lbs (74 kg) per roll, 19 rolls per pallet

3.25 ft x 65 ft (1 m x 20 m) roll, 81 lbs (37 kg) per roll, 40 rolls per pallet

**TECHNICAL DATA****TYPICAL PHYSICAL PROPERTIES\***

Properties	ASTM Test Method	Typical Results
Overall Thickness, mil	D751	60
Reinforcing Material	--	Fiberglass
Weight, lb/ft <sup>2</sup> (kg/m <sup>2</sup> )	--	0.39 (1.93)
Breaking Strength, lbf/in (N)	D751	80 (356)
Elongation at Break, % M.D. <sup>1</sup> & C.M.D. <sup>1</sup>	D751	270 & 250
Seam Strength, % of original <sup>2</sup>	D751	80
Retention of Properties After Heat Aging	D3045	--
Tensile Strength, % of original	D751	95
Elongation, % of original	D751	90
Tearing Resistance, lbf (N)	D1004	14 (63)
Low Temperature Bend, -40°F (-40°C)	D2136	Pass
Accelerated Weathering Test (Florescent Light, UV exposure)	G154	Pass
Cracking (7x magnification)	--	None
Discoloration (by observation)	--	Negligible
Crazing (7x magnification)	--	None
Linear Dimensional Change, %	D1204	0.02
Weight Change After Immersion in Water, %	D570	2.5
Static Puncture Resistance	D5602	Pass
Dynamic Puncture Resistance	D5635	Pass

\* Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions, and curing conditions.

<sup>1</sup> M.D. = Machine Direction, C.M.D. = Cross Machine Direction

<sup>2</sup> Failure occurs through membrane rupture not seam failure.

**STORAGE****STORAGE CONDITIONS**

Store rolls on pallets and fully protected from the weather with clean canvas tarpaulins. Unvented polyethylene tarpaulins are not accepted due to the accumulation of moisture beneath the tarpaulin in certain weather conditions that may affect the ease of membrane weldability.

**SYSTEM INFORMATION****APPLICATION INSTRUCTIONS**

G459 Flashing Membrane is installed on walls, curbs and other penetrations using Sika adhesives. The seams are heat welded together by trained operators using hot-air welding equipment.

**AVAILABILITY**

From Sika Authorized Applicators when used within Sarnafil or Sikaplan roofing systems.

**MAINTENANCE**

Standard maintenance of roofs should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

**WARRANTY**

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

---

**LEGAL NOTES**

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling 800-451-2504.

**Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at [usa.sarnafil.sika.com](http://usa.sarnafil.sika.com) or by calling Sika's Technical Service Department at 800-451-2504. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.**

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

---

**SIKA CORPORATION – ROOFING****UNITED STATES**

100 Dan Road  
Canton, MA 02021  
800-451-2504 (p)  
781-828-5365 (f)  
[usa.sarnafil.sika.com](http://usa.sarnafil.sika.com)  
[webmaster.sarnafil@us.sika.com](mailto:webmaster.sarnafil@us.sika.com)

**SIKA CANADA INC.**

6915 Davand Drive  
Mississauga, ON L5T 1L5  
905-795-3177 (p)  
905-795-3192 (f)  
[can.sika.com](http://can.sika.com)  
[marketing.construction@ca.sika.com](mailto:marketing.construction@ca.sika.com)

---