

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

---

### SECTION 1. IDENTIFICATION

Product name : Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray

Product code : 000000000051376969

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE  
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

---


### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Central nervous system)

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H319 Causes serious eye irritation.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P260 Do not breathe dusts or mists.

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

P270 Do not eat, drink or smoke when using this product.  
P264 Wash face, hands and any exposed skin thoroughly after handling.

### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture based on:  
polymers

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	$\geq 10 - < 20$
calcium carbonate	471-34-1	$\geq 10 - < 20$
Stoddard solvent	8052-41-3	$\geq 5 - < 10$
Titanium dioxide	13463-67-7	$\geq 1 - < 5$
Ethylenediamine, propoxylated	25214-63-5	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.  
Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air.  
If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water  
and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

---

- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do not induce vomiting unless told to by a poison control center or doctor.
  - Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.
  - Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
  - Unsuitable extinguishing media : water jet
  - Hazardous combustion products : fumes/smoke  
harmful vapours  
Carbon oxides  
nitrogen oxides  
carbon black
  - Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water.  
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
  - Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
Wear eye/face protection.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
  - Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
  - Methods and materials for containment and cleaning up : Pick up with suitable appliance and dispose of.  
Dispose of absorbed material in accordance with regulations.
-

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.
- Advice on safe handling : Avoid inhalation of dusts/mists/vapours.  
Avoid contact with skin and eyes.  
Ensure adequate ventilation.  
No special measures necessary provided product is used correctly.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
- Further information on storage stability : Stable under recommended storage conditions.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

**Respiratory protection** : Wear appropriate certified respirator when exposure limits may be exceeded.  
Use NIOSH approved respiratory protection.

**Hand protection**

**Remarks** : Chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Wear safety glasses with side shields or goggles.

**Skin and body protection** : Body protection must be chosen based on level of activity and exposure.

**Protective measures** : Do not inhale dust/fumes/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

**Hygiene measures** : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : paste

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

---

Color : gray

Odor : aromatic

Odor Threshold : not determined

pH : neutral to slightly alkaline

Melting point : No data available

Boiling point : No data available

Flash point : does not flash

Evaporation rate : No data available

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 6.9 - 7.9 lb/USg (68 °F / 20 °C)

Solubility(ies)

    Water solubility : emulsifiable

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : not applicable for mixtures

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : No data available

Explosive properties : Not explosive

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

---

Oxidizing properties : not fire-propagating  
Sublimation point : No data available  
Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.  
Chemical stability : The product is stable if stored and handled as prescribed/indicated.  
Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.  
Conditions to avoid : See SDS section 7 - Handling and storage.  
Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents  
Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified based on available information.

##### Respiratory sensitization

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

##### Carcinogenicity

Not classified based on available information.

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

---

**IARC**      Group 2B: Possibly carcinogenic to humans  
Titanium dioxide      13463-67-7

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

### Aspiration toxicity

Not classified based on available information.

### Further information

#### Product:

Remarks      :    Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

### Ecotoxicology Assessment

Acute aquatic toxicity      :    This product has no known ecotoxicological effects.

Chronic aquatic toxicity      :    This product has no known ecotoxicological effects.

### Persistence and degradability

#### Product:

Biodegradability      :    Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

### Bioaccumulative potential

#### Product:

Bioaccumulation      :    Remarks: No data available. Discharge into the environment must be avoided.

### Mobility in soil

No data available



# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

### Other adverse effects

#### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
isobutane	75-28-5	100	37721

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version 1.1      Revision Date: 05/16/2022      SDS Number: 000000534117      Date of last issue: 09/21/2020  
Date of first issue: 09/21/2020

### US State Regulations

#### Pennsylvania Right To Know

Limestone	1317-65-3
calcium carbonate	471-34-1
Stoddard solvent	8052-41-3
Titanium dioxide	13463-67-7
zinc neodecanoate	27253-29-8

#### New Jersey Right To Know

Limestone	1317-65-3
Stoddard solvent	8052-41-3
Titanium dioxide	13463-67-7

#### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


#### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory  
DSL : All components of this product are on the Canadian DSL

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2020
1.1	05/16/2022	000000534117	Date of first issue: 09/21/2020

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
ACGIH / TWA : 8-hour, time-weighted average  
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek  
NIOSH REL / C : Ceiling value not be exceeded at any time.  
OSHA P0 / TWA : 8-hour time weighted average  
OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/16/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# SAFETY DATA SHEET

## Sikaflex NP 2 Part A precast gray Formerly MSeal NP 2 precast gray



Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2020
1.1	05/16/2022	000000534117	Date of first issue: 09/21/2020

---

US / EN