

PRODUCT DATA SHEET

Sikalastic® Primer EPDM

SINGLE COMPONENT PRIMER FOR CONSISTENT AND DURABLE ADHESION BETWEEN SIKALASTIC® ROOFPRO ROOFING AND WATERPROOFING SYSTEMS AND EPDM MEMBRANES

PRODUCT DESCRIPTION

Sikalastic® Primer EPDM is a single component rubber polymer based primer to improve adhesion of Sikalastic liquid applied membranes to flexible EPDM roofing membranes. Unlike thin primers that run and puddle, the high viscosity formulation promotes uniform coverage on both horizontal and vertical surfaces. Sikalastic® Primer EPDM does not react with atmospheric moisture allowing it to be opened and resealed for use at a later date.

USES

Sikalastic® Primer EPDM is used to prime EPDM roofing membrane to improve adhesion of Sikalastic® RoofPRO Systems. It is typically used for overcoating existing roofing membranes, flashing and flashing of penetrations and perimeter terminations, performance of repairs, or modification to the existing roofing system.

CHARACTERISTICS / ADVANTAGES

- Provides excellent adhesion of new Sikalastic® liquid applied membrane to most EPDM membranes.
- Quick cure allows same-day Sikalastic® membrane application in most instances.

PRODUCT INFORMATION

Packaging	1 gal. (3.8 L) cans, 6 cans per carton	
Appearance / Color	Off-white	
Shelf Life	12 months in original, unopened and undamaged sealed containers	
Storage Conditions	Store dry between 41 °F and 86 °F (5–30 °C)	
Density	0.779 kg/l	
Solid Content	15 %	(ASTM D-2697)
Volatile organic compound (VOC) content	690 g/l	(ASTM D-2369-81)

TECHNICAL INFORMATION

Service Temperature -22–176 °F (-30–80 °C) intermittent

APPLICATION INFORMATION

Coverage 200 - 250 sq.ft./ gal.

Ambient Air Temperature 41 °F (5 °C) min. / 95 °F (35 °C) max.

Relative Air Humidity 80 % R.H. max.

Dew Point Beware of condensation.
The substrate and uncured coating must be ≥ 5 °F (3 °C) above dew point.

Substrate Temperature 41 °F (5 °C) min. / 140 °F (60 °C) max.

Pot Life Once opened, the product should be used and resealed promptly. Sikalastic® Primer EPDM does not react with atmospheric moisture allowing it to be opened and resealed for use at a later date.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All work surfaces should be clean, dry, free of dirt, dust, debris, oils, un-adhered coatings, deteriorated membrane and other contaminants that may result in a surface that is not sound or is uneven. If necessary, clean the surface with an approved EPDM membrane cleaner prior to application of Sikalastic® Primer EPDM.

MIXING

Shake or stir the 1 gal. (3.8 L) can of Sikalastic® Primer EPDM for 30 seconds prior to application.

APPLICATION

Do not dilute or extend Sikalastic® Primer EPDM. Surfaces should be dry and clean before applying Sikalastic® Primer EPDM. EPDM surfaces should be cleaned with a suitable solvent such as mineral spirits prior to priming. Observe all manufacturers' safety precautions and use recommendations when using solvents. When the surfaces are dry, apply Sikalastic® Primer EPDM with a fully saturated roller or brush. The surface should appear wet during application. Do not overwork primer. Allow primer to dry completely before applying resins. Primer will visually appear "dull" or "flat" and will feel dry to the touch. Drying conditions will vary depending on ambient air conditions. When not in use, keep lid on primer to prevent solvent evaporation. When finished, secure lid and store primer as recommended for use at a later date.

LIMITATIONS

- Do not store materials outdoors exposed to sunlight and moisture for prolonged periods.
- Existing membrane must be dry prior to application. Do not apply to a frosted, wet or damp surface.

- Allow sufficient time for the existing membrane to dry after rain or inclement weather, or following pressure washing, as there is the potential for bonding problems.
- Precautions should be taken to prevent vapors and/or odors from entering the building/structure, including but not limited to turning off and sealing air intake vents and through-wall air conditioners, and other means of vapor/odor ingress during application and cure
- Do not use as a membrane cleaner.
- Talc, dust, oil, ice, snow, or wet conditions inhibit good adhesion. Clean and dry surfaces are a necessity.
- Not for use on PVC roof membranes.
- Do not use on extruded or expanded polystyrene insulation.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation
 201 Polito Avenue
 Lyndhurst, NJ 07071
 Phone: +1-800-933-7452
 Fax: +1-201-933-6225
usa.sika.com

Sika Sarnafil
 100 Dan Road
 Canton, MA 02021
 Phone: +1 800-451-2504
 Fax: +1 781-828-5365
usa.sarnafil.sika.com
webmaster.sarnafil@us.sika.com

Sika Mexicana S.A. de C.V.
 Carretera Libre Celaya Km. 8.5
 Fracc. Industrial Balvanera
 Corregidora, Queretaro
 C.P. 76920
 Phone: 52 442 2385800
 Fax: 52 442 2250537

SIKA CORPORATION – ROOFING
 100 Dan Road
 Canton, MA 02021
 Phone: +1-800-451-2504
 Fax: +1-781-828-5365



Product Data Sheet
 Sikalastic® Primer EPDM
 February 2019, Version 01.01
 020915951000000036

SikalasticPrimerEPDM-en-US-(02-2019)-1-1.pdf

