according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

SECTION 1. IDENTIFICATION

Product name : Sikafloor PGM 155 Pronto light stone Formerly MTop PGM

155 lgt stone

Product code : 00000000050184175

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Coloring agents, pigments

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

Other hazards

None known.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Pigment

Components

Chemical name	CAS No./Unique	Concentration (% w/w)	Trade secret			
Titanium dioxide	13463-67-7*	>= 65 - <= 85	TSC			
Limestone	1317-65-3*	>= 10 - <= 30	TSC			

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : After inhalation of dust.

Keep patient calm, remove to fresh air, seek medical atten-

tion.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Contact lenses should be removed. Hold eyelids open and

flush with copious amounts of clean, fresh water or a special

eyewash solution and seek medical advice.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do not induce vomiting unless told to by a poison control cen-

ter or doctor.

Most important symptoms and effects, both acute and

delayed

None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Hazardous combustion prod: :

ucts

harmful vapours nitrogen oxides

fumes/smoke carbon black carbon oxides

Further information : The degree of risk is governed by the burning substance and

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version **Revision Date:** SDS Number: Date of last issue: -

000000477865 1.0 03/27/2025 Date of first issue: 03/27/2025

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Avoid dust formation. Do not breathe dust.

Avoid contact with skin and eyes. Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Sweep up and shovel into suitable containers for disposal.

Avoid raising dust.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Dust can form an explosive mixture with air.

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Keep away from sources of ignition - No smoking.

Advice on safe handling Avoid dust formation.

> Avoid inhalation of dusts. Avoid skin contact.

Wear suitable protective clothing and eye/face protection. Pour downwind and allow as little free fall as possible while

emptying bags into equipment.

Breathing must be protected when large quantities are de-

canted without local exhaust ventilation.

Conditions for safe storage Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.2 mg/m3 (Titanium dioxide)	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	2.5 mg/m3 (Titanium dioxide)	ACGIH
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's direc-

tions for use should be observed because of great diversity of

types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

and exposure.

Protective measures : Avoid contact with the skin, eyes and clothing.

Avoid inhalation of dusts.

In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene

and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : beige

Odor : odorless

Odor Threshold : Not applicable

pH : No data available

Melting point/freezing point : Not applicable

Boiling point : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

: No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Sublimation temperature : No data available

Molecular weight : Not applicable

Particle characteristics

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac- :

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

03/27/2025 000000477865 1.0 Date of first issue: 03/27/2025

Incompatible materials Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC Group 2B: Possibly carcinogenic to humans

> Titanium dioxide 13463-67-7

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks Health injuries are not known or expected under normal use.

> The product has not been tested. The statements on toxicology have been derived from the properties of the individual

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

IATA-DGR

Not permitted for transport

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Titanium dioxide 13463-67-7 Limestone 1317-65-3

New Jersey Right To Know

Titanium dioxide 13463-67-7 Limestone 1317-65-3

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

NFPA 704:

Health 1 1 0 Instability

Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC

according to the OSHA Hazard Communication Standard



Sikafloor PGM 155 Pronto light stone Formerly MTop PGM 155 lgt stone

Version Revision Date: SDS Number: Date of last issue: -

1.0 03/27/2025 000000477865 Date of first issue: 03/27/2025

- No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/27/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN