

# SIKA CORPORATION • ROOFING

## PLATES AND DISCS SELECTION GUIDE

Plates and Discs	Fastener Type								Insulation or Cover Board Attachment	Membrane Attachment	Sizes Available
	Sarnafastener #12	Sarnafastener #14	Sarnafastener #15 XP	Sarnafastener MAXLoad	RetroDriller	CD-10	Polymer GypTec	Lite-Deck			
Sarnadisc	-	●	●	-	●	●	-	-	N/A	Base of walls, curbs, roof penetrations, and intermediate wall securement.	2"
Sarnadisc XPN	-	●	●	-	●	●	-	-	N/A	In-seam membrane attachment	3.75" x 1.5"
Sarnadisc GypTec	-	-	-	-	-	-	●	-	N/A	In-seam attachment of 5 ft membrane	2"
Sarnadisc MAXLoad	-	-	-	●	-	-	-	-	N/A	In-seam membrane attachment	3"
Sarnadisc RhinoBond	-	●	●	● <sup>3</sup>	-	-	-	-	Attach approved boards directly to the roof deck or structural purlins	Induction membrane welding	3"
RhinoBond PS (Cardboard Disc)	-	●	●	-	-	-	-	-	Protects EPS fanfold from heat during the induction welding process	Induction membrane welding	4"
Sarnadisc Trufast Induction Weld	-	●	●	-	-	-	-	-	Attach approved boards directly to the roof deck or structural purlins	Induction membrane welding	3"
Sarnaplate	●	●	●	-	-	●	-	-	Attach insulation or roof boards direct to the roof deck	N/A	3" x 3"
Sarnaplate Low Profile	●	●	●	-	-	-	-	-	Attach insulation or roof boards direct to the roof deck <sup>(1)</sup>	N/A	2.75" x 2.75"
Sarnaplate Accutrac	●	●	●	-	-	-	-	-	Attach insulation or roof boards direct to the roof deck	N/A	3" x 3"
Sarnaplate Lite-Deck	-	-	-	-	-	-	-	●	Attach approved boards directly to gypsum or cementitious wood fiber roof decks	N/A	3"
Sarnaplate GypTec	-	-	-	-	-	-	●	-	Attach approved boards directly to gypsum or cementitious wood fiber roof decks	N/A	3"
Sarnabar	-	●	●	-	-	●	-	-	N/A	Clamp membrane to the roof deck	10 ft x 1"
Sarnabar® stainless steel	-	●	●	-	-	●	-	-	N/A	Clamp membrane to the roof deck	10 ft x 1"
Sarnarail	-	●	●	-	-	-	-	-	N/A	In-seam attachment	250 ft x 0.75"
Sarnastop	-	●	●	-	-	●	-	-	N/A	Clamp membrane to the roof deck at base of walls, curbs and transitions	10 ft x 1"
Sarnareglet	-	●	●	-	-	●	-	-	N/A	Clamp flashing to the roof deck at base of walls, curbs and transitions	10 ft x 2.25"
Sikaplan® Disc	-	●	●	-	●	●	-	-	N/A	In-seam membrane attachment	2.375"
Sikaplan Termination Bar	●	●	●	-	-	●	-	-	N/A	Membrane termination	10 ft x 0.75"
CR-Base Sheet Fastener <sup>(2)</sup>	-	-	-	-	-	-	-	-	N/A	Basesheet Securement into LWIC	1.125" x 1"
OlyLok Locking Impact Nail	-	-	-	-	-	-	-	-	Used to secure recovery boards to LWIC	Basesheet Securement into LWIC	2.7"

<sup>1</sup> Not recommended for use directly over plywood or OSB surface

<sup>2</sup> Used to secure base sheets to lightweight insulating concrete or various gypsum

<sup>3</sup> Requires matched component Rhinobond Maxload Plate

