

PRODUCT DATA SHEET

DUROSEAL Quellpaste Type E

SikaSwell Swelling Paste Type E

PRODUCT DESCRIPTION

SikaSwell Swelling Paste Type E is a 1-componentic Polyurethan-based Swelling Paste, wich is free of solvent.

USES

- Sealing of construction joints in concrete constructions
- Sealing of all types of penetrations through concrete
- Sealing of details and material transitions to concrete structures

CHARACTERISTICS / ADVANTAGES

- Easy and quick to install, also on rough substrates
- Can be applied on different substrates
- Swelling approx. 350 Vol.-%
- Good flexibility of hardened paste

PRODUCT INFORMATION

Chemical Base	PU Polyurethan (moisture curing)
Packaging	cartridge of 310 ml (12 cartridges per Carton)
Appearance / Color	white
Shelf Life	12 months from date of production
Storage Conditions	Stored in unopened, undamaged and sealed original packaging in dry conditions at temperatures between +40°F and +80°F. Protect from direct sunlight, rain, ice and heat.
Density	~ 1,45 g/ml

TECHNICAL INFORMATION

Tensile Strength	~ 2,0 MPa	DIN 53504
Elongation	~ 500 %	DIN 53504
Swelling	~ 350 Vol.-%	

APPLICATION INFORMATION

Coverage	by 310 ml cartridge: Ø 6 mm ~ 8–10 m Ø 8 mm ~ 4–5 m Ø 10 mm ~ 3 m
Skin Time	~ 12 hours (+ 20 °C / 60 % r. F.)
Ambient Air Temperature	min. + 40 °F for the time of application and hardening
Substrate Temperature	min. + 40 °F for the time of application and hardening

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The substrate must be clean, free from any loose particles and any separating agents (e.g. form oils, fats, dust) and dry or max mat damp.

APPLICATION METHOD / TOOLS

SikaSwell Swelling Paste Type E can be applied by hand, pneumatic pressure, or a caulk gun. The Paste must be applied in a continuous line without interruptions.

SikaSwell Swelling Paste Type E is a moisture curing paste. It is important that a full and continuous contact between the SikaSwell Swelling Paste Type E and the substrate is achieved. During concreting, compact well around the swelling paste to achieve a dense concrete without and honeycombs or voids.

SikaSwell Swelling Paste Type E is intended for use in construction joints - expansion joint are not possible. A minimum of 3 in. of concrete cover is needed to prevent concrete spalling from the swelling pressure.

SikaSwell Swelling Paste Type E should be protected by suitable measures from early swelling (e.g. from rain) between installation and placing of concrete, especially on horizontal surfaces where standing water could occur.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF**

MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

DUROSEAL Quellpaste Type E
May 2019, Version 01.01
020703300112000001

DUROSEALQuellpasteTypeE-en-US-(05-2019)-1-1.pdf

