



SikaBond®-T55

ADHESIVE FOR SOLID WOOD FLOORING

- Bonds to difficult woods
- Fast curing - sand & finish in 12 hours
- Bonds super wide solids

BUILDING TRUST



SikaBond®-T55 ADHESIVE FOR SOLID WOOD FLOORING

SikaBond-T55 is a one-component, low-VOC, highly elastic, crack bridging, super strong polyurethane adhesive for full surface bonding of wood flooring and ceramic tiles.

FEATURES AND BENEFITS

- 400% elongation
- Extremely easy to trowel
- Fast curing - floors can be sanded after 12 hours of cure
- Crack bridging
- Compatible with problematic woods
- Suitable for in-floor radiant heat installations
- Excellent "green grab"
- Footfall-sound-dampening adhesive



FOR MORE SikaBond® INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452), Website www.usa.sika.com



RESPONSIBLE CARE
OUR COMMITMENT TO SUSTAINABILITY



ISO 9001
Certified # FM 89711
RC 14001
Certified # RC 51039

Can contribute 1 LEED® point per installation

SIKA CORPORATION
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201 933 8800
800 933 SIKA
Fax: 201 933-6225

SIKA CANADA, INC.
601 Delmar Avenue
Quebec H9R4A9
Phone: 514 697 2610
Fax: 514 694 3087

SIKA MEXICANA S.A. DE C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

BUILDING TRUST

