

## PRODUCT DATA SHEET

# SikaColor<sup>®</sup>-401 Tint Cup

Liquid colorant tint cup used to pigment SikaCem<sup>®</sup>-100 Silane PRO 350<sup>®</sup>

### PRODUCT DESCRIPTION

SikaColor<sup>®</sup>-401 Tint Cup is a liquid colorant tint cup used to pigment SikaCem<sup>®</sup>-100 Silane PRO 350<sup>®</sup>.

### USES

- Used to pigment SikaCem<sup>®</sup>-100 Silane PRO 350<sup>®</sup>

### PRODUCT INFORMATION

<b>Chemical Base</b>	Solvent-Based Iron Oxide
<b>Packaging</b>	Variable oz. fill in 32 oz. (946.4 ml) plastic bottle
	<b>Note:</b> Fill volume for all colors is approximately 20 oz. (591.5 ml).
<b>Appearance / Color</b>	Available in 65 standard colors. Refer to the SikaColor <sup>®</sup> -100 P Powder Integral Colors color chart or the SikaColor <sup>®</sup> -120 G Granular Integral Colors color chart (excluding U35 Shadow Slate, U51 Clary Sage, and C34 Dark Gray).
<b>Shelf Life</b>	24 months in original unopened container
<b>Storage Conditions</b>	Store in original, unopened containers in dry storage.

### BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

### ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety

### CHARACTERISTICS / ADVANTAGES

- A blended liquid colorant with ease of incorporation

Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

### APPLICATION INSTRUCTIONS

#### MIXING

Shake the tint cup vigorously for 1 minute. Add 1 tint cup to 5 gal. (18.9 L) of SikaCem<sup>®</sup>-100 Silane PRO 350<sup>®</sup>.

Mix mechanically for 3 minutes at low speed, taking care not to impregnate with air. Do not thin.

## APPLICATION

Once the SikaColor®-401 Tint Cup is mixed into SikaCem®-100 Silane PRO 350®, consult the most current SikaCem®-100 Silane PRO 350® local Product Data Sheet for complete Application Instructions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD**

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



### Product Data Sheet

SikaColor®-401 Tint Cup  
October 2024, Version 02.01  
020815110050000005

## BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

SikaColor-401TintCup-en-US-(10-2024)-2-1.pdf

