

TECHNICAL BULLETIN

Allegro, Fog Coat & Color Matching

Sika LaHabra Allegro Cement Coating and Fog Coat are bonding cement coatings, used to revive the existing color and beauty of Stucco or to virtually eliminate color differences caused by job site conditions like changes in the weather. Fog Coat looks best when spray applied. Fog Coat cures to become an integral part of the stucco surface to which it is applied. It will not peel like conventional paint; LaHabra Allegro and Fog Coat provide a durable and long-lasting integrally colored coating material for existing un-painted stucco finishes.

Fog Coat is formulated with portland cement, hydrated lime and lime-resistant mineral color Pigments. The same ingredients found in our stucco, minus only the sand. Fog Coat can be applied to a dry stucco surface as soon as needed. Fog Coat can be applied if/as necessary and it is UV resistant, although like stucco it is porous and is susceptible to staining caused by rain such as, run off from roofs or splashing of dirt in planter areas. To improve the performance and the bonding qualities of Fog Coat we recommend the use of SikaWall Acrylic Bonder as an admix, 1 quart for conventional finishes and up to 1 gallon for semi smooth finishes (Per 25 # bag). The acrylic admix should be added last after the mixing process has been completed and stirred in slowly so as not to entrain air. The normal water curing is eliminated with the use of acrylic admix and the finish should remain dry for a minimum period of 72 hours in order to stabilize.

Before ordering Fog Coat, determine the type of surface texture to which the material will be applied. Different surface Finishes require a different color level of Fog Coat. LaHabra DX Fog Coat color level is formulated to match a sand float finish application. A textured stucco application will require approximately 25% to 50% more color pigment. A machine application will require approximately 50% to 100% more color pigment, unless the original color used is greater than 1 X Then use the original formula and increase it according to the type of finish.

Colors vary due to weather and job conditions. Prior to Fog Coating the surface, a sample should be applied and allowed to dry for color approval.

Prior to ordering Fog Coat, it is always a good to compare an actual sample to the wall surface to determine if additional color pigment will need to be added. **Fog Coat is NOT recommended for application over a high-density smooth surface.**

LIMITED WARRANTY NOTICE

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling our Technical Service Department at +1 (800) 589-1336. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at usa.sika.com.