



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

SECTION 1. IDENTIFICATION

Product name : SikaWall® Color Pack

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity (Inhalation) : Category 1A

Other hazards

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

P280 Wear protective gloves/ protective clothing/ eye protection/
face protection/ hearing protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/
attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-
posal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS No./Unique ID	Classification	Concentration (% w/w)
Dichromium trioxide	1308-38-9		$\geq 7 - \leq 13$
Diiron trioxide	1309-37-1		$\geq 7 - \leq 13$
Titanium dioxide	13463-67-7		$\geq 7 - \leq 13$
Limestone	1317-65-3		$\geq 7 - \leq 13$
Quartz (SiO ₂)	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	$\geq 0.1 - \leq 1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attend-
ance.
- If inhaled : Move to fresh air.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

- | | | |
|---|---|--|
| If swallowed | : | Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : | May cause cancer by inhalation.
No known significant effects or hazards.
Prolonged exposure can cause silicosis.
No information available. |
| Notes to physician | : | Treat symptomatically. |

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|---|
| Suitable extinguishing media | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Hazardous combustion products | : | No hazardous combustion products are known |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.
Avoid breathing dust.
Deny access to unprotected persons. |
| Environmental precautions | : | Try to prevent the material from entering drains or water courses.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : | Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal. |

SECTION 7. HANDLING AND STORAGE

- | | | |
|---|---|--|
| Advice on protection against fire and explosion | : | Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed. |
|---|---|--|



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.
- Further information on storage stability : Keep in a dry place.
No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Dichromium trioxide	1308-38-9	TWA	0.5 mg/m ³ (chromium)	OSHA Z-1
Diiron trioxide	1309-37-1	TWA (Respirable particulate matter)	5 mg/m ³	ACGIH
		TWA (Fumes)	10 mg/m ³	OSHA Z-1
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Fumes)	10 mg/m ³	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA (Total)	10 mg/m ³	OSHA P0
Limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total dust)	15 mg/m ³	OSHA P0



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Particles of nuisance dust

Form of exposure	Value type	Control parameters	Basis
total dust	TWA	15 mg/m3	OSHA Z-3
respirable fraction	TWA	5 mg/m3	OSHA Z-3

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

ed or statutory limits.

Personal protective equipment

- Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Avoid breathing dust.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : powder
- Color : various
- Odor : odorless
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : Not applicable
- Evaporation rate : No data available



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Density	: ca. 1.9 - 2.2 g/cm ³ (68 °F / 20 °C)
Solubility(ies)	
Water solubility	: dispersible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Dynamic	: No data available
Kinematic	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available
Particle size	: No data available
Particle Size Distribution	: No data available
Volatile organic compounds (VOC) content	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

Dichromium trioxide:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Diiron trioxide:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans Titanium dioxide (> 10 µm)	13463-67-7
OSHA	OSHA specifically regulated carcinogen Quartz (SiO ₂) (crystalline silica)	14808-60-7

NTP Known to be human carcinogen



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

Quartz (SiO₂)
(Silica, Crystalline (Respirable Size))

14808-60-7

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Prolonged exposure can cause silicosis.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks

: Titanium dioxide (13463-67-7)
In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Carcinogenicity

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Dichromium tri-oxide	1308-38-9	>= 10 - < 20 %
----------------------	-----------	----------------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65



WARNING: This product can expose you to chemicals including Titanium dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average



SikaWall® Color Pack

Revision Date 02/18/2026

Print Date 02/18/2026

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 02/18/2026

100000072239
US / Z8