

Revision Date 12/05/2023 Print Date 12/05/2023

#### **SECTION 1. IDENTIFICATION**

Product name : Merkrete® 700 Premium Set

Company name : Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: +1-703-527-3887

Recommended use of the

chemical and restrictions on

use

For further information, refer to product data sheet.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity :

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity : Category

- repeated exposure

Category 1 (Lungs)

**GHS** label elements

Hazard pictograms :







Signal Word : Danger

according to OSHA 1910.1200 Hazard Communication Standard



# Merkrete® 700 Premium Set

Revision Date 12/05/2023 Print Date 12/05/2023

Hazard Statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure.

**Precautionary Statements** 

## Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

## Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

P362 + P364 Take off contaminated clothing and wash it before reuse.

## Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

## Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

## **Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.



Revision Date 12/05/2023 Print Date 12/05/2023

## Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Mixtures**

## Components

| Chemical name      | CAS-No.    | Classification      | Concentra-   |
|--------------------|------------|---------------------|--------------|
|                    |            |                     | tion (% w/w) |
| Quartz (SiO2) >5µm | 14808-60-7 | Carc. 1A; H350      | >= 50 - < 70 |
|                    |            | STOT RE 1; H372     |              |
|                    |            | STOT SE 3; H335     |              |
| Portland Cement    | 65997-15-1 | Skin Corr. 1C; H314 | >= 20 - < 30 |
|                    |            | Eye Dam. 1; H318    |              |
|                    |            | Skin Sens. 1; H317  |              |
|                    |            | STOT SE 3; H335     |              |
| Limestone          | 1317-65-3  |                     | >= 5 - < 10  |

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in attend-

ance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.



Revision Date 12/05/2023 Print Date 12/05/2023

Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. Causes serious eye damage.

May cause respiratory irritation. May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure.

Causes severe burns.

Health injuries may be delayed.

corrosive effects irritant effects sensitizing effects

Prolonged exposure can cause silicosis.

Cough

Respiratory disorder Allergic reactions

**Dermatitis** 

Notes to physician Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal. containment and cleaning up

## **SECTION 7. HANDLING AND STORAGE**



Revision Date 12/05/2023 Print Date 12/05/2023

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : Explosives

Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids

Spontaneously Combustible Substances

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

| Components         | CAS-No.    | Value type<br>(Form of<br>exposure)                | Control parameters / Permissible concentration | Basis    |
|--------------------|------------|--|--|----------|
| Quartz (SiO2) >5μm | 14808-60-7 | TWA (Res-<br>pirable par-<br>ticulate mat-<br>ter) | 0.025 mg/m3                                    | ACGIH    |
|                    |            | TWA (Res-<br>pirable dust)                         | 0.05 mg/m3                                     | OSHA Z-1 |
|                    |            | TWA (respir-<br>able)                              | 10 mg/m3 /<br>%SiO2+2                          | OSHA Z-3 |
|                    |            | TWA (respir-<br>able)                              | 250 mppcf /<br>%SiO2+5                         | OSHA Z-3 |



Revision Date 12/05/2023 Print Date 12/05/2023

|                 |            | TWA (respirable dust fraction)                     | 0.1 mg/m3                                | OSHA P0   |
|-----------------|------------|--|--|-----------|
|                 |            | TWA (Res-<br>pirable par-<br>ticulate mat-<br>ter) | 0.025 mg/m3<br>(Silica)                  | ACGIH     |
|                 |            | PÉL (respir-<br>able)                              | 0.05 mg/m3                               | OSHA CARC |
|                 |            | TWA (respirable dust fraction)                     | 0.1 mg/m3                                | OSHA P0   |
|                 |            | TWA (Respirable particulate matter)                | 0.025 mg/m3                              | ACGIH     |
|                 |            | TWA (Respirable particulate matter)                | 0.025 mg/m3<br>(Silica)                  | ACGIH     |
| Portland Cement | 65997-15-1 | TWA (Respirable particulate matter)                | 1 mg/m3                                  | ACGIH     |
|                 |            | TWA (total dust)                                   | 15 mg/m3                                 | OSHA Z-1  |
|                 |            | TWA (respirable fraction)                          | 5 mg/m3                                  | OSHA Z-1  |
|                 |            | TWA (Total dust)                                   | 10 mg/m3                                 | OSHA P0   |
|                 |            | TWA (respirable dust fraction)                     | 5 mg/m3                                  | OSHA P0   |
|                 |            | TWA (Dust)   | 50 Million parti-<br>cles per cubic foot | OSHA Z-3  |
|                 |            | TWA (Total)  | 10 mg/m3                                 | OSHA P0   |
|                 |            | TWA (Res-<br>pirable frac-<br>tion)                | 5 mg/m3                                  | OSHA P0   |
| Limestone       | 1317-65-3  | TWA (total dust)                                   | 15 mg/m3                                 | OSHA Z-1  |
|                 |            | TWA (respirable fraction)                          | 5 mg/m3                                  | OSHA Z-1  |
|                 |            | TWA (Total dust)                                   | 15 mg/m3                                 | OSHA P0   |
|                 |            | TWA (respir-<br>able dust<br>fraction)             | 5 mg/m3                                  | OSHA P0   |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

according to OSHA 1910.1200 Hazard Communication Standard



# Merkrete® 700 Premium Set

Revision Date 12/05/2023 Print Date 12/05/2023

#### Particles of nuisance dust

| Form of exposure    | Value type | Control parameters | Basis    |
|---------------------|------------|--------------------|----------|
| total dust          | TWA        | 15 mg/m3           | OSHA Z-3 |
| respirable fraction | TWA        | 5 mg/m3            | OSHA Z-3 |

**Engineering measures** : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommend-

ed or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk as-

sessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

Associations attains a facet

Avoid breathing dust.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder



Revision Date 12/05/2023 Print Date 12/05/2023

Color : gray, white

Odor : odorless

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : ca. 1.03 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Volatile organic compounds

(VOC) content

Not applicable



Print Date 12/05/2023 Revision Date 12/05/2023

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

tions

Possibility of hazardous reac- : Stable under recommended storage conditions.

No data available Conditions to avoid

Incompatible materials No data available

Hazardous decomposition

products

No decomposition if stored and applied as directed.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Not classified due to lack of data.

#### Skin corrosion/irritation

Causes severe burns.

## Serious eye damage/eye irritation

Causes serious eye damage.

## Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

## Respiratory sensitization

Not classified due to lack of data.

## Germ cell mutagenicity

Not classified due to lack of data.

## Carcinogenicity

May cause cancer by inhalation.

**IARC** Group 1: Carcinogenic to humans

14808-60-7 Quartz (SiO2)

(Silica dust, crystalline)

**OSHA** OSHA specifically regulated carcinogen

Quartz (SiO2) 14808-60-7

(crystalline silica)

**NTP** Known to be human carcinogen

> 14808-60-7 Quartz (SiO2)

(Silica, Crystalline (Respirable Size))



Revision Date 12/05/2023 Print Date 12/05/2023

## Reproductive toxicity

Not classified due to lack of data.

## STOT-single exposure

May cause respiratory irritation.

## STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Prolonged exposure can cause silicosis.

## **Aspiration toxicity**

Not classified due to lack of data.

#### **Further information**

#### **Product:**

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

## **SECTION 12. ECOLOGICAL INFORMATION**

## **Ecotoxicity**

No data available

#### Persistence and degradability

No data available

## **Bioaccumulative potential**

No data available

## Mobility in soil

No data available

#### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

Do not empty into drains; dispose of this material and its con-

tainer in a safe way.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.



Revision Date 12/05/2023 Print Date 12/05/2023

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

## **SECTION 14. TRANSPORT INFORMATION**

## **International Regulations**

**IATA-DGR** 

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

**Domestic regulation** 

**49 CFR** 

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

TSCA list : All chemical substances in this product are either listed as ac-

tive on the TSCA Inventory or are in compliance with a TSCA

Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

## **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

according to OSHA 1910.1200 Hazard Communication Standard



# Merkrete® 700 Premium Set

Revision Date 12/05/2023 Print Date 12/05/2023

## California Prop. 65



**WARNING:** This product can expose you to chemicals including Quartz (SiO2) >5µm, which is known to the State of California to cause cancer, and Portland Cement, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## **SECTION 16. OTHER INFORMATION**

## Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average
OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

## Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 12/05/2023

100000051846 US / Z8