



SECTION 1. IDENTIFICATION

Product name : Sika® MB Redline Part A

Company name : Sika Corporation
 201 Polito Avenue
 Lyndhurst, NJ 07071
 USA
 www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
 INTERNATIONAL: 703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H351 Suspected of causing cancer.

Precautionary Statements : **Prevention:**
 P201 Obtain special instructions before use.



P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P310 Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
bisphenol-A-(epichlorhydrin) epoxy resin	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	$\geq 70 - < 90$
benzyl alcohol	100-51-6	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2A; H319	$\geq 10 - < 20$
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318	$\geq 10 - < 20$



Solvent naphtha (petroleum), heavy arom.	64742-94-5	Skin Sens. 1; H317 STOT SE 3; H336 Asp. Tox. 1; H304	>= 1 - < 5
2-methylnaphthalene	91-57-6	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2A; H319	>= 1 - < 5
Naphtha (petroleum), heavy alkylate	64741-65-7	Flam. Liq. 3; H226 Eye Irrit. 2B; H320 Asp. Tox. 1; H304	>= 1 - < 5
naphthalene	91-20-3	Acute Tox. 4; H302 Carc. 2; H351	>= 0.1 - < 1
(R)-p-mentha-1,8-diene	5989-27-5	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.



Suspected of causing cancer.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.



Conditions for safe storage : Store in original container.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL
2-methylnaphthalene	91-57-6	TWA	0.5 ppm	ACGIH
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		TWA	10 ppm 50 mg/m ³	OSHA Z-1
		TWA	10 ppm 50 mg/m ³	OSHA P0
		STEL	15 ppm 75 mg/m ³	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection



Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: red
Odor	: aromatic
Odor Threshold	: No data available
pH	: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 212 °F / > 100 °C (Method: closed cup)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: 0.1 hpa
Relative vapor density	: No data available



Density	:	ca. 1.13 g/cm ³ (73 °F / 23 °C)
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	62 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

bisphenol-A-(epichlorhydrin) epoxy resin:

Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 20,000 mg/kg



benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist

1,4-bis(2,3 epoxypropoxy)butane:

Acute oral toxicity : LD50 Oral (Rat): 1,163 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Naphtha (petroleum), heavy alkylate:

Assessment : Repeated exposure may cause skin dryness or cracking.
 Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

IARC	Group 2B: Possibly carcinogenic to humans naphthalene	91-20-3
	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7
OSHA	Not applicable	
NTP	Reasonably anticipated to be a human carcinogen naphthalene	91-20-3

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

Further information**Product:**

Remarks : Titanium dioxide (13463-67-7)
 In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****bisphenol-A-(epichlorhydrin) epoxy resin:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
 Exposure time: 48 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h

naphthalene:**Persistence and degradability**

No data available

Bioaccumulative potential

No data available



Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 May be harmful to the environment if released in large quantities.
 Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 3082
 Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
 (bisphenol-A-(epichlorhydrin) epoxy resin)
 Class : 9
 Packing group : III
 Labels : Miscellaneous Dangerous Goods
 Packing instruction (cargo aircraft) : 964
 Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
 N.O.S.
 (bisphenol-A-(epichlorhydrin) epoxy resin)
 Class : 9
 Packing group : III
 Labels : 9
 EmS Code : F-A, S-F



Marine pollutant : yes

Domestic regulation

49 CFR

Not regulated as a dangerous good

DOT & Domestic Aircraft: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant.

IMDG: As per IMDG Chapter 3.3 Special Provision 188, Material is Not Regulated.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

: Skin corrosion or irritation
 Serious eye damage or eye irritation
 Respiratory or skin sensitization
 Carcinogenicity

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

naphthalene	91-20-3	>= 0.1 - < 1 %
-------------	---------	----------------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop 65



WARNING: Cancer and Reproductive Harm -
www.P65Warnings.ca.gov



SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	8-hr TWA

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 05/20/2019

100000014925

US / Z8