



SC 155, 175, 180, 390

EXTRUDABLE EPOXY MODELING PASTE

BUILDING TRUST



SC 155, 175, 180, 390

Extrudable epoxy modeling paste with 1" vertical hang and very good surface aspect used for large seamless models, mock-ups, master plugs, and composite tooling.

Main Features

- Single layer application (25-40 mins)
- Dimensional accuracy and stability
- Low density
- Low exotherm
- Seamless surface - no bond lines
- Minimal waste
- Easy to machine
- Creates chips, no dust
- Can be machined within 24 hours
- Low toxicity
- Reduced time in mold production

Markets

- Aerospace
- Architectural
- Automotive
- Marine
- Renewable Energy
- Transportation
- Wind

EXTRUDABLE EPOXY PASTE

Product	Density (lbs/ft ³)	Shore Hardness	Tg (°F)	CTE (ppm/ °F)
SC 155	34	51 D	140	49
SC 175	39	60 D	181	39
SC 180	50	62 D	180	43
SC 390	67	75 D	196	29

Our most current General Sales Conditions shall apply.
Please consult the Data Sheet prior to any use and processing.

SIKA ADVANCED RESINS **CUSTOMER SERVICE**
30800 Stephenson Highway (248) 588 2270
Madison Heights, MI 48071 Advanced.Resins@us.sika.com
(248) 577 0020
www.SikaAdvancedResins.us

BUILDING TRUST

