



BUILDING TRUST



PRODUCT DATA SHEET

ZAR® Wood Patch

Wood Patch Filler

DESCRIPTION

ZAR® Wood Patch is a ready-to-use latex patching compound containing treated pulverized wood to fill nail holes, repair cracks, gouges, chips, etc., in all types of wood. Special property allows ZAR® Wood Patch to accept stain more uniformly than other wood fillers.

USES

- **FILLS:** Cracks, dents, holes, gouges, broken edges, and chipped corners.
- **REPAIRS:** Toys, patterns, furniture, picture frames, most items made from wood.
- **REPLACES:** Rotted wood-carpentry mistakes.
- **MAKES:** Inlays, models, novelties, carved objects.

CHARACTERISTICS / ADVANTAGES

- Accepts stain uniformly
- Greatly diminishes the lighter area or "halo" effect surrounding the patch when patch requires a wood stain
- May be sanded, sawed or drilled
- Tintable
- Will accept paint, varnish, shellac, polyurethanes, & stains
- Can be used indoors & outdoors

PRODUCT DATA SHEET

ZAR® Wood Patch

September 2025, Version 01.01

020513030000000112

PRODUCT INFORMATION

Composition	Latex base				
Packaging	Size	PC/Case	Color	Order No.	Old Order No.
	3 fl.oz.	12	Red Oak	832514	31041
	0.5 pt.	6	Neutral	832548	30906
	3 fl.oz.	12	Neutral	832513	30941
	1 qt.	6	Neutral	832560	30912
	1 pt.	6	Neutral	832549	30911
	3 fl.oz.	12	Golden Oak	832515	31441
Shelf life	3 years in the original, unopened container.				
Storage conditions	Store in a cool, dry place. Avoid exposure to temperatures exceeding 90°F (32°C). Keep away from heat sources, sparks, open flames, and electrical equipment. Keep from freezing.				
Density	14.7 ± 0.3 (lbs./US gal)				
Solid content by mass	76.0 ± 0.1%				
Solid content by volume	57.2± 0.1%				
APPLICATION INFORMATION					
Coverage	Up to 56 cu.in./qt.				
	Note: Actual coverage will vary.				
Setting time	<ul style="list-style-type: none">▪ For latex stain or paint: 1½ - 2 hours▪ For oil base stain, paint, varnish, shellac or polyurethane: overnight Note: Maximum cure and dry time will be prolonged when slightly humid and damp,cool conditions prevail.				



BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

- Not for use on exterior wooden decks or other exterior horizontal surfaces.
- Do not use material when the material and/or air temperature is below 40°F.
- Inhalation: Remove to fresh air

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Remove all dirt, grease, oil and loose particles from the patch area. Dampen surfaces to be patched with water. Do not use when material and/or air temperature is below 40°F.

MIXING

Tinting: Use universal colorants or colors used in latex paints.

APPLICATION

To Use as a Wood Patching Compound for Cracks and Holes:

Apply with smooth edge non metallica finishing trowel, putty knife or use 3 oz. tube to apply patch directly into imperfection. Press compound tightly into place, building up patch slightly higher than surround area. Patches under ¼" wide and deep will usually require just one application. May be sanded after one hour. Deeper areas should be filled in layer allowing each layer to dry between applications. Sand after each layer has completely dried.

Allow overnight drying of patch before applying an oil base stain - 1½ to 2 hours before applying latex paint. All exterior applications must be top coated.

To Use as a Wood Filler for Open-Grained Woods Such as Oak and Mahogany:

Reduce ZAR® Wood Patch with water so that a creamy consistency is obtained. Apply against the grain so that the material fills the pores of the wood. Let set for 5-10 minutes and scrape off excess material in the direction of the grain with a non-metallic scraper. Allow to dry overnight. Sand lightly and apply ZAR Wood Stain and/or ZAR Polyurethane.

Staining:

Wipe off excess patching material with a damp cloth immediately after application. When dry, sand patch with medium grit sandpaper. Allow overnight drying before applying an oil base stain, paint, varnish, shellac or polyurethane - 1½ - 2 hours before applying a latex stain or paint. All exterior applications must be top-coated with a paint or solid color stain within 24 hours. Not for use on exterior wooden decks or other exterior horizontal surfaces.

PRODUCT DATA SHEET

ZAR® Wood Patch

September 2025, Version 01.01

020513030000000112



BUILDING TRUST



LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at www.zar.com or by calling SIKA's Technical Service Department at 1-800-272-3235, option 2. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAM-**

AGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-272-3235, option 2.

PRODUCT DATA SHEET

ZAR® Wood Patch

September 2025, Version 01.01

020513030000000112

