

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

### SECTION 1. IDENTIFICATION

Product name : SikaSet Waterplug Formerly MSeal 590 Industrial

Product code : 000000000055396807

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE  
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Serious eye damage/eye irritation : Category 1

Skin corrosion/irritation : Category 2

Carcinogenicity (Inhalation) : Category 1A (Lung)

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Kidney, Immune system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lung)

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



Version 1.2      Revision Date: 01/21/2021      SDS Number: 000000249750      Date of last issue: 01/04/2021  
Date of first issue: 05/11/2020

**Hazard Statements** : H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H350 May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.  
H373 May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

**Precautionary Statements** : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P271 Use only outdoors or in a well-ventilated area.  
P260 Do not breathe dust or mist.  
P202 Do not handle until all safety precautions have been read and understood.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash the contact area thoroughly after handling.

**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P310 Immediately call a POISON CENTER or doctor/ physician.

**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**  
P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**  
None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : modified cement mortar

#### Components

| Chemical name               | CAS-No.    | Concentration (% w/w) |
|-----------------------------|------------|-----------------------|
| Quartz (SiO <sub>2</sub> )  | 14808-60-7 | >= 25 - < 50          |
| Cement, portland, chemicals | 65997-15-1 | >= 20 - < 50          |
| Calcium dihydroxide         | 1305-62-0  | >= 1 - < 7            |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



Version 1.2      Revision Date: 01/21/2021      SDS Number: 000000249750      Date of last issue: 01/04/2021  
Date of first issue: 05/11/2020

|                                                               |            |                  |
|---------------------------------------------------------------|------------|------------------|
| Limestone                                                     | 1317-65-3  | $\geq 0.3 - < 5$ |
| Gypsum ( $\text{Ca}(\text{SO}_4) \cdot 2\text{H}_2\text{O}$ ) | 13397-24-5 | $\geq 0.3 - < 3$ |

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause cancer.  
Causes damage to organs through prolonged or repeated exposure if inhaled.  
May cause damage to organs through prolonged or repeated exposure.  
Prolonged or repeated inhalation of respirable crystalline silica (quartz) may result in silicosis.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

- Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)  
Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are sufficient.
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.  
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Neutralize with acid.  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation.  
Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Avoid formation of respirable particles.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



Version 1.2      Revision Date: 01/21/2021      SDS Number: 000000249750      Date of last issue: 01/04/2021  
Date of first issue: 05/11/2020

- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Containers should be stored tightly sealed in a dry place.
- Materials to avoid : Segregate from metals.  
Segregate from acids and bases.  
Segregate from oxidants.  
Segregate from foods and animal feeds.
- Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components          | CAS-No.   | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis                          |
|---------------------|-----------|----------------------------------|------------------------------------------------|--------------------------------|
| calcium carbonate   | 471-34-1  | REL value (Total)                | 10 mg/m3                                       | NIOSH                          |
|                     |           | REL value (Respirable)           | 5 mg/m3                                        | NIOSH                          |
|                     |           | PEL (Respirable fraction)        | 5 mg/m3                                        | 29 CFR 1910.1000 (Table Z-1)   |
|                     |           | PEL (Total dust)                 | 15 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1)   |
|                     |           | TWA (Respirable)                 | 5 mg/m3 (Calcium carbonate)                    | NIOSH REL                      |
|                     |           | TWA (total)                      | 10 mg/m3 (Calcium carbonate)                   | NIOSH REL                      |
| Calcium dihydroxide | 1305-62-0 | TWA value                        | 5 mg/m3                                        | ACGIHTLV                       |
|                     |           | REL value                        | 5 mg/m3                                        | NIOSH                          |
|                     |           | PEL (Respirable fraction)        | 5 mg/m3                                        | 29 CFR 1910.1000 (Table Z-1)   |
|                     |           | PEL (Total dust)                 | 15 mg/m3                                       | 29 CFR 1910.1000 (Table Z-1)   |
|                     |           | TWA value                        | 5 mg/m3                                        | 29 CFR 1910.1000 (Table Z-1-A) |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



Version 1.2      Revision Date: 01/21/2021      SDS Number: 000000249750      Date of last issue: 01/04/2021  
Date of first issue: 05/11/2020

|               |           |                                     |                     |                                |
|---------------|-----------|-------------------------------------|---------------------|--------------------------------|
|               |           | TWA                                 | 5 mg/m3             | ACGIH                          |
|               |           | TWA                                 | 5 mg/m3             | NIOSH REL                      |
|               |           | TWA (total dust)                    | 15 mg/m3            | OSHA Z-1                       |
|               |           | TWA (respirable fraction)           | 5 mg/m3             | OSHA Z-1                       |
|               |           | TWA                                 | 5 mg/m3             | OSHA P0                        |
| calcium oxide | 1305-78-8 | TWA value                           | 2 mg/m3             | ACGIH TLV                      |
|               |           | REL value                           | 2 mg/m3             | NIOSH                          |
|               |           | PEL                                 | 5 mg/m3             | 29 CFR 1910.1000 (Table Z-1)   |
|               |           | TWA value                           | 5 mg/m3             | 29 CFR 1910.1000 (Table Z-1-A) |
|               |           | TWA                                 | 2 mg/m3             | ACGIH                          |
|               |           | TWA                                 | 2 mg/m3             | NIOSH REL                      |
|               |           | TWA                                 | 5 mg/m3             | OSHA Z-1                       |
|               |           | TWA                                 | 5 mg/m3             | OSHA P0                        |
| Iron oxide    | 1309-37-1 | TWA value (Respirable fraction)     | 5 mg/m3             | ACGIH TLV                      |
|               |           | REL value (Dust and fume)           | 5 mg/m3 (iron (Fe)) | NIOSH                          |
|               |           | PEL (fumes/smoke)                   | 10 mg/m3            | 29 CFR 1910.1000 (Table Z-1)   |
|               |           | TWA value (fumes/smoke)             | 10 mg/m3            | 29 CFR 1910.1000 (Table Z-1-A) |
|               |           | TWA (Respirable particulate matter) | 5 mg/m3             | ACGIH                          |
|               |           | TWA (dust and fume)                 | 5 mg/m3 (Iron)      | NIOSH REL                      |
|               |           | TWA (Fumes)                         | 10 mg/m3            | OSHA Z-1                       |
|               |           | TWA (total dust)                    | 15 mg/m3            | OSHA Z-1                       |
|               |           | TWA (respirable fraction)           | 5 mg/m3             | OSHA Z-1                       |
|               |           | TWA (Fumes)                         | 10 mg/m3            | OSHA P0                        |
| Limestone     | 1317-65-3 | REL value (Respirable)              | 5 mg/m3             | NIOSH                          |
|               |           | REL value (Total)                   | 10 mg/m3            | NIOSH                          |
|               |           | PEL (Respirable fraction)           | 5 mg/m3             | 29 CFR 1910.1000 (Table Z-1)   |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



Version 1.2      Revision Date: 01/21/2021      SDS Number: 000000249750      Date of last issue: 01/04/2021  
Date of first issue: 05/11/2020

|                       |            |                                 |                              |                                |
|-----------------------|------------|---------------------------------|------------------------------|--------------------------------|
|                       |            | PEL (Total dust)                | 15 mg/m3                     | 29 CFR 1910.1000 (Table Z-1)   |
|                       |            | TWA value (Respirable fraction) | 5 mg/m3                      | 29 CFR 1910.1000 (Table Z-1-A) |
|                       |            | TWA value (Total dust)          | 15 mg/m3                     | 29 CFR 1910.1000 (Table Z-1-A) |
|                       |            | TWA (total dust)                | 15 mg/m3                     | OSHA Z-1                       |
|                       |            | TWA (respirable fraction)       | 5 mg/m3                      | OSHA Z-1                       |
|                       |            | TWA (Total dust)                | 15 mg/m3                     | OSHA P0                        |
|                       |            | TWA (respirable dust fraction)  | 5 mg/m3                      | OSHA P0                        |
|                       |            | TWA (Respirable)                | 5 mg/m3 (Calcium carbonate)  | NIOSH REL                      |
|                       |            | TWA (total)                     | 10 mg/m3 (Calcium carbonate) | NIOSH REL                      |
| Gypsum (Ca(SO4).2H2O) | 13397-24-5 | TWA value (Inhalable fraction)  | 10 mg/m3                     | ACGIHTLV                       |
|                       |            | REL value (Respirable)          | 5 mg/m3                      | NIOSH                          |
|                       |            | REL value (Total)               | 10 mg/m3                     | NIOSH                          |
|                       |            | PEL (Total dust)                | 15 mg/m3                     | 29 CFR 1910.1000 (Table Z-1)   |
|                       |            | PEL (Respirable fraction)       | 5 mg/m3                      | 29 CFR 1910.1000 (Table Z-1)   |
|                       |            | TWA value (Total dust)          | 15 mg/m3                     | 29 CFR 1910.1000 (Table Z-1-A) |
|                       |            | TWA value (Respirable fraction) | 5 mg/m3                      | 29 CFR 1910.1000 (Table Z-1-A) |
|                       |            | TWA (Respirable)                | 5 mg/m3                      | NIOSH REL                      |
|                       |            | TWA (total)                     | 10 mg/m3                     | NIOSH REL                      |
|                       |            | TWA (total dust)                | 15 mg/m3                     | OSHA Z-1                       |
|                       |            | TWA (respirable fraction)       | 5 mg/m3                      | OSHA Z-1                       |
|                       |            | TWA (Total dust)                | 15 mg/m3                     | OSHA P0                        |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



Version 1.2      Revision Date: 01/21/2021      SDS Number: 000000249750      Date of last issue: 01/04/2021  
Date of first issue: 05/11/2020

|                             |            |                                     |                               |                                |
|-----------------------------|------------|-------------------------------------|-------------------------------|--------------------------------|
|                             |            | TWA (respirable dust fraction)      | 5 mg/m3                       | OSHA P0                        |
|                             |            | TWA (Inhalable particulate matter)  | 10 mg/m3 (Calcium)            | ACGIH                          |
| Quartz (SiO2)               | 14808-60-7 | TWA value (Respirable fraction)     | 0.025 mg/m3                   | ACGIHTLV                       |
|                             |            | TWA value                           | 0.05 mg/m3 (Respirable dust)  | 29 CFR 1910.1001-1050          |
|                             |            | OSHA Action level                   | 0.025 mg/m3 (Respirable dust) | 29 CFR 1910.1001-1050          |
|                             |            | REL value (Respirable dust)         | 0.05 mg/m3                    | NIOSH                          |
|                             |            | TWA (Respirable dust)               | 0.05 mg/m3                    | OSHA Z-1                       |
|                             |            | TWA (respirable)                    | 10 mg/m3 / %SiO2+2            | OSHA Z-3                       |
|                             |            | TWA (respirable)                    | 250 mppcf / %SiO2+5           | OSHA Z-3                       |
|                             |            | TWA (respirable dust fraction)      | 0.1 mg/m3                     | OSHA P0                        |
|                             |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica)          | ACGIH                          |
|                             |            | PEL (respirable)                    | 0.05 mg/m3                    | OSHA CARC                      |
|                             |            | TWA (Respirable dust)               | 0.05 mg/m3 (Silica)           | NIOSH REL                      |
| Cement, portland, chemicals | 65997-15-1 | TWA value (Respirable fraction)     | 1 mg/m3                       | ACGIHTLV                       |
|                             |            | REL value (Total)                   | 10 mg/m3                      | NIOSH                          |
|                             |            | REL value (Respirable)              | 5 mg/m3                       | NIOSH                          |
|                             |            | PEL (Total dust)                    | 15 mg/m3                      | 29 CFR 1910.1000 (Table Z-1)   |
|                             |            | PEL (Respirable fraction)           | 5 mg/m3                       | 29 CFR 1910.1000 (Table Z-1)   |
|                             |            | TWA value (Total dust)              | 10 mg/m3                      | 29 CFR 1910.1000 (Table Z-1-A) |
|                             |            | TWA value                           | 5 mg/m3                       | 29 CFR                         |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



Version 1.2      Revision Date: 01/21/2021      SDS Number: 000000249750      Date of last issue: 01/04/2021  
Date of first issue: 05/11/2020

|                            |            |                                     |                                                |                              |
|----------------------------|------------|-------------------------------------|------------------------------------------------|------------------------------|
|                            |            | (Respirable fraction)               |                                                | 1910.1000 (Table Z-1-A)      |
|                            |            | TWA value                           | 50 millions of particles per cubic foot of air | 29 CFR 1910.1000 (Table Z-3) |
|                            |            | TWA (Respirable particulate matter) | 1 mg/m <sup>3</sup>                            | ACGIH                        |
|                            |            | TWA (Respirable)                    | 5 mg/m <sup>3</sup>                            | NIOSH REL                    |
|                            |            | TWA (total)                         | 10 mg/m <sup>3</sup>                           | NIOSH REL                    |
|                            |            | TWA (total dust)                    | 15 mg/m <sup>3</sup>                           | OSHA Z-1                     |
|                            |            | TWA (respirable fraction)           | 5 mg/m <sup>3</sup>                            | OSHA Z-1                     |
|                            |            | TWA (Total dust)                    | 10 mg/m <sup>3</sup>                           | OSHA P0                      |
|                            |            | TWA (respirable dust fraction)      | 5 mg/m <sup>3</sup>                            | OSHA P0                      |
|                            |            | TWA (Dust)                          | 50 Million particles per cubic foot            | OSHA Z-3                     |
| Quartz (SiO <sub>2</sub> ) | 14808-60-7 | TWA value (Respirable fraction)     | 0.025 mg/m <sup>3</sup>                        | ACGIH TLV                    |
|                            |            | TWA value                           | 0.05 mg/m <sup>3</sup> (Respirable dust)       | 29 CFR 1910.1001-1050        |
|                            |            | OSHA Action level                   | 0.025 mg/m <sup>3</sup> (Respirable dust)      | 29 CFR 1910.1001-1050        |
|                            |            | REL value (Respirable dust)         | 0.05 mg/m <sup>3</sup>                         | NIOSH                        |
|                            |            | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup>                         | OSHA Z-1                     |
|                            |            | TWA (respirable)                    | 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2    | OSHA Z-3                     |
|                            |            | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5               | OSHA Z-3                     |
|                            |            | TWA (respirable dust fraction)      | 0.1 mg/m <sup>3</sup>                          | OSHA P0                      |
|                            |            | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup> (Silica)               | ACGIH                        |
|                            |            | PEL (respirable)                    | 0.05 mg/m <sup>3</sup>                         | OSHA CARC                    |
|                            |            | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup> (Silica)                | NIOSH REL                    |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

**Engineering measures** : Provide local exhaust ventilation to maintain recommended P.E.L.

### Personal protective equipment

**Respiratory protection** : Breathing protection if dusts are formed.  
Wear a NIOSH-certified (or equivalent) particulate respirator.

**Hand protection**

**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Protective measures** : Avoid contact with the skin, eyes and clothing.  
Avoid inhalation of dusts.  
In order to prevent contamination while handling, closed working clothes and working gloves should be used.  
Handle in accordance with good building materials hygiene and safety practice.

**Hygiene measures** : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : powder

**Color** : gray

**Odor** : odorless

**pH** : approx. 12 - 13 (approx. 68 °F / 20 °C)  
(as aqueous suspension)

**Melting point** : No data available

**Flash point** : No data available

**Evaporation rate** : The product is a non-volatile solid.

**Flammability (solid, gas)** : not flammable

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

|                                        |                                                                   |
|----------------------------------------|-------------------------------------------------------------------|
| Vapor pressure                         | : No data available                                               |
| Relative vapor density                 | : The product is a non-volatile solid.                            |
| Bulk density                           | : approx. 1,800 - 2,400 kg/m <sup>3</sup>                         |
| Solubility(ies)                        |                                                                   |
| Water solubility                       | : dispersible (68 °F / 20 °C)                                     |
| Solubility in other solvents           | : No applicable information available.                            |
| Partition coefficient: n-octanol/water | : Not applicable                                                  |
| Decomposition temperature              | : No decomposition if stored and handled as prescribed/indicated. |
| Viscosity                              |                                                                   |
| Viscosity, dynamic                     | : Not applicable                                                  |
| Viscosity, kinematic                   | : No applicable information available.                            |
| Explosive properties                   | : Not explosive<br>Not explosive                                  |
| Oxidizing properties                   | : not fire-propagating                                            |
| Self-heating substances                | : No data available                                               |
| Sublimation point                      | : No applicable information available.                            |
| Molecular weight                       | : No data available                                               |

### SECTION 10. STABILITY AND REACTIVITY

|                                    |                                                                                      |
|------------------------------------|--------------------------------------------------------------------------------------|
| Reactivity                         | : No decomposition if stored and applied as directed.                                |
| Chemical stability                 | : No decomposition if stored and applied as directed.                                |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed.                                |
| Conditions to avoid                | : See SDS section 7 - Handling and storage.                                          |
| Incompatible materials             | : Strong bases<br>Strong acids                                                       |
| Hazardous decomposition products   | : No hazardous decomposition products if stored and handled as prescribed/indicated. |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Product:

Remarks : May cause irreversible eye damage.

#### Respiratory or skin sensitization

##### Skin sensitization

Not classified based on available information.

##### Respiratory sensitization

Not classified based on available information.

#### Product:

Remarks : Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

May cause cancer.

#### Reproductive toxicity

Not classified based on available information.

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.  
May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

#### Aspiration toxicity

Not classified based on available information.

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

### Further information

#### Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Not applicable for inorganic substances.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: The product will not be readily bioavailable due to its consistency and insolubility in water.

### Mobility in soil

#### Product:

Distribution among environmental compartments : Remarks: Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected. The substance will not evaporate into the atmosphere from the water surface.

### Other adverse effects

#### Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into waterways or sewer systems without proper authorization.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### US State Regulations

##### Pennsylvania Right To Know

|                                                 |            |
|-------------------------------------------------|------------|
| Calcium dihydroxide                             | 1305-62-0  |
| Limestone                                       | 1317-65-3  |
| Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O) | 13397-24-5 |
| Cement, portland, chemicals                     | 65997-15-1 |
| crystalline silica                              | 14808-60-7 |

##### New Jersey Right To Know

|                             |            |
|-----------------------------|------------|
| Calcium dihydroxide         | 1305-62-0  |
| Limestone                   | 1317-65-3  |
| Quartz (SiO <sub>2</sub> )  | 14808-60-7 |
| Cement, portland, chemicals | 65997-15-1 |

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|                |                              |                             |                                                                   |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|
| Version<br>1.2 | Revision Date:<br>01/21/2021 | SDS Number:<br>000000249750 | Date of last issue: 01/04/2021<br>Date of first issue: 05/11/2020 |
|----------------|------------------------------|-----------------------------|-------------------------------------------------------------------|

### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO<sub>2</sub>), which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.


DSL : This product contains the following components that are not on the Canadian DSL nor NDSL.

Trisodium citrate

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

|                 |  |  |
|-----------------|--|--|
| HEALTH          |  |  |
| FLAMMABILITY    |  |  |
| PHYSICAL HAZARD |  |  |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000

29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 01/04/2021  |
| 1.2     | 01/21/2021     | 000000249750 | Date of first issue: 05/11/2020 |

|                                            |   |                                                                                           |
|--------------------------------------------|---|-------------------------------------------------------------------------------------------|
| NIOSH                                      | : | NIOSH Pocket Guide to Chemical Hazards (US)                                               |
| NIOSH REL                                  | : | USA. NIOSH Recommended Exposure Limits                                                    |
| OSHA CARC                                  | : | OSHA Specifically Regulated Chemicals/Carcinogens                                         |
| OSHA P0                                    | : | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000                             |
| OSHA Z-1                                   | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants          |
| OSHA Z-3                                   | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts                        |
| 29 CFR 1910.1000 (Table Z-1-A) / TWA value | : | Time Weighted Average (TWA):                                                              |
| 29 CFR 1910.1000 (Table Z-1) / PEL         | : | Permissible exposure limit                                                                |
| 29 CFR 1910.1000 (Table Z-3) / TWA value   | : | Time Weighted Average (TWA):                                                              |
| 29 CFR 1910.1001-1050 / OSHA Action level  | : | OSHA Action level:                                                                        |
| 29 CFR 1910.1001-1050 / TWA value          | : | Time Weighted Average (TWA):                                                              |
| ACGIH / TWA                                | : | 8-hour, time-weighted average                                                             |
| ACGIH TLV / TWA value                      | : | Time Weighted Average (TWA):                                                              |
| NIOSH / REL value                          | : | Recommended exposure limit (REL):                                                         |
| NIOSH REL / TWA                            | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA CARC / PEL                            | : | Permissible exposure limit (PEL)                                                          |
| OSHA P0 / TWA                              | : | 8-hour time weighted average                                                              |
| OSHA Z-1 / TWA                             | : | 8-hour time weighted average                                                              |
| OSHA Z-3 / TWA                             | : | 8-hour time weighted average                                                              |

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and

# SAFETY DATA SHEET

## SikaSet Waterplug Formerly MSeal 590 Industrial



|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 01/04/2021  |
| 1.2     | 01/21/2021     | 000000249750 | Date of first issue: 05/11/2020 |

Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/21/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN