

SikaProof® FixTape-50

Double-sided Adhesive Tape, Butyl Rubber Based

Description	SikaProof® FixTape-50 is a double-sided adhesive tape, consists of a butyl rubber adhesive that is covered with a release liner.
Where to Use	SikaProof® FixTape-50 is used for different detailing application of the SikaProof® A system.
Advantages	<ul style="list-style-type: none"> ■ High adhesion of the butyl rubber adhesive ■ High durability ■ Easy and fast to install
Typical Data	
Packaging	5 rolls, packed in one cardboard box Each roll is 50 mm x 20 m
Coverage	50 mm x 20 m roll

Appearance: White release liner over black butyl rubber adhesive

Dimensions

Width: 50 mm

Length: 20 m

Thickness: 1.50 mm

System Information

System Components:

SikaProof® ExTape-150 and SikaProof® Tape-150 A are self-adhesive tapes to adhere joints, connections and details in the SikaProof® A sheet membrane waterproofing system.

SikaProof® A-05, membrane in rolls of widths 1.0 or 2.0 m

SikaProof® A-08, membrane in rolls of widths 1.0 or 2.0 m

SikaProof® A-12, membrane in rolls of widths 1.0 or 2.0 m

SikaProof® Ex Tape-150, self-adhesive tape for external jointing, based on butylrubber, in 150 mm width

SikaProof® Tape-150 A, self-adhesive tape for internal jointing, based on a polyacrylate-adhesive, in 150 mm width



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://usa.sika.com/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

Waterproofing

How to Use

Surface Prep

The contact surfaces must be dry, clean and free of materials that could impair adhesion.

Application

SikaProof® FixTape-50 is a cold-applied double-sided adhesive tape for different detailing application. For further, more detailed information about the installation method, please refer to the SikaProof® A membrane Product Data Sheet and the Method Statement.

Limitations

The SikaProof® A system must only be installed by trained and approved Sika contractors. SikaProof® FixTape-50 is not UV stabilized and cannot be installed on structures permanently exposed to UV light and weathering. Do not apply the SikaProof® FixTape-50 during continuous or prolonged rainfall.

Substrate Temperature: +5°C min. / + 35°C max. (+40°F min. / +95°F max.)

Ambient air temperature: +5°C min. / + 35 °C max. (+40°F min. / +95°F max.)

Shelf Life

SikaProof® FixTape-50 rolls have a shelf-life of 24 months from date of production if stored properly in unopened, undamaged, original packaging, in a horizontal position, in dry conditions and at temperatures between +5°C (+40°F) and +30°C (+85°F). Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sika Greenstreak Office
3400 Tree Court Industrial Blvd.
St. Louis, MO 63122
Tel: (800) 325-9504
Fax: (636) 225-2049
usa.sika.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: (201) 933-8800
Fax: (201) 933-6225
usa.sika.com

Sika Canada Inc.
601, Delmar Avenue
Pointe-Claire, QC H9R 4A9
Phone: (514) 697-2610
Fax: (514) 697-3087
can.sika.com

The Sika logo consists of the word "Sika" in a bold, yellow, sans-serif font, set against a red triangular background. A registered trademark symbol (®) is located to the right of the logo.

PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://USA.SIKA.COM/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.