

# Plastiment®

## Water Reducing and Retarding Admixture

<b>Description</b>	Plastiment® is a water-reducing and retarding admixture. Plastiment® meets the requirements of ASTM C-494 Types B and D and AASHTO M194 Types B and D admixtures.
<b>Applications</b>	Plastiment® is recommended for use whenever high quality concrete with predictable and controlled set times is desired. Use in flatwork and horizontal or vertical slipform placements where a superior surface finish is required.
<b>Benefits</b>	<p>Plastiment® is highly effective in hot weather concreting to offset the accelerating effects of high ambient temperatures by slowing the hydration reaction and controlling the hydration heat. Concrete workability is enhanced and a superior surface finish is obtained. In mass concrete pours Plastiment® controls temperature rise and reduces the risk of thermal cracking.</p> <ul style="list-style-type: none"><li>■ Initial set times are delayed, allowing time for proper placement and finishing without cold joints in hot weather conditions.</li><li>■ Plastiment® increases concrete density and delivers increased early and ultimate, compressive and flexural strengths.</li><li>■ For flatwork applications Plastiment® acts as a finishing aid, workability is improved, bleeding is controlled and a superior surface finish is obtained.</li><li>■ Lower water cement ratios provide decreased permeability and increased durability.</li><li>■ Plastiment® can be used to retard concrete during the hot weather concreting.</li></ul> <p>Refer to ACI 305R Hot Weather Concreting for more information. Plastiment® does not contain no calcium chloride or any other intentionally added chlorides.</p>
<b>How to Use</b>	
<b>Dosage</b>	Dosage rates of 2-4 fl.oz. / 100 lbs. (130-260 ml / 100 kg) cement are recommended for general concrete applications. Where extended retardation is required dosage may be increased. Please contact your local Sika representative for more information and assistance.

Concrete



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://usa.sika.com/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

<b>Mixing</b>	<p>Add Plastiment® at the concrete plant. Measure required quantity manually or by automated dispenser. Add into the water line at the batch plant or directly into the concrete at the end of the mixing cycle.</p> <p>When used in combination with other admixtures, care must be taken to dispense each admixture separately into the mix. Do not mix with dry cement.</p> <p><b>Combination with Other Admixtures:</b> Plastiment® works effectively as a single admixture or in combination with other admixtures in the Sika system.</p>
<b>Packaging</b>	Plastiment® is available in 55 gallon drums (208 liter), 275 gallon totes (1040 liters) and bulk delivery.
<b>Storage and Shelf Life</b>	<p>Plastiment® should be stored at above 30°F (-1°C). If frozen, thaw and agitate thoroughly to return to normal state before use.</p> <p>Shelf life when stored in dry warehouse conditions between 50°F and 80°F (10°C- 27°C) is one year minimum.</p>
<b>Typical Data</b>	
<b>Appearance</b>	Fluorescent Green/Brown Liquid
<b>Specific Gravity</b>	Approx. 1.18

**KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY**

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

**Sika Corporation**  
 201 Polito Avenue  
 Lyndhurst, NJ 07071  
 Phone: (201) 933-8800  
 Fax: (201) 933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Canada Inc.**  
 601, Delmar Avenue  
 Pointe-Claire, QC H9R 4A9  
 Phone: (514) 697-2610  
 Fax: (514) 697-3087  
[can.sika.com](http://can.sika.com)

**Regional Information and Sales Centers.** For the location of your nearest Sika representative, contact your regional center.

**U.S. :**  
**Northeast:** Fairless Hills, PA, Phone: (215) 295-6600  
**South East:** Conyers, GA, Phone: (770) 760-1300  
**Western Region:** Santa Fe Springs, CA, Phone: (972) 289-6480  
**North Central:** Ottawa, IL 61350, Phone: (815) 431-1080  
**South Central:** Mesquite, TX, Phone: (972) 289-6480

**Canada:**  
**Ontario:** Mississauga, ON, Phone: (905) 795-3177  
**Alberta:** Edmonton, AB, Phone: (780) 486-6111

Quality Certification Numbers: Lyndhurst: FM 69711 (ISO 9000), FM 70421 (QS 9000), Marion: FM 69715, Kansas City: FM 69107, Santa Fe Springs: FM 69408



**PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://USA.SIKA.COM/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.**