

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0 Revision Date: 03/15/2021 SDS Number: 960000009295 Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

SECTION 1. IDENTIFICATION

Product name : Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE

Product code : 00000000058407884

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Sealant

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization : Category 1

Reproductive toxicity : Category 1B

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : The image shows two GHS hazard pictograms side-by-side. The first is a red diamond with a black silhouette of a person with a starburst on their chest, representing Health Hazard. The second is a red diamond with a black exclamation mark, representing Irritant or Harmful.

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0 Revision Date: 03/15/2021 SDS Number: 960000009295 Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Preparation based on:
polymers
inorganic compounds

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 30 - < 50
Titanium dioxide	13463-67-7	>= 1 - < 5
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	>= 0.1 - < 1
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	>= 0.1 - < 1
Carbon black	1333-86-4	>= 0.1 - < 1
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	>= 0.1 - < 1
dibutyltin dilaurate	77-58-7	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.
Immediately remove contaminated clothing.

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0	Revision Date: 03/15/2021	SDS Number: 960000009295	Date of last issue: 01/26/2021 Date of first issue: 01/26/2021
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

- If inhaled : Keep patient calm, remove to fresh air.
If symptoms persist, seek medical advice.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
May damage fertility or the unborn child.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0 Revision Date: 03/15/2021 SDS Number: 960000009295 Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

- Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wear eye/face protection.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Pick up with suitable appliance and dispose of.
Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.
- Advice on safe handling : Avoid inhalation of dusts/mists/vapours.
Avoid skin contact.
Ensure adequate ventilation.
No special measures necessary provided product is used correctly.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version
2.0

Revision Date:
03/15/2021

SDS Number:
960000009295

Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Carbon black	1333-86-4	TWA value (Inhalable fraction)	3 mg/m3	ACGIHTLV
		PEL	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	3.5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		REL value	0.1 mg/m3 (Polycyclic aromatic hydrocarbons (PAH))	NIOSH
		TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m3 (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m3 (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m3	NIOSH

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0 Revision Date: 03/15/2021 SDS Number: 960000009295 Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

			(tin (Sn))	
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.
Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).
When using do not eat or drink.

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0	Revision Date: 03/15/2021	SDS Number: 960000009295	Date of last issue: 01/26/2021 Date of first issue: 01/26/2021
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	various
Odor	:	mild, aromatic
Odor Threshold	:	not determined
pH	:	Not applicable
Melting point	:	Not applicable
Boiling point/boiling range	:	Not applicable
Flash point	:	155.5 °F / 68.6 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	The product is not flammable.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	11.4 lb/gal
Solubility(ies)		
Water solubility	:	insoluble (59 °F / 15 °C)
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	8,000 poise

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0	Revision Date: 03/15/2021	SDS Number: 960000009295	Date of last issue: 01/26/2021 Date of first issue: 01/26/2021
----------------	------------------------------	-----------------------------	-------------------------------------------------------------------

Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0 Revision Date: 03/15/2021 SDS Number: 960000009295 Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans	
	Carbon black	1333-86-4

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

dibutyltin dilaurate:

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version 2.0 Revision Date: 03/15/2021 SDS Number: 960000009295 Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

M-Factor (Acute aquatic toxicity) : 1

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available.
Discharge into the environment must be avoided.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2021
2.0	03/15/2021	960000009295	Date of first issue: 01/26/2021

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

Limestone	1317-65-3
Di-isononylphthalate	28553-12-0
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	68515-48-0
Titanium dioxide	13463-67-7
1,2,4-trimethylbenzene	95-63-6
cumene	98-82-8
xylene	1330-20-7
methanol	67-56-1

New Jersey Right To Know

Limestone	1317-65-3
Titanium dioxide	13463-67-7
Carbon black	1333-86-4

California Prop. 65

WARNING: This product can expose you to chemicals including Di-isononylphthalate, which is/are known to the State of California to cause cancer, and 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains the following components that are not on the Canadian DSL nor NDSL.

Proprietary Polymer

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE




Version
2.0

Revision Date:
03/15/2021


SDS Number:
960000009295

Date of last issue: 01/26/2021
Date of first issue: 01/26/2021

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	:	OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	:	OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	:	American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	:	NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / TWA value	:	Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	:	Permissible exposure limit
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIHTLV / STEL value	:	Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	:	Time Weighted Average (TWA):
NIOSH / REL value	:	Recommended exposure limit (REL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2021
2.0	03/15/2021	960000009295	Date of first issue: 01/26/2021

Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/15/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU

SAFETY DATA SHEET

Sikaflex HY 35 special bronze Formerly MSeal HY 35 SPEC BRONZE



Version	Revision Date:	SDS Number:	Date of last issue: 01/26/2021
2.0	03/15/2021	960000009295	Date of first issue: 01/26/2021

EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN