

Print Date 03/24/2025

#### **SECTION 1. IDENTIFICATION**

Product name	:	Sika <sup>®</sup> Ucrete <sup>®</sup> NA Part 2
Company name	:	Sika Corporation
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Inhalation)	:	Category 4
Skin irritation	:	Category 2
Eye irritation	:	Category 2B
Respiratory sensitization	:	Category 1
Skin sensitization	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure (Inhala- tion)	:	Category 2
Other hazards		

GHS label elements



Revision Date 03/24/2025	Print Date 03/24/2025
Hazard pictograms :	
Signal Word :	Danger
Hazard Statements :	<ul> <li>H315 + H320 Causes skin and eye irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H332 Harmful if inhaled.</li> <li>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.</li> <li>H335 May cause respiratory irritation.</li> <li>H373 May cause damage to organs through prolonged or repeated exposure if inhaled.</li> </ul>
Precautionary Statements :	<ul> <li>Prevention:</li> <li>P260 Do not breathe mist or vapors.</li> <li>P264 Wash skin thoroughly after handling.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P272 Contaminated work clothing must not be allowed out of the workplace.</li> <li>P280 Wear protective gloves.</li> <li>P284 Wear respiratory protection.</li> </ul>
	<ul> <li>Response:</li> <li>P302 + P352 IF ON SKIN: Wash with plenty of water.</li> <li>P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.</li> <li>P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.</li> <li>P337 + P313 If eye irritation persists: Get medical advice/ attention.</li> <li>P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.</li> <li>P362 + P364 Take off contaminated clothing and wash it before reuse.</li> <li>Storage:</li> <li>P403 + P233 Store in a well-ventilated place. Keep container tightly closed.</li> </ul>
	P405 Store locked up. <b>Disposal:</b> P501 Dispose of contents/ container to an approved waste dis- posal plant.
	2/13



#### Revision Date 03/24/2025

Print Date 03/24/2025

#### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%. None known.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Mixtures**

#### Components

Chemical name	CAS No./Unique ID	Classification	Concentration (% w/w)
4,4'-methylenediphenyl diisocyanate	101-68-8	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 45 - <= 70
Diphenylmethanediisocyanate, iso- meres and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 15 - <= 40
o-(p-isocyanatobenzyl)phenyl isocy- anate	5873-54-1	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2B; H320 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 STOT RE 2; H373	>= 10 - <= 30

Actual concentration is withheld as a trade secret

#### SECTION 4. FIRST AID MEASURES

General advice	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in atter ance.	nd-
If inhaled	Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.	



Revision Date 03/24/2025		Print Date 03/24/2025
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	:	irritant effects sensitizing effects Asthmatic appearance Cough Respiratory disorder Allergic reactions Headache Causes skin and eye irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure if inhaled.
Notes to physician	:	Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system.



Revision Date 03/24/2025		Print Date 03/24/2025
		If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
SECTION 7. HANDLING AND ST	OR	AGE
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	<ul> <li>Avoid formation of aerosol.</li> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Provide sufficient air exchange and/or exhaust in work rooms.</li> <li>Follow standard hygiene measures when handling chemical products.</li> </ul>
Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
4,4'-methylenediphenyl diiso- cyanate	101-68-8	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm	ACGIH
Diphenylmethanediisocyanate,	9016-87-9	С	0.02 ppm	OSHA Z-1

#### Ingredients with workplace control parameters



#### Revision Date 03/24/2025

#### Print Date 03/24/2025

isomeres and homologues			0.2 mg/m3	
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm	ACGIH
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		С	0.02 ppm 0.2 mg/m3	OSHA P0
		TWA	0.005 ppm	ACGIH

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures :	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend- ed or statutory limits.
Personal protective equipment	
Respiratory protection :	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.
	The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary.
Eye protection :	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection :	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hygiene measures :	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.



Revision Date 03/24/2025

Print Date 03/24/2025

Appearance	:	liquid
Color	:	amber
Odor	:	musty
Odor Threshold	:	No data available
рН	:	Not applicable
Melting point/ range / Freez-	:	No data available
ing point Boiling point/boiling range	:	No data available
Flash point	:	424 °F / 218 °C (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.01 hpa
Relative vapor density	:	No data available
Density	:	1.2 g/cm3
Solubility(ies) Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm2/s (104 °F / 40 °C)



Revision Date 03/24/2025		Print Date 03/24/2025		
Explosive properties	:	No data available		
Oxidizing properties	:	No data available		
Volatile organic compounds (VOC) content	:	44 g/l Sika® Ucrete® NA Part 1 + Part 2 + Sika® Ucrete® HS22 NA Part 3 Combined.		
		44 g/l Sika® Ucrete® NA Part 1 + Part 2 + Sika® Ucrete® HS22 NA Part 3 + Sika® Ucrete® Accelerator Combined.		
		5 g/l Sika® Ucrete® NA Part 1 + Part 2 + Sika® Ucrete® HS24 NA Part 3 Combined.		
		5 g/l Sika® Ucrete® NA Part 1 + Part 2 + Sika® Ucrete® HS24 NA Part 3 + Sika® Ucrete® Accelerator Combined.		
		5 g/l Sika® Ucrete® NA Part 1 + Part 2 + Sika® Ucrete® RG29 NA Part 3 Combined.		
		13 g/l Sika® Ucrete® NA Part 1 + Part 2 + Sika® Ucrete® TC31 NA Part 3 Combined.		
		1 g/l Sika® Ucrete® UD 200 Part 1 + Part 2 + Sika® Ucrete® UD 200 Part 3 Combined.		
		1 g/l Sika® Ucrete® UD 200 Part 1 + Part 2 + Sika® Ucrete® UD 200 Part 3 + Sika® Ucrete® Accelerator Combined.		
		1 g/l Sika® Ucrete® UD 200 Part 1 + Part 2 + Sika® Ucrete® UD 200 SR Part 3 Combined.		
		1 g/l Sika® Ucrete® UD 200 Part 1 + Part 2 + Sika® Ucrete® UD 200 SR Part 3 + Sika® Ucrete® Accelerator Combined.		
		1 g/l Sika® Ucrete® UD 200 Part 1 + Part 2 + Sika® Ucrete® IF Part 3 Combined.		
		1 g/l Sika® Ucrete® UD 200 Part 1 + Part 2 + Sika® Ucrete® IF		
	8 / 13			



#### Revision Date 03/24/2025

Print Date 03/24/2025

Part 3 + Sika® Ucrete® Accelerator Combined.

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity Harmful if inhaled. **Components:** 4,4'-methylenediphenyl diisocyanate: Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 : LC50: 1.5 mg/l Acute inhalation toxicity Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment Diphenylmethanediisocyanate, isomeres and homologues: : LD50 Oral (Rat): > 10,000 mg/kg Acute oral toxicity Acute inhalation toxicity : LC50: 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgment Assessment: The component/mixture is moderately toxic after short term inhalation. Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg



#### Revision Date 03/24/2025

Print Date 03/24/2025

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes eye irritation.

#### Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

#### **Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data. IARC Not applicable

**OSHA** Not applicable

NTP Not applicable

#### **Reproductive toxicity**

Not classified due to lack of data.

#### STOT-single exposure

May cause respiratory irritation.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Aspiration toxicity

Not classified due to lack of data.

#### SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

#### Components:

#### Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l



ision Date 03/24/2025		Print Date 03/24/202
Persistence and degradabil	ity	
No data available		
Bioaccumulative potential No data available		
<b>Mobility in soil</b> No data available		
Other adverse effects		
Product:		
Additional ecological infor- mation	: Do not empty into drains; dispose of this mate tainer in a safe way.	erial and its con-
	Avoid dispersal of spilled material and runoff soil, waterways, drains and sewers.	and contact with

#### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulations**

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### **Domestic regulation**

**49 CFR Road** Not regulated as a dangerous good

#### Special precautions for user

Not applicable

#### **SECTION 15. REGULATORY INFORMATION**

```
TSCA list
```

: All chemical substances in this product are either listed as ac-



#### Revision Date 03/24/2025

Print Date 03/24/2025

tive on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)
4,4'-methylenediphenyl diisocyanate	101-68-8	5000

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	Acute toxicity (any route of exposure) Respiratory or skin sensitization Specific target organ toxicity (single or repeated exposure) Skin corrosion or irritation Serious eye damage or eye irritation			
SARA 313	5	The following components are subject to reporting levels es- tablished by SARA Title III, Section 313:		
	4,4'- methylenediphe- nyl diisocyanate	101-68-8	>= 50 - < 70 %	
	Diphenylme- thanediisocya- nate, isomeres and homologues	9016-87-9	>= 30 - < 50 %	
Clean Air Act				

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61): 4,4'-methylenediphenyl 101-68-8 >= 50 - < 70 % diisocyanate

#### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### **SECTION 16. OTHER INFORMATION**

#### Full text of other abbreviations



Revision Date 03/24/2025	Print Date 03/24/202	5
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)	
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)	
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants	
ACGIH / TWA	: 8-hour, time-weighted average	
OSHA P0 / C	: Ceiling limit	
OSHA Z-1 / C	: Ceiling	

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/24/2025

10000003529 US / Z8