

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

SECTION 1. IDENTIFICATION

Product name : Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA
Product code : 000000000050544522
Other means of identification : MSeal M 790 Grey PTA

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2
Serious eye damage : Category 1
Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure
Specific target organ toxicity : Category 2 (Kidney)
- repeated exposure

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H373 May cause damage to organs (Kidney) through prolonged

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

or repeated exposure.

Precautionary Statements :

Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P314 Get medical advice/ attention if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Preparation based on: polyetherpolyol

Components

Chemical name	CAS-No.	Concentration (% w/w)
Calcium dihydroxide	1305-62-0	>= 20 - < 30
ethylene glycol	107-21-1	>= 10 - < 20
Titanium dioxide	13463-67-7	>= 1 - < 5
talc	14807-96-6	>= 1 - < 5
Naphtha (petroleum), heavy alkylate	64741-65-7	>= 1 - < 5
Silicon dioxide	7631-86-9	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version	Revision Date:	SDS Number:	Date of last issue: 02/09/2021
2.0	08/15/2022	000000827345	Date of first issue: 02/09/2021

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.
- In case of eye contact : Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon oxides
harmful vapours
fumes/smoke
nitrogen oxides
carbon black
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 00000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Wear eye/face protection.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Pick up with suitable appliance and dispose of.
Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.

Recommended storage temperature : 41 - 86 °F / 5 - 30 °C

Further information on storage stability : PROTECT FROM FREEZING.

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
 Date of first issue: 02/09/2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium dihydroxide	1305-62-0	TWA	5 mg/m3	ACGIH
		TWA	5 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
Naphtha (petroleum), heavy alkylate	64741-65-7	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Res-	0.05 mg/m3	NIOSH REL

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

		pirable dust)	(Silica)	
		TWA	6 mg/m3 (Silica)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Use NIOSH approved respiratory protection.

Hand protection

Remarks : Chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale dust/fumes/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : gray

Odor : faint, earthy

Odor Threshold : No data available

pH : 11 - 12

Melting point : No data available

Boiling point : not determined

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

Flash point : approx. 212 °F / 100 °C

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Self-ignition : not self-igniting

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : approx. 1.27 g/cm³ (approx. 73 °F / 23 °C)

Bulk density : Not applicable

Solubility(ies)

 Water solubility : partly soluble

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : not applicable for mixtures

Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

 Viscosity, dynamic : 1,000 mPa.s (73 °F / 23 °C)

 Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : not fire-propagating

Sublimation point : No data available

Molecular weight : No data available

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.
- Chemical stability : The product is stable if stored and handled as prescribed/indicated.
- Possibility of hazardous reactions : No decomposition if stored and applied as directed.
- Conditions to avoid : See SDS section 7 - Handling and storage.
- Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents
- Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.
-

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available. Discharge into the environment must be avoided.

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 000000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

tions.
Do not discharge into drains/surface waters/groundwater.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethylene glycol 107-21-1 >= 10 - < 20 %

US State Regulations

Pennsylvania Right To Know

Calcium dihydroxide	1305-62-0
ethylene glycol	107-21-1
Titanium dioxide	13463-67-7
talc	14807-96-6
Naphtha (petroleum), heavy alkylate	64741-65-7

New Jersey Right To Know

Calcium dihydroxide	1305-62-0
ethylene glycol	107-21-1
Titanium dioxide	13463-67-7
talc	14807-96-6

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version 2.0 Revision Date: 08/15/2022 SDS Number: 00000827345 Date of last issue: 02/09/2021
Date of first issue: 02/09/2021

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory
DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / C : Ceiling limit
OSHA Z-1 / TWA : 8-hour time weighted average

SAFETY DATA SHEET

Sikagard M 790 Part A grey Formerly MSeal M 790 grey PTA



Version	Revision Date:	SDS Number:	Date of last issue: 02/09/2021
2.0	08/15/2022	00000827345	Date of first issue: 02/09/2021

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/15/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN