

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL

Product code : 000000000050377823

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

FLAMMABLE LIQUIDS : 3

Skin corrosion/irritation : 2

Serious eye damage/eye irritation : Category 1

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

Short-term (acute) aquatic hazard : 3

Long-term (chronic) aquatic hazard : 3

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

H318 Causes serious eye damage.
H315 Causes skin irritation.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust or mist.
P273 Avoid release to the environment.
P243 Take action to prevent static discharges.
P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.
P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P242 Use only non-sparking tools.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/ doctor/
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 00000244218 Date of last issue: -
Date of first issue: 09/16/2020

Stoddard solvent	8052-41-3	$\geq 5 - < 7$
calcium oxide	1305-78-8	$\geq 5 - < 7$
Solvent naphtha (petroleum), light arom.	64742-95-6	$\geq 3 - < 7$
1,2,4-trimethylbenzene	95-63-6	$\geq 0 - < 3$
talc	14807-96-6	$\geq 7 - < 10$
Asphalt	8052-42-4	$\geq 5 - < 7$
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	$\geq 5 - < 7$

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 00000244218 Date of last issue: -
Date of first issue: 09/16/2020

- Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
-

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

- Conditions for safe storage : no smoking
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep container tightly closed and in a well-ventilated place.
Keep away from heat.
Avoid all sources of ignition: heat, sparks, open flame.
- Materials to avoid : Segregate from foods and animal feeds.
- Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1,2,4-trimethylbenzene	95-63-6	TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 125 mg/m3	NIOSH
		TWA value	25 ppm 125 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm 125 mg/m3	NIOSH REL
		TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m3	OSHA P0
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR 1910.1000

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version
1.0

Revision Date:
09/16/2020

SDS Number:
000000244218

Date of last issue: -
Date of first issue: 09/16/2020

				(Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Asphalt	8052-42-4	TWA value (Inhalable fraction)	0.5 mg/m3 (benzene solubles)	ACGIHTLV
		Ceil_Time (fumes/smoke)	5 mg/m3	NIOSH
		TWA value (Inhalable fume)	0.5 mg/m3 (benzene solubles)	ACGIHTLV
		TWA (Fume, inhalable fraction)	0.5 mg/m3 (benzene soluble aerosol)	ACGIH
		C (Fumes)	5 mg/m3	NIOSH REL
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIHTLV
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA value (Inhalable)	5 mg/m3	ACGIHTLV

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

		fraction)		
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Avoid inhalation of dusts/mists/vapours.
Avoid contact with the skin, eyes and clothing.
Avoid prolonged and/or repeated contact with the skin.
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : black

Odor : solvent

Odor Threshold : No data available

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

pH : not applicable

Melting point : No applicable information available.

Boiling point : 307 °F / 153 °C

boiling temperature : 307 - 662 °F / 153 - 350 °C

Flash point : 134 °F / 57 °C
Method: Flash Point by Tag Closed Tester.

Evaporation rate : not determined

Flammability (solid, gas) : Flammable.

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : approx. 0.9 %(V)

Vapor pressure : No data available

Relative vapor density : not determined

Relative density : No applicable information available.

Density : approx. 9 lb/USg (72 °F / 22 °C)
approx. 1.08 g/cm³ (approx. 68 °F / 20 °C)

Solubility(ies)
Water solubility : slightly soluble (68 °F / 20 °C)
Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : not applicable for mixtures

Autoignition temperature : No data available

Decomposition temperature : Vapors may form explosive mixture with air.
No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No applicable information available.
Viscosity, kinematic : approx. 200 mm²/s (68 °F / 20 °C)

Explosive properties : Not explosive
Not explosive

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0	Revision Date: 09/16/2020	SDS Number: 000000244218	Date of last issue: - Date of first issue: 09/16/2020
----------------	------------------------------	-----------------------------	--

Oxidizing properties : not fire-propagating
Sublimation point : No applicable information available.
Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapors may form explosive mixture with air.
Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Strong oxidizing agents
Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0	Revision Date: 09/16/2020	SDS Number: 000000244218	Date of last issue: - Date of first issue: 09/16/2020
----------------	------------------------------	-----------------------------	--

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Stoddard solvent:

Partition coefficient: n-
octanol/water : log Pow: 3.5 - 6.4 (68 °F / 20 °C)
Method: Partition coefficient (n-octanol/water), HPLC method.

calcium oxide:

Partition coefficient: n-
octanol/water : Remarks: The value has not been determined because the
substance is inorganic.

Solvent naphtha (petroleum), light arom.:

Partition coefficient: n- : log Pow: 3.17

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

octanol/water Method: other (calculated)
GLP: no

1,2,4-trimethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3.63 (77 °F / 25 °C)
Method: other (calculated)

talc:

Partition coefficient: n-octanol/water : Remarks: not applicable

Asphalt:

Partition coefficient: n-octanol/water : Remarks: not applicable

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(SOLVENT NAPHTHA, STODDARD SOLVENT)
Class : 3

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

Packing group : III
Labels : 3

IATA-DGR

UN/ID No. : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(SOLVENT NAPHTHA, STODDARD SOLVENT)
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(SOLVENT NAPHTHA, STODDARD SOLVENT)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : NA 1993
Proper shipping name : COMBUSTIBLE LIQUID, N.O.S.
(SOLVENT NAPHTHA, STODDARD SOLVENT)
Class : C
Packing group : III
Labels : Combustible Liquid
ERG Code : 128
Marine pollutant : no
Remarks : Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters).

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/16/2020	000000244218	Date of first issue: 09/16/2020

1,2,4-
trimethylbenzene 95-63-6

US State Regulations

Pennsylvania Right To Know

1,2,4-trimethylbenzene	95-63-6
calcium oxide	1305-78-8
Asphalt	8052-42-4
talc	14807-96-6
Solvent naphtha (petroleum), light arom.	64742-95-6
Stoddard solvent	8052-41-3
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
4-methyl-m-phenylene diisocyanate	584-84-9

New Jersey Right To Know

1,2,4-trimethylbenzene	95-63-6
calcium oxide	1305-78-8
talc	14807-96-6
Solvent naphtha (petroleum), light arom.	64742-95-6
Stoddard solvent	8052-41-3
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
carbon black	1333-86-4

California Prop. 65

WARNING: This product can expose you to chemicals including 4-methyl-m-phenylene diisocyanate, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information


SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL




Version 1.0 Revision Date: 09/16/2020 SDS Number: 000000244218 Date of last issue: -
Date of first issue: 09/16/2020

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/16/2020	000000244218	Date of first issue: 09/16/2020

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/16/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE

SAFETY DATA SHEET

Sikaflex CR 125 INTNL (PMU) Formerly MSeal CR 125 INTNL



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/16/2020	000000244218	Date of first issue: 09/16/2020

MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN