



SikaTile® Ultima Grout

PROFESSIONAL GRADE READY TO USE GROUT

- Superior performing ready to use grout
- No mixing, easy to spread and clean
- Color consistent with no efflorescence
- Virtually stainproof, no sealing required
- For grout joints from 1/16" to 1/2" (1.5 to 13 mm)
- **Colors:** 14 colors - see back for details
- **Packaging:** 1 gal. pail

Attributes Include:



BUILDING TRUST



SikaTile® Ultima Grout

PROFESSIONAL GRADE READY TO USE GROUT

WHERE TO USE

- For interior and exterior applications in both residential and commercial
- For grouting floors, walls, countertops, backsplashes, and intermittent wet conditions such as bathtub surrounds, shower walls and shower floors
- For grouting luxury vinyl tile and plank (LVT/LVP)

SUITABLE TILE TYPES:

- Brick and thin brick
- Cement-based precast terrazzo
- Impervious porcelain and glass tile
- Natural stone tile, granite and slate
- Vitreous, semi-vitreous or non-vitreous tile:
 - Ceramic, mosaic, quarry, cement body tile

COLORS AVAILABLE

00011 Snow White



00012 Navajo White



00018 Cream



00021 Canvas



00025 Tumbleweed



00153 Buckskin



00071 Sandstone



00150 Santa Fe



00175 Dark Chocolate



00030 Silver



00034 River Rock



00035 Natural Gray



00038 Gray



00525 Black Sapphire



FEATURES AND BENEFITS

- Superior performing ready to use grout
- No mixing, easy to spread and clean
- Color consistent with no efflorescence
- Virtually stainproof, no sealing required
- For grout joints from 1/16" to 1/2" (1.5 to 13 mm)
- Provides hard, durable, and full grout joints for professional results
- For interior and exterior floors, walls, and countertops
- For grouting luxury vinyl tile and plank (LVT/LVP)
- Ready-to-use - Use right from the pail, without the need to mix or add water
- Reusable - tightly close lid and store properly for reuse
- Mold and mildew resistant

NOTE: Always refer to Current Product data Sheet and SDS for detailed performance specifications prior to use.

APPROXIMATE COVERAGE

SikaTile® Ultima Grout						
Coverage in sqft. (m ²) per 1 gal. (3.79 L)*						
Tile Size	Grout Joint Width					
	1/16" (1.5 mm)	1/8" (3 mm)	3/16" (4.5 mm)	1/4" (6 mm)	3/8" (10 mm)	1/2" (12 mm)
2" x 2" x 1/4" (50 x 50 x 6 mm)	103 (9.6)	50 (4.7)	33 (3.1)	24 (2.2)	15 (1.4)	11 (1.0)
4-1/4" x 4-1/4" x 1/4" (108 x 108 x 6 mm)	221 (20.5)	109 (10.1)	72 (6.7)	54 (5.0)	35 (3.3)	26 (2.4)
6" x 6" x 1/4" (150 x 150 x 6 mm)	313 (29.1)	155 (14.4)	103 (9.6)	77 (7.2)	50 (4.7)	37 (3.4)
8" x 8" x 3/8" (200 x 200 x 10 mm)	278 (25.8)	138 (12.8)	91 (8.5)	68 (6.3)	45 (4.2)	33 (3.1)
12" x 12" x 3/8" (300 x 300 x 10 mm)	417 (38.7)	208 (19.3)	138 (12.8)	103 (9.6)	68 (6.3)	50 (4.7)
6" x 24" x 3/8" (150 x 610 x 10 mm)	334 (31.0)	166 (15.4)	110 (10.2)	82 (7.6)	54 (5.0)	40 (3.7)
12" x 24" x 3/8" (300 x 610 x 10 mm)	557 (51.7)	278 (25.8)	184 (17.1)	138 (12.8)	91 (8.5)	68 (6.3)

FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.SikaTile.com

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

BUILDING TRUST

