



SIKAFLEX®-221

MULTI-PURPOSE ONE COMPONENT POLYURETHANE SEALANT/ADHESIVE

Sikaflex®-221 is a high-quality multi-purpose non-sag 1-c polyurethane sealant/adhesive that cures on exposure to atmospheric humidity to form a durable elastomer. Ideal for sealant and adhesive applications for off-site construction. Meets approvals ASTM C920 types and Federal Specifications TT-S-00230C. Sikaflex®-221 is tested and classified in accordance with ANSI/UL 723 "Test for Surface Burning Characteristics of Building Materials."

PRODUCT BENEFITS

- Highly elastic and durable
- Resistant to aging and weathering exposure
- Non-corrosive
- Can be sanded and overpainted
- NSF registered, Proprietary Substances and Nonfood Compounds (black, gray, and white)
- UL listed for potable water (black, gray, and white)

PACKAGING

- 300 ml cartridge
- 300 ml unipack | 600 ml unipack
- 4.5 gal pail | 50 gal drum



1-800-688-7452
sikaindustry.com

BUILDING TRUST



GLOBAL BUT LOCAL PARTNERSHIP



Sika is a globally active company supplying the specialty chemicals markets. It is a leader in processing materials used in sealing, bonding, damping, reinforcing and protecting load-bearing structures in construction (buildings and infrastructure construction) and in industry (vehicle, building components, equipment production, solar and wind power).

Sika's product lines feature high-quality concrete admixtures, specialty mortars, sealants and adhesives, damping and reinforcing materials, structural strengthening systems, industrial flooring and membranes. Subsidiaries in more than 101 countries worldwide and approximately 20,000 employees link customers directly to Sika.

CONTACT US:

Sika Industry

30800 Stephenson Highway
Madison Heights, MI 48071
Tel: 248.577.0020

Sika North America Plant Locations

Lyndhurst, New Jersey
Lakewood, New Jersey
Marion, Ohio
Grandview, Missouri
Montreal, Quebec

North America Silicone Competence Center

995 Towbin Avenue
Lakewood, NJ 08701

Customer Service

800.688.7452

Technical Service

email: tsmh@us.sika.com

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. Sale of Sika products are subject Sika's Terms and Conditions of Sale available at <http://usa.sika.com/> or by calling 201-933-8800. Our most current General Sales Conditions shall apply. Please consult the Data Sheet prior to any use and processing.

REV-1.26.2021