



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

### SECTION 1. IDENTIFICATION

Product name : Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion : Category 1C

Serious eye damage : Category 1

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 2  
- repeated exposure


#### GHS label elements



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

|                          |   |   |
|--------------------------|---|---|
| Hazard pictograms        | : |    |
| Signal Word              | : | Danger  |
| Hazard Statements        | : | <p>H314 Causes severe skin burns and eye damage.<br/>H317 May cause an allergic skin reaction.<br/>H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br/>H341 Suspected of causing genetic defects.<br/>H350 May cause cancer by inhalation.<br/>H361 Suspected of damaging fertility or the unborn child.<br/>H373 May cause damage to organs through prolonged or repeated exposure.</p>  |
| Precautionary Statements | : | <p><b>Prevention:</b><br/>P201 Obtain special instructions before use.<br/>P202 Do not handle until all safety precautions have been read and understood.<br/>P260 Do not breathe mist or vapors.<br/>P264 Wash skin thoroughly after handling.<br/>P272 Contaminated work clothing must not be allowed out of the workplace.<br/>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.<br/>P284 Wear respiratory protection.</p> <p><b>Response:</b><br/>P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.<br/>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.<br/>P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.<br/>P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.<br/>P308 + P313 IF exposed or concerned: Get medical advice/ attention.<br/>P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.<br/>P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.<br/>P362 + P364 Take off contaminated clothing and wash it before reuse.</p> <p><b>Storage:</b></p> |



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

| Chemical name                         | CAS-No.    | Classification   | Concentration (% w/w) |
|---------------------------------------|------------|--|-----------------------|
| P-tert-butylphenol (PTBP)             | 98-54-4    | Skin Irrit. 2; H315<br>Eye Dam. 1; H318<br>Repr. 2; H361   | $\geq 10 - < 20$      |
| m-phenylenebis(methylamine)           | 1477-55-0  | Acute Tox. 4; H302<br>Acute Tox. 4; H332<br>Skin Corr. 1B; H314<br>Skin Sens. 1B; H317   | $\geq 10 - < 20$      |
| Trimethylhexane-1,6-diamine           | 25620-58-0 | Acute Tox. 4; H302<br>Skin Corr. 1A; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1A; H317   | $\geq 5 - < 10$       |
| Phenol, 4-nonyl, branched             | 84852-15-3 | Acute Tox. 4; H302<br>Skin Corr. 1B; H314<br>Eye Dam. 1; H318<br>Repr. 2; H361   | $\geq 5 - < 10$       |
| Talc                                  | 14807-96-6 |  | $\geq 5 - < 10$       |
| phenol                                | 108-95-2   | Acute Tox. 3; H301<br>Acute Tox. 3; H331<br>Acute Tox. 3; H311<br>Skin Corr. 1B; H314<br>Muta. 2; H341<br>STOT RE 2; H373      | $\geq 1 - < 5$        |
| 2,4,6-tris(dimethylaminomethyl)phenol | 90-72-2    | Skin Corr. 1C; H314<br>Eye Dam. 1; H318  | $\geq 1 - < 5$        |
| 2,2'-iminodiethylamine                | 111-40-0   | Acute Tox. 4; H302<br>Acute Tox. 2; H330<br>Acute Tox. 4; H312<br>Skin Corr. 1B; H314<br>Skin Sens. 1; H317<br>STOT SE 3; H335 | $\geq 0.1 - < 1$      |



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

|                                 |            |  |              |
|---------------------------------|------------|--|--------------|
| Quartz (SiO <sub>2</sub> ) >5µm | 14808-60-7 | Carc. 1A; H350<br>STOT RE 1; H372<br>STOT SE 3; H335 | >= 0.1 - < 1 |
|---------------------------------|------------|--|--------------|

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.  
corrosive effects  
sensitizing effects  
Asthmatic appearance  
Allergic reactions  
Dermatitis  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of causing genetic defects.  
May cause cancer by inhalation.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
Causes severe burns.



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

products.

Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Dangerous when wet  
Flammable solids  
Organic peroxides  
Poisonous liquids  
Spontaneously Combustible Substances

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components                      | CAS-No.    | Value type<br>(Form of exposure)    | Control parameters / Permissible concentration | Basis     |
|---------------------------------|------------|-------------------------------------|--|-----------|
| m-phenylenebis(methylamine)     | 1477-55-0  | C                                   | 0.018 ppm                                      | ACGIH     |
|                                 |            | C                                   | 0.1 mg/m <sup>3</sup>                          | OSHA P0   |
| Talc                            | 14807-96-6 | TWA (Dust)                          | 20 Million particles per cubic foot            | OSHA Z-3  |
|                                 |            | TWA (respirable dust fraction)      | 2 mg/m <sup>3</sup>                            | OSHA P0   |
|                                 |            | TWA (Respirable particulate matter) | 2 mg/m <sup>3</sup>                            | ACGIH     |
|                                 |            | PEL (respirable)                    | 0.05 mg/m <sup>3</sup>                         | OSHA CARC |
| phenol                          | 108-95-2   | TWA                                 | 5 ppm<br>19 mg/m <sup>3</sup>                  | OSHA Z-1  |
|                                 |            | TWA                                 | 5 ppm<br>19 mg/m <sup>3</sup>                  | OSHA P0   |
| 2,2'-iminodiethylamine          | 111-40-0   | TWA                                 | 1 ppm  | ACGIH     |
|                                 |            | TWA                                 | 1 ppm<br>4 mg/m <sup>3</sup>                   | OSHA P0   |
| Quartz (SiO <sub>2</sub> ) >5µm | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup>                        | ACGIH     |



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

|  |  |                                     |   |           |
|--|--|-------------------------------------|---|-----------|
|  |  | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup>                      | OSHA Z-1  |
|  |  | TWA (respirable)                    | 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 | OSHA Z-3  |
|  |  | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5            | OSHA Z-3  |
|  |  | TWA (respirable dust fraction)      | 0.1 mg/m <sup>3</sup>                       | OSHA P0   |
|  |  | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup> (Silica)            | ACGIH     |
|  |  | PEL (respirable)                    | 0.05 mg/m <sup>3</sup>                      | OSHA CARC |
|  |  | TWA (respirable dust fraction)      | 0.1 mg/m <sup>3</sup>                       | OSHA P0   |
|  |  | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup>                     | ACGIH     |
|  |  | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup> (Silica)            | ACGIH     |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

- essary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : dark gray
- Odor : amine-like
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 212 °F / > 100 °C  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : 0.05 hpa
- Relative vapor density : No data available
- Density : 1.45 g/cm<sup>3</sup> (73 °F / 23 °C)





## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

|  |  |
|--|--|
| Solubility(ies)                          |  |
| Water solubility                         | : partly soluble                             |
| Solubility in other solvents             | : No data available                          |
| Partition coefficient: n-octanol/water   | : No data available                          |
| Autoignition temperature                 | : No data available                          |
| Decomposition temperature                | : No data available                          |
| Viscosity                                |  |
| Viscosity, dynamic                       | : No data available                          |
| Viscosity, kinematic                     | : > 20.5 mm <sup>2</sup> /s (104 °F / 40 °C) |
| Explosive properties                     | : No data available                          |
| Oxidizing properties                     | : No data available                          |
| Volatile organic compounds (VOC) content | : 2 g/l<br>A+B Combined                      |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |
|------------------------------------|---|
| Reactivity                         | : No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : The product is chemically stable.                           |
| Possibility of hazardous reactions | : Stable under recommended storage conditions.                |
| Conditions to avoid                | : No data available   |
| Incompatible materials             | : No data available   |
| Hazardous decomposition products   | : No decomposition if stored and applied as directed.         |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

### **Phenol, 4-nonyl, branched:**

Acute oral toxicity : LD50 Oral (Rat): 1,412 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,160 mg/kg

### **phenol:**

Acute oral toxicity : LD50 Oral (Rat): 300 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.9 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal: 660 mg/kg

### **2,4,6-tris(dimethylaminomethyl)phenol:**

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

### **2,2'-iminodiethylamine:**

Acute oral toxicity : LD50 Oral (Rat): 1,553 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.071 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): 1,045 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

### **Product:**

Method : In Vitro Membrane Barrier Test Method for Skin Corrosion -  
CORROSITEX

Result : Corrosive after 1 to 4 hours of exposure

### **Components:**

#### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Corrosive  
Method : OECD Test Guideline 404



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

### Serious eye damage/eye irritation

Causes serious eye damage.

### Components:

#### 2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit  
Assessment : Causes serious eye damage.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Germ cell mutagenicity

Suspected of causing genetic defects.

#### Carcinogenicity

May cause cancer by inhalation.

|             |   |            |
|-------------|---|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans<br>Quartz (SiO <sub>2</sub> )<br>(Silica dust, crystalline)   | 14808-60-7 |
| <b>OSHA</b> | OSHA specifically regulated carcinogen<br>Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )<br>(crystalline silica) | 14807-96-6 |
|             | OSHA specifically regulated carcinogen<br>Quartz (SiO <sub>2</sub> )<br>(crystalline silica)  | 14808-60-7 |
| <b>NTP</b>  | Known to be human carcinogen<br>Quartz (SiO <sub>2</sub> )<br>(Silica, Crystalline (Respirable Size))                                     | 14808-60-7 |

#### Reproductive toxicity

Suspected of damaging fertility or the unborn child.

#### STOT-single exposure

Not classified due to lack of data.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

#### Aspiration toxicity

Not classified due to lack of data.



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

### Further information

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **m-phenylenebis(methylamine):**

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): > 10 - 100 mg/l  
aquatic invertebrates Exposure time: 48 h

##### **Phenol, 4-nonyl, branched:**

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Toxicity to algae/aquatic : EC50 (*Scenedesmus capricornutum* (fresh water algae)): > 10  
plants - 100 mg/l

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 3267
- Proper shipping name : Corrosive liquid, basic, organic, n.o.s.  
(m-phenylenebis(methylamine), 4-nonylphenol, branched)
- Class : 8
- Packing group : III
- Labels : Corrosive
- Packing instruction (cargo aircraft) : 856
- Packing instruction (passenger aircraft) : 852

##### IMDG-Code

- UN number : UN 3267
- Proper shipping name : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.  
(m-phenylenebis(methylamine), 4-nonylphenol, branched)
- Class : 8
- Packing group : III
- Labels : 8
- EmS Code : F-A, S-B
- Marine pollutant : yes

#### Domestic regulation

##### 49 CFR

- UN/ID/NA number : UN 3267
- Proper shipping name : Corrosive liquid, basic, organic, n.o.s.  
(m-phenylenebis(methylamine), Phenol, 4-nonyl, branched)
- Class : 8
- Packing group : III
- Labels : CORROSIVE
- ERG Code : 153
- Marine pollutant : no

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

The following substance(s) is/are subject to a Significant New Use Rule:

Phenol, 4-nonyl, branched                      84852-15-3                      See 40 CFR § 721.10765; Proposed Rule

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

Phenol, 4-nonyl, branched                      84852-15-3

### CERCLA Reportable Quantity

| Components | CAS-No.  | Component RQ (lbs) |
|------------|----------|--------------------|
| phenol     | 108-95-2 | 1000               |

### SARA 304 Extremely Hazardous Substances Reportable Quantity

| Components | CAS-No.  | Component RQ (lbs) |
|------------|----------|--------------------|
| phenol     | 108-95-2 | 1000               |

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Germ cell mutagenicity  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Phenol, 4-nonyl, branched                      84852-15-3                      >= 5 - < 10 %

phenol                      108-95-2                      >= 1 - < 5 %

### Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

phenol                      108-95-2                      >= 1 - < 5 %

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including Talc, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



## Sikadur®-31 SBA Normal Set (20-45 °F) Part B

Revision Date 03/21/2024

Print Date 03/21/2024

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

|                 |   |  |
|-----------------|---|--|
| ACGIH           | : | USA. ACGIH Threshold Limit Values (TLV)  |
| OSHA CARC       | : | OSHA Specifically Regulated Chemicals/Carcinogens                                |
| OSHA P0         | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)               |
| OSHA Z-1        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts               |
| ACGIH / TWA     | : | 8-hour, time-weighted average  |
| ACGIH / C       | : | Ceiling limit  |
| OSHA CARC / PEL | : | Permissible exposure limit (PEL)   |
| OSHA P0 / TWA   | : | 8-hour time weighted average   |
| OSHA P0 / C     | : | Ceiling limit  |
| OSHA Z-1 / TWA  | : | 8-hour time weighted average   |
| OSHA Z-3 / TWA  | : | 8-hour time weighted average   |

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 03/21/2024

000000603945  
US / Z8