

PRODUCT DATA SHEET

SikaWall® Super Shower Finish

Formerly LaHabra® Super Shower Finish.

PRODUCT DESCRIPTION

SikaWall® Super Shower Finish is a mechanically-blended compound of grey portland cement, hydrated lime, inert aggregates, and specific additives, designed to achieve a steel trowel finish over a portland cement base.

USES

SikaWall® Super Shower Finish is a mechanically-blended compound of grey portland cement, hydrated lime, inert aggregates, and specific additives, designed to achieve a steel trowel finish over a portland cement base. It requires the addition of only clean potable water for mixing. SikaWall® Super Shower Finish to provide an durable decorative finish that will bond to any properly prepared portland cement base surface. It may be used on interior or exterior surfaces to provide a highly condensed, smooth surface for painting. Ideal for use in high moisture areas such as showers, bathrooms, swimming pool dressing rooms, laundry rooms and locker rooms.

CHARACTERISTICS / ADVANTAGES

- Decorative finish that provides durability for exterior/interior applications
- Can be colored using Sika Wall Color Paks.
- Mixes easily with potable water.
- Conventional portland cement plaster finish.
- Low maintenance, economical.
- Weather resistant

PRODUCT INFORMATION

Chemical Base	▪ Portland cement: Type 1-ASTM. ▪ C150-56 Hydrated lime: Federal specs SS-L-351 B Type F, ASTM C206-88. ▪ Silica Sand: ASTM C-144.
Packaging	90 lb. (40.8 kg) net weight in a multi-wall bag.
Color	White. If you prefer to color Super Shower Finish with SikaWall Color Packs, it will achieve its own variance of color based on color selection and application. When tinted the finish coat will exhibit natural color variations that vary with substrates, drying times, and application techniques.
Shelf Life	12 months from date of production if stored properly in original, unopened and undamaged sealed packaging.

APPLICATION INFORMATION

Coverage	One 90 lb. (40.8 kg) bag covers approximately 10 to 16 sq. yds. (8.3 to 14.5m ²), depending on thickness and condition of basecoat.
-----------------	---

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

USES

- Use only on surfaces that are sound, clean, dry, unpainted, and free from any residue that might affect the ability of this product to bond to the surface.
- Ambient and surface temperature must be 40°F (4°C) or higher during application. Protect from freezing for a period of not less than 48 hours after set has occurred. Provide supplemental heat and protection from precipitation as needed.
- Ambient and surface temperatures must not exceed 120°F (49°C) during and 24 hours after application.
- Avoid application in direct sunlight in hot weather.
- Moist curing may be necessary during hot/dry weather conditions. **Do not moist cure if intergally colored with SikaWall Color Packs**
- Before applying product, a sample should be applied and allowed to cure for color and texture approval.
- On interior applications, openings in the building (windows, doors, etc.) should be covered to avoid excessive wind which could cause premature dry-out.
- Protect adjacent surfaces from overspray and droppings, drips or spills. They should be removed immediately with water or soap and water to prevent the possibility of permanent staining.
- Not to be used as the primary waterproofing for indoor showers applications.

LIMITATIONS

SikaWall® Super Shower Finish should be applied true and even without imperfections which can be attributed to the applicator's work and materials. A top quality plastering job requires not only top-grade materials, but careful planning and application techniques. Do not deviate from instructions.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

New portland cement substrates should be properly cured prior to application of SikaWall® Super Shower

Finish (approximately 7 days). All receiving surfaces must be structurally sound, clean, free of dust, dirt, silicones, paint products, efflorescence or any other contaminant which could impair the natural bond. Surface defects, such as cracks, holes or voids should be repaired prior to application. Basecoat should be plum, level, and square to prevent uneven thickness of SikaWall® Super Shower Finish.

MIXING

SikaWall® Super Shower Finish should be mechanically mixed for approximately 15 to 20 minutes to provide maximum workability. For Hand Application: 8 to 10 qts. (7.6 to 9.5 ltr.) of clean water per 90 lb. (40.8 kg.) sack will be necessary. Add approximately 1/2 of the required water to the mixer. With the blades running, carefully add the SikaWall® Super Shower Finish. Allow ample time for initial mixing, add remaining mix water, and complete mixing to produce a smooth, workable consistency. For Machine or Spray Application: Additional mixing water may be necessary. NOTE: For maximum strength and increased moisture resistance, add SikaWall Adacryl Admix & Bonder to the mix water using a 3:1 ratio (3 parts water/1 part Adacryl).

APPLICATION

Apply SikaWall® Super Shower Finish to a thoroughly dry basecoat which has been evenly wetted by brushing or spraying (to control suction). Allow surface moisture to dissipate prior to application. Avoid the use of excessive moisture during application. SikaWall® Super Shower Finish should be applied to an approximate thickness of 1/8 inch (3mm). Trowel apply the initial coat (scratch coat) evenly to the substrate with enough pressure to insure tight contact. After the basecoat has been covered completely, double back and fill out to a true, even surface. Allow material to hydrate (begin to lose its moisture to the basecoat and to the ambient air) and then trowel it well, firmly compacting the material with water, free from catfaces and/or other blemishes or irregularities. Avoid unnecessary "build-ups" which cause shrinkage or check-cracking. A properly prepared basecoat will prevent leveling with the SikaWall® Super Shower Finish.

CLEANING OF TOOLS

Upon completion of work clean all mixing equipment and application tools immediately with water.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

SikaWall® Super Shower Finish
September 2026, Version 01.01
021840501000245935

SikaWallSuperShowerFinish-en-US-(09-2026)-1-1.pdf

