



# Sikalastic® 320 NS/SL




## SINGLE COMPONENT, BITUMEN MODIFIED WATERPROOFING MEMBRANE

- Available in Self-leveling and Non-sag consistencies
- Application on green or damp concrete
- Low VOC content (<48 g/L)
- Alkali Resistant
- Catalyzed by water
- Can be applied around pool areas
- Solvent Free

### Available in

Pail  
5 gallons

Drum  
55 gallons



BUILDING TRUST



# Sikalastic® 320 NS/SL

SINGLE COMPONENT, BITUMEN MODIFIED WATERPROOFING MEMBRANE

## APPLICATIONS

- Planters
- Plazas
- Between Slabs
- Foundation Walls
- Bridges
- Shower Pans
- Tunnels

## LITERATURE

- Product Data Sheet
- Safety Data Sheet
- Architectural Details
- Specification Component

\*Always refer to Current Product Data Sheet and SDS for detailed performance specifications prior to use.

## BENEFITS

- Available in Self-leveling and Non-sag consistencies
- Low VOC content (<48 g/L)
- Alkali Resistant
- Can be applied around pool areas
- Catalyzed by water
  - Faster cure
  - Applied horizontally up to 120 mils
- Application on green concrete
  - **Horizontal:** 48 hours after pour or walkable
  - **Vertical:** 24 hours after forms removed
- Detailed cracks can be coated with Sikalastic® 320 in one hour with:
  - Sikaflex® 11FC - Existing Concrete
  - Sikaflex® 1a - Green Concrete

COVERAGE	DRY FILM THICKNESS	SYSTEM TYPE
50 FT <sup>2</sup> /GAL	30 ± MILS DFT	
25 FT <sup>2</sup> /GAL	60 ± MILS DFT	5 YEAR SYSTEM
18 FT <sup>2</sup> /GAL	90 ± MILS DFT	10 YEAR SYSTEM
13 FT <sup>2</sup> /GAL	120 ± MILS DFT	20 YEAR SYSTEM

## GOING ON GREEN?

TRY Sikaflex® 1a OR Sikaflex® 1c SL  
WHEN SEALING GREEN CONCRETE.



**Note:** 1) Advice on specific applications is available from the Technical Service Department of Sika Construction Products Division.  
2) See Product Data Sheet and Warranty Guidelines for more information.

## FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: [www.usa.sika.com](http://www.usa.sika.com)

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 201-933-8800  
Fax: 201-933-6225



**BUILDING TRUST**

