

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

SECTION 1. IDENTIFICATION

Product name : Sikaflex Primer-179 Formerly MSeal P 179

Product code : 000000000050340078

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC

Address : 201 POLITO AVE
Lyndhurst NJ 07071

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Aspiration hazard : Category 1

FLAMMABLE LIQUIDS : 2

Skin corrosion/irritation : 2

Serious eye damage/eye irritation : Category 1

Skin sensitization : Category 1

Reproductive toxicity : 2

Specific target organ toxicity - single exposure : 3

Specific target organ toxicity - repeated exposure : 2 (Central nervous system)

Short-term (acute) aquatic hazard : 2

Long-term (chronic) aquatic hazard : 3





GHS label elements

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

- Hazard pictograms :    
- Signal Word : Danger
- Hazard Statements : H225 Highly flammable liquid and vapour.
H318 Causes serious eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
H401 Toxic to aquatic life.
- Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P260 Do not breathe dust or mist.
P243 Take action to prevent static discharges.
P273 Avoid release to the environment.
P201 Obtain special instructions before use.
P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.
P202 Do not handle until all safety precautions have been read and understood.
P272 Contaminated work clothing should not be allowed out of the workplace.
P240 Ground and bond container and receiving equipment.
P242 Use only non-sparking tools.
P264 Wash face, hands and any exposed skin thoroughly after handling.
- Response:**
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/ doctor/
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

P362 + P364 Take off contaminated clothing and wash it before reuse.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P233 Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Methylethylketone	78-93-3	$\geq 50 - < 75$
toluene	108-88-3	$\geq 15 - < 20$
Reaction product: bisphenol-A-(epichlorhydrin)-Epoxy resin (number average molecular weight ≤ 700)	25068-38-6	$\geq 15 - < 20$
3-aminopropyltriethoxysilane	919-30-2	$\geq 3 - < 5$

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

- Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
-

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Product is not explosive.
- Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : no smoking
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
-

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
 Date of first issue: 09/10/2020

Materials to avoid : Observe VCI storage rules.

Further information on storage stability : No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methylethylketone	78-93-3	STEL value	300 ppm	ACGIHTLV
		TWA value	200 ppm	ACGIHTLV
		REL value	200 ppm 590 mg/m3	NIOSH
		STEL value	300 ppm 885 mg/m3	NIOSH
		PEL	200 ppm 590 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	200 ppm 590 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	300 ppm 885 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	OSHA P0
STEL	300 ppm 885 mg/m3	OSHA P0		
toluene	108-88-3	TWA value	20 ppm	ACGIHTLV
		REL value	100 ppm 375 mg/m3	NIOSH
		STEL value	150 ppm 560 mg/m3	NIOSH
		TWA value	100 ppm 375 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 560 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		max. conc.	500 ppm	29 CFR 1910.1000 (Table Z-2)

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
 Date of first issue: 09/10/2020

		CLV	300 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA value	200 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
 Tightly fitting safety goggles
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.
 Avoid contact with the skin, eyes and clothing.
 Avoid exposure - obtain special instructions before use.
 Handle in accordance with good building materials hygiene and safety practice.
 Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

Appearance : liquid

Color : No applicable information available.

Odor : product specific

Odor Threshold : No data available

Melting point : No applicable information available.

boiling temperature : 226 °F / 108 °C
No data available

Flash point : 25.00 °F / -3.89 °C
25 °F / -4 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : approx. 0.9 g/cm³ (68 °F / 20 °C)
approx. 7.50 lb/USg (68 °F / 20 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No applicable information available.

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

Viscosity, kinematic : No applicable information available.
Sublimation point : No applicable information available.
Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapors may form explosive mixture with air.
Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents
Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.
Acute inhalation toxicity : Remarks: No applicable information available.
Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May also damage the lung at swallowing (aspiration hazard).

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.
Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: Taking into consideration the properties of several

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

Stability in water : Remarks: The product is slightly soluble in water. It can be eliminated from water by abiotic processes.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Because of the product's consistency and low water solubility, bioavailability is improbable.

Components:

Methylethylketone:

Partition coefficient: n-octanol/water : log Pow: 0.29
Method: other (measured)
GLP: no data
Remarks: Information taken from reference works and the literature.

toluene:

Partition coefficient: n-octanol/water : log Pow: 2.73 (68 °F / 20 °C)
pH: 7
Method: other (measured)
GLP: no data
Remarks: Information taken from reference works and the literature.

3-aminopropyltriethoxysilane:

Partition coefficient: n-octanol/water : log Pow: 1.7 (68 °F / 20 °C)
pH: 7

Mobility in soil

Product:

Distribution among environmental compartments : Remarks: The substance will not evaporate into the atmosphere from the water surface.
Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.
Following exposure to soil, adsorption to solid soil particles is unlikely, therefore contamination of groundwater is expected.

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with national, state and local regulations.
Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : II
Labels : 3

IATA-DGR

- UN/ID No. : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

- UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

- UN/ID/NA number : UN 1263
Proper shipping name : PAINT


SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
 Date of first issue: 09/10/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1000 (Table Z-2) : OSHA Table Z-2 (Toxic and Hazardous Substances) 29 CFR 1910.1000
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2
- 29 CFR 1910.1000 (Table Z-1-A) / STEL value : Short Term Exposure Limit (STEL):
- 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
- 29 CFR 1910.1000 (Table Z-2) / CLV : Ceiling Limit Value:
- 29 CFR 1910.1000 (Table Z-2) / TWA value : Time Weighted Average (TWA):
- 29 CFR 1910.1000 (Table Z-2) / max. conc. : Maximum concentration:
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / REL value : Recommended exposure limit (REL):

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version 1.0 Revision Date: 09/10/2020 SDS Number: 000000261026 Date of last issue: -
Date of first issue: 09/10/2020

NIOSH / STEL value : Short Term Exposure Limit (STEL):
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek
NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded
at any time during a workday
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-2 / TWA : 8-hour time weighted average
OSHA Z-2 / CEIL : Acceptable ceiling concentration
OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling con-
centration for an 8-hr shift

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/10/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensur-

SAFETY DATA SHEET

Sikaflex Primer-179 Formerly MSeal P 179



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/10/2020	000000261026	Date of first issue: 09/10/2020

ing the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN