

PRODUCT DATA SHEET

Detail Membrane PVC

Detail Membrane is a PVC Thermoplastic membrane used for flashing details

PRODUCT DESCRIPTION

Detail Membrane PVC is produced with an integral fiberglass mat reinforcement for dimensional stability and is more pliable than Sarnafil G 410 flashing membrane making it easier to stretch and weld. Detail Membrane is intended for flashing pipes, inside/outside corners and unusual shaped penetrations.

USES

For Sarnafil and Sikaplan roofing and waterproofing flashing details

AREAS OF APPLICATION

- Flashing pipes
- Inside/outside corners
- Unusual shaped penetrations

CHARACTERISTICS / ADVANTAGES

More pliable than Sarnafil G 410 membrane, making it easier to stretch and weld

- Reinforced for dimensional stability and durability
- Lacquer coated top surface to reduce dirt pick up
- Convenient pre-cut rolls

PRODUCT INFORMATION

Chemical Base	Thermoplastic PVC membrane containing ultraviolet light stabilizers, flame retardant and integral carrier. Detail Membrane has a unique lacquer coating applied to the top surface of the membrane. Available in 60 mil (1.5 mm) thickness.
Packaging	24" x 50 ft (61 cm x 15.2 m) roll, 40 lbs (18.2 kg) per roll
Appearance / Color	<ul style="list-style-type: none">▪ Top: White, Tan or Reflective Gray▪ Bottom: Gray
Shelf Life	N/A
Storage Conditions	Store rolls standing on end on pallets and fully protected from the weather with clean canvas tarpaulins. Unvented polyethylene tarpaulins are not accepted due to the accumulation of moisture beneath the tarpaulin in certain weather conditions that may affect the ease of membrane weldability.

APPLICATION INSTRUCTIONS

APPLICATION

Detail Membrane is installed by Authorized Applicators on pipes, corners and other roof penetrations. Detail Membrane can be heated slightly and stretched to conform around various shapes. Seams are heat welded together using standard hot air welding tools. Install Detail Membrane with lacquer coated (glossy appearance) side up.

MAINTENANCE

Standard maintenance of Sarnafil or Sikaplan systems should include regular inspections of flashings, drains, and termination sealants at least twice a year and after each storm.

AVAILABILITY/WARRANTY

AVAILABILITY

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

WARRANTY

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Sarnafil

100 Dan Road
Canton, MA 02021
Phone: +1 800-451-2504
Fax: +1 781-828-5365
usa.sika.com/sarnafil
webmaster.sarnafil@us.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

Detail Membrane PVC
August 2020, Version 04.01
02090511299000005

DetailMembranePVC-en-US-(08-2020)-4-1.pdf