

PRODUCT DATA SHEET

Roofing Granule

Mineral granules for SikaShield modified bituminous membranes

PRODUCT DESCRIPTION

Roofing Granule features the same mineral granules used on the top surface of our SikaShield bituminous membranes. They are durable, UV-resistant, and available in various color to match the SikaShield range. They can be used for repair or to complement the membrane application by protecting the asphalt surface and helping prevent premature aging and oxidation.

USES

Apply Roofing Granule to:

- Areas of exposed asphalt, such as bleed-out on heat-welded membranes
- Over exposed asphalt adhesives, mastics, sealants, and similar materials

CHARACTERISTICS / ADVANTAGES

- High quality mineral granule
- Prevents the oxidation of the asphalt
- Available in various colors

PRODUCT INFORMATION

Packaging	Pails or bags depending on the type of granule
Color	High reflective white, standard white or any other SikaShield color
Shelf Life	36 months from the date of production
Storage Conditions	The product must be stored in original unopened and undamaged packaging in dry conditions and temperatures between 41°F (5°C) and 95°F (35°C).

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

AVAILABILITY/WARRANTY

AVAILABILITY

From Sika Corporation – Roofing Authorized Applicators when used within SikaShield systems.

ENVIRONMENTAL, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL DISCLAIMER

This information and, in particular, the recommendations regarding the application and final use of the product, are given in good faith, based on Sika's current knowledge and experience of the products when properly stored, handled and applied, in normal situations, within its lifetime and in accordance with Sika's recommendations. In practice, the possible differences in the materials, supports and actual conditions in the place of application are such, which can not be inferred from the information of this document, nor from any other written recommendation, nor from any advice offered, no guarantee in terms of marketing or suitability for particular purposes, or any obligation outside any legal relationship that may exist. The user must test the suitability of the products for the desired application and purpose. Sika reserves the right to modify the properties of its products. Property rights of third parties are reserved. Orders are accepted in accordance with the terms of our current General Conditions of Sale and Supply. Users must know and use the latest and updated version of the Product Data Sheets, copies of which will be sent to whoever requests them, or through the page www.sika.com.mx. Ensure the handling of loads according to NOM-036-1-STPS-2018.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Roofing Granule
June 2025, Version 01.01
020945139000000020

RoofingGranule-en-US-(06-2025)-1-1.pdf

