

PRODUCT DATA SHEET

SikaWall® Color Pack

Formerly LaHabra® Color Pack.

PRODUCT DESCRIPTION

Pre-packaged powdered pigments for use with SikaWall® Exterior Stucco Color Coat tint bases (Base 100 and Base 200).

USES

Used to create SikaWall standard and custom colors of SikaWall® Exterior Stucco Color Coat.

CHARACTERISTICS / ADVANTAGES

- SikaWall® Color Pack is specially formulated to tint SikaWall® Exterior Stucco Color Coat
- One SikaWall® Color Pack is mixed with one bag of SikaWall® Exterior Stucco Color Coat to create a color from the SikaWall® Cement Stucco Color Collection (48 colors)
- SikaWall® Color Pack can be formulated to create custom colors

PRODUCT INFORMATION

Packaging	1 lb. (0.45 kg) and 2 lb. (0.9 kg) bags
Color	Available in 48 standard colors (the SikaWall Cement Stucco Color Collection) and in custom colors.
Shelf Life	Not applicable when properly stored.
Storage Conditions	Unopened, undamaged, original sealed bag that is properly transported and stored. Store dry, off ground and protect from rain and moisture.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must

APPLICATION INSTRUCTIONS

Obtain, read and follow the application instructions on the product data sheet for SikaWall® Exterior Stucco Color Coat.

Jobsite mock up is recommended using contractor's actual substrate, mixing procedures, and application techniques for final color approval.

MIXING

Add all of the color packs (1 per 90 lb. bag for a SikaWall® standard color, a maximum of 4 standard 1 lb. color packs can be added per 90 lb. bag for increased color depth) to be used for one "batch" and mix until color is evenly dispersed, (approximately 1 to 2 minutes).

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

SikaWall® Color Pack
September 2026, Version 01.01
021810101000245932

SikaWallColorPack-en-US-(09-2026)-1-1.pdf

