

Revision Date 08/08/2023

Print Date 08/08/2023

SECTION 1. IDENTIFICATION

Product name	:	Sikafloor [®] -2570 WB Part A
Company name	:	Sika Corporation
		201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)			
Skin irritation	:	Category 2	
Eye irritation	:	Category 2A	
Skin sensitization	:	Category 1	
GHS label elements Hazard pictograms	:		
Signal Word	:	Warning	
Hazard Statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.	
Precautionary Statements	:	Prevention: P261 Avoid breathing mist or vapors.	
		1 / 11	

Revision Date 08/08/2023



Print Date 08/08/2023

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentra- tion (% w/w)
bisphenol-A-(epichlorhydrin) epoxy resin	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 30 - < 50
bisphenol-F-(epichlorhydrin) epoxy resin	28064-14-4	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 5 - < 10

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attend- ance.
If inhaled	:	Move to fresh air.



Revision Date 08/08/2023		Print Date 08/08/2023
		Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	:	irritant effects sensitizing effects Allergic reactions Excessive lachrymation Erythema Dermatitis Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
Notes to physician	:	Treat symptomatically.
SECTION & EIDE EIGHTING MEA	CI	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages



Revision Date 08/08/2023	Print Date 08/08/2023
Methods and materials for : containment and cleaning up	cannot be contained. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
SECTION 7. HANDLING AND STOR	AGE
Advice on protection against : fire and explosion	Normal measures for preventive fire protection.
Advice on safe handling :	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage :	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures :	Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use pro- cess enclosures, local exhaust ventilation or other engineer- ing controls to keep worker exposure below any recommend- ed or statutory limits.
Porsonal protoctive equipmer	+

Personal protective equipment

Respiratory protection	:	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary.
		The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when han-



Revision Date 08/08/2023		Print Date 08/08/2023
	dling the product. If this concentration is exceeded contained breathing apparatus must be used.	l, self-
Hand protection	Chemical-resistant, impervious gloves complying approved standard should be worn at all times wh chemical products if a risk assessment indicates the essary.	en handling
Eye protection	: Safety eyewear complying with an approved stand be used when a risk assessment indicates this is r	
Skin and body protection	: Choose body protection in relation to its type, to the tration and amount of dangerous substances, and cific work-place.	
Hygiene measures	 Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after the product. Remove contaminated clothing and protective equ before entering eating areas. Wash thoroughly after handling. 	C C

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	milky, white
Odor	:	characteristic
Odor Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing	:	No data available
point Boiling point/boiling range	:	No data available
Flash point	:	> 212 °F / > 100 °C (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available



Print Date 08/08/2023

Sikafloor[®]-2570 WB Part A

Revision Date 08/08/2023

Vapor pressure	:	23 hpa
Relative vapor density	:	No data available
Density		ca. 1.095 g/cm3 (74.7 °F / 23.7 °C)
Density	•	ca. 1.035 g/cm (74.7 + 725.7 G)
Solubility(ies) Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm2/s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	28 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.



Revision Date 08/08/2023

Print Date 08/08/2023

<u>Components:</u>
bisphenol-A-(epichlorhydrin) epoxy resin:
Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg
bisphenol-F-(epichlorhydrin) epoxy resin:
Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye irritation Causes serious eye irritation.
Respiratory or skin sensitization
Skin sensitization May cause an allergic skin reaction.
Respiratory sensitization
Not classified due to lack of data.
Germ cell mutagenicity
Not classified due to lack of data.
Carcinogenicity
Not classified due to lack of data. IARC Not applicable
OSHA Not applicable
NTP Not applicable
Reproductive toxicity
Not classified due to lack of data.
STOT-single exposure
Not classified due to lack of data.
STOT-repeated exposure
Not classified due to lack of data. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.



SECTION 12. ECOLOGICAL INFORMATION

Revision Date 08/08/2023

Print Date 08/08/2023

Ecotoxicity	
<u>Components:</u>	
bisphenol-A-(epichlorhydrin) e Toxicity to fish :	poxy resin: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other : aquatic invertebrates	EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h
Persistence and degradability No data available	
Bioaccumulative potential No data available	
Mobility in soil No data available	
Other adverse effects	
Product:	
Additional ecological infor- : mation	Do not empty into drains; dispose of this material and its con- tainer in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May be harmful to the environment if released in large quanti- ties. Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste han- dling site for recycling or disposal.



Revision Date 08/08/2023

Print Date 08/08/2023

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR UN/ID No. Proper shipping name	:	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
Class	:	9
Packing group	:	
Labels	:	Miscellaneous
Packing instruction (cargo aircraft)	:	964
Packing instruction (passen- ger aircraft)	:	964
IMDG-Code		
UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes

Domestic regulation

49 CFR

Not regulated as a dangerous good

DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant. IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Revision Date 08/08/2023

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Respiratory or skin sensitization Skin corrosion or irritation Serious eye damage or eye irritation
SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

MARNING: This product can expose you to chemicals including Oxirane, (chloromethyl)- Epichlorohydrin, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.





Sikafloor®-2570 WB Part A

Revision Date 08/08/2023

Print Date 08/08/2023

Revision Date 08/08/2023

100000016308 US / Z8