



SikaTile®-800 Sanded Grout & SikaTile®-800 Unsanded Grout

PREMIUM, POLYMER MODIFIED, DUSTLESS, PORTLAND CEMENT GROUT

- Available in both sanded and unsanded
 - SikaTile®-800 Sanded Grout - for 1/8" (3 mm) to 1/2" (13 mm) grout joints
 - SikaTile®-800 Unsanded Grout - for 1/16" (1.5 mm) to 1/8" (3 mm) grout joints
- Stain resistant and color consistent
- Easy mixing – just add water, no additives required
- **Colors:** 18 colors - see back for details
- **Packaging:**
 - SikaTile®-800 Sanded Grout - 25 lb. bags
 - SikaTile®-800 Unsanded Grout - 10 lb. boxes

Standards

- Exceeds ANSI A118.6

Attributes Include:



SANDED

UNSANDED

BUILDING TRUST



SikaTile®-800 Sanded Grout & SikaTile®-800 Unsanded Grout

PREMIUM, POLYMER MODIFIED, DUSTLESS, PORTLAND CEMENT GROUT

WHERE TO USE

- For interior and exterior applications in both residential and commercial applications in dry or wet conditions.
- For floors, walls, countertops, and submerged conditions.
- For application in submerged conditions (swimming pools, spas, water features and fountains), after 21 days.

SUITABLE TILE TYPES:


- Brick and thin brick
- Cement-based precast terrazzo
- Impervious porcelain and glass tile
- Natural stone tile, granite and slate
- Vitreous, semi-vitreous or non-vitreous tile:
 - Ceramic, mosaic, quarry, cement body tile

COLORS AVAILABLE

00010 Bright White



00011 Snow White



00012 Navajo White



00018 Cream



00021 Canvas



00032 Light Taupe



00025 Tumbleweed



00153 Buckskin




00071 Sandstone



00150 Santa Fe



00175 Dark Chocolate



00191 Terracotta



00030 Silver



00034 River Rock



00035 Natural Gray



00038 Gray



00162 True Taupe



00525 Black Sapphire



FEATURES AND BENEFITS

- Stain resistant and color consistent
- Easy mixing – just add water, no additives required
- Dustless formula – provides approximately 80% less dust than ordinary grouts
- Promotes cleaner working conditions by minimizing dust
- Creamier and easier to spread
- Uses less water for consistent hydration and quicker drying
- Longer working time
- Mold and mildew resistant

NOTE: Always refer to Current Product data Sheet and SDS for detailed performance specifications prior to use.

APPROXIMATE COVERAGE

SikaTile®-800 Sanded Grout Coverage in sqft. (m ²) per 25 lb. Bag (11.34 kg)*				
Tile Size	Grout Joint Width			
	1/8" (3 mm)	1/4" (6 mm)	3/8" (10 mm)	1/2" (13 mm)
1" x 1" x 1/4" (25 x 25 x 6 mm)	58 (5.4)	34 (3.2)	26 (2.4)	22 (2.0)
2" x 2" x 1/4" (50 x 50 x 6 mm)	106 (9.8)	58 (5.4)	42 (3.9)	34 (3.2)
4" x 4" x 3/8" (100 x 100 x 10 mm)	136 (12.6)	71 (6.6)	49 (4.6)	39 (3.6)
6" x 6" x 3/8" (150 x 150 x 10 mm)	201 (18.7)	103 (9.6)	71 (6.6)	55 (5.1)
8" x 8" x 3/8" (200 x 200 x 10 mm)	265 (24.6)	136 (12.6)	93 (8.6)	71 (6.6)
12" x 12" x 3/8" (300 x 300 x 10 mm)	395 (36.7)	201 (18.7)	136 (12.6)	103 (9.6)
18" x 18" x 3/8" (150 x 610 x 10 mm)	589 (54.7)	298 (27.7)	201 (18.7)	152 (14.1)
24" x 24" x 3/8" (610 x 610 x 10 mm)	784 (72.8)	395 (36.7)	265 (4.6)	201 (18.7)
6" x 24" x 3/8" (150 x 610 x 10 mm)	318 (29.5)	162 (15.1)	111 (10.3)	85 (7.9)
12" x 24" x 3/8" (300 x 610 x 10 mm)	525 (48.8)	266 (24.7)	179 (16.6)	136 (12.6)

SikaTile®-800 Unsanded Grout Coverage in sqft. (m ²) per 10 lb. Box (4.53 kg)*			
Tile Size	Grout Joint Width		
	1/16" (1.5 mm)	3/32" (2.4 mm)	1/8" (3 mm)
1" x 1" x 1/4" (25 x 25 x 6 mm)	42 (3.9)	29 (2.7)	23 (2.1)
2" x 2" x 1/4" (50 x 50 x 6 mm)	81 (7.5)	55 (5.1)	42 (3.9)
4" x 4" x 3/8" (100 x 100 x 10 mm)	105 (9.8)	71 (6.6)	54 (5.0)
6" x 6" x 3/8" (150 x 150 x 10 mm)	156 (14.5)	105 (9.8)	79 (7.3)
12" x 12" x 3/8" (300 x 300 x 10 mm)	310 (28.8)	207 (19.2)	156 (14.5)
18" x 18" x 3/8" (150 x 610 x 10 mm)	464 (43.1)	310 (28.8)	233 (21.6)
24" x 24" x 3/8" (610 x 610 x 10 mm)	618 (57.4)	412 (38.3)	310 (28.8)
6" x 24" x 3/8" (150 x 610 x 10 mm)	249 (23.1)	167 (15.5)	126 (11.7)
12" x 24" x 3/8" (300 x 610 x 10 mm)	413 (38.4)	276 (25.6)	208 (19.3)

FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.SikaTile.com

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

BUILDING TRUST

