Sikagard® WDE Primer Part B

Revision Date 09/18/2026 Print Date 09/18/2026

SECTION 1. IDENTIFICATION

Product name	:	Sikagard® WDE Primer Part B
Company name	:	Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: +1-703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	:	Category 4
Acute toxicity (Oral)	:	Category 4
Acute toxicity (Dermal)	:	Category 4
Skin corrosion	:	Sub-category 1B
Serious eye damage	:	Category 1
Skin sensitization	:	Category 1
Reproductive toxicity	:	Category 1B
Specific target organ toxicity - repeated exposure	:	Category 1

GHS label elements

Sikagard® WDE Primer Part B

Hazard pictograms :



Signal Word : Danger

Hazard Statements :
H227 Combustible liquid.
H302 + H312 Harmful if swallowed or in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Supplemental Hazard Statements : Corrosive to the respiratory tract.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapors.
P264 Wash hands and exposed skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye protection, face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or a doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or a doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or a doctor.
P308 + P313 IF exposed or concerned: Get medical advice or attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice

or attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS No./Unique ID	Classification	Concentration (% w/w)
2-piperazin-1-ylethylamine	140-31-8	Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 2; H361 STOT RE 1; H372	>= 15 - <= 40
4,4'-isopropylidenediphenol	80-05-7	Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 1B; H360 STOT SE 3; H335	>= 10 - <= 30
Benzyl alcohol	100-51-6	Acute Tox. 4; H302 Eye Irrit. 2A; H319 Skin Sens. 1B; H317	>= 10 - <= 30
Phenol, 4-nonyl, branched	84852-15-3	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Repr. 2; H361	>= 5 - <= 10

triethylenetetramine	112-24-3	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 3 - <= 7
Isophoronediamine	2855-13-2	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 3 - <= 7
[3-(2,3-epoxypro-poxy)propyl]trimethoxysilane	2530-83-8	Eye Dam. 1; H318	>= 3 - <= 7
Adduct XA-P (epoxy amine adduct, polymer)	110839-13-9	Acute Tox. 4; H302 Skin Sens. 1; H317	>= 1 - <= 5
[(dimethylamino)methyl]phenol	25338-55-0	Skin Corr. 1B; H314	>= 0.5 - <= 1.5
m-phenylenebis(methylamine)	1477-55-0	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1B; H317	>= 0.5 - <= 1.5
Salicylic acid, o-hydroxybenzoic acid	69-72-7	Acute Tox. 4; H302 Eye Dam. 1; H318 Repr. 2; H361	>= 0.1 - <= 1
Phenol, 2-nonyl-, branched	91672-41-2	Acute Tox. 4; H302 Skin Corr. 1B; H314, EUH071 Eye Dam. 1; H318 Repr. 2; H361	>= 0.1 - <= 1
2-(2-aminoethylamino)ethanol	111-41-1	Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Repr. 1B; H360 STOT SE 3; H335	>= 0.1 - <= 1
2,2'-iminodiethylamine	111-40-0	Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317 STOT SE 3; H335	>= 0.1 - <= 1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

		Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
In case of eye contact	:	Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Health injuries may be delayed. corrosive effects sensitizing effects toxic effects for reproduction Gastrointestinal discomfort Allergic reactions Dermatitis Skin disorders Harmful if swallowed or in contact with skin. May cause an allergic skin reaction. Causes serious eye damage. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Causes severe burns.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam Dry powder Carbon dioxide (CO2) Water spray
Unsuitable extinguishing media	:	Water jet
Hazardous combustion products	:	No hazardous combustion products are known
Further information	:	Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Pregnant women or women of child-bearing age should not be exposed to this product. Follow standard hygiene measures when handling chemical products.
Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

Materials to avoid : Explosives
Oxidizing agents
Poisonous gases
Dangerous when wet
Flammable solids
Organic peroxides
Poisonous liquids
Spontaneously Combustible Substances

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
m-phenylenebis(methylamine)	1477-55-0	C	0.018 ppm	ACGIH
		C	0.1 mg/m3	OSHA P0
2,2'-iminodiethylamine	111-40-0	TWA	1 ppm	ACGIH
		TWA	1 ppm 4 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methanol	67-56-1	TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

Respiratory protection	:	Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove respiratory and skin/eye protection only after vapors have been cleared from the area. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	liquid
Color	:	light yellow
Odor	:	ammoniacal
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/ range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available

Flash point	:	145 °F / 63 °C (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.07 hpa
Relative vapor density	:	No data available
Density	:	1.050 g/ml (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	slightly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Dynamic	:	No data available
Kinematic	:	> 20.5 mm2/s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Particle size	:	Not applicable
Particle Size Distribution	:	Not applicable
Volatile organic compounds (VOC) content	:	0 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.

Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	methanol

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or in contact with skin.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 1,949 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 14.44 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: 1,942 mg/kg Method: Calculation method

Components:

2-piperazin-1-ylethylamine:

Acute oral toxicity	:	LD50 Oral (Rat): 2,097 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): ca. 866 mg/kg

Benzyl alcohol:

Acute oral toxicity	:	LD50 Oral (Rat): 1,200 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 4.178 mg/l Exposure time: 4 h Test atmosphere: dust/mist

Phenol, 4-nonyl, branched:

Acute oral toxicity	:	LD50 Oral (Rat): 1,412 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 3,160 mg/kg

triethylenetetramine:

Acute oral toxicity	:	LD50 Oral (Rat): 1,716 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1,465 mg/kg

Isophoronediamine:

Acute oral toxicity	:	LD50 Oral (Rat): 1,030 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 - 5,000 mg/kg

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Acute oral toxicity	:	LD50 Oral (Rat): 7,010 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.3 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 4,248 mg/kg

Adduct XA-P (epoxy amine adduct, polymer):

Acute oral toxicity	:	LD50 Oral (Rat): 300 - 2,000 mg/kg Method: OECD Test Guideline 423

m-phenylenebis(methylamine):

Acute oral toxicity	:	LD50 Oral (Rat): 930 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 1.34 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	:	LD50 Dermal (Rat): > 3,100 mg/kg

Salicylic acid, o-hydroxybenzoic acid:

Acute oral toxicity	:	LD50 Oral (Rat): 891 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2,000 mg/kg

2,2'-iminodiethylamine:

Acute oral toxicity	:	LD50 Oral (Rat): 1,553 mg/kg

Acute inhalation toxicity	:	LC50 (Rat): 0.071 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rat): 1,045 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	Not applicable
OSHA	Not applicable
NTP	Not applicable

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.
Corrosive to the respiratory tract.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2-piperazin-1-ylethylamine:

Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h

4,4'-isopropylidenediphenol:

Benzyl alcohol:

Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h

Phenol, 4-nonyl, branched:

triethylenetetramine:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia): 10 - 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 10 - 100 mg/l Exposure time: 72 h

Isophoronediamine:

Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Toxicity to fish	:	LC50 (Cyprinus carpio (Carp)): 55 mg/l Exposure time: 96 h

m-phenylenebis(methylamine):

Toxicity to fish	:	LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other	:	EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

aquatic invertebrates	Exposure time: 48 h

Phenol, 2-nonyl-, branched:

Persistence and degradability
No data available

Bioaccumulative potential
No data available

Mobility in soil
No data available

Other adverse effects

Product:

Additional ecological information	:	Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May be harmful to the environment if released in large quantities. Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No.	:	UN 2735
Proper shipping name	:	Amines, liquid, corrosive, n.o.s. (2-piperazin-1-ylethylamine, 4-nonylphenol, branched)
Class	:	8
Packing group	:	II
Labels	:	Corrosive

Packing instruction (cargo aircraft)	:	855
Packing instruction (passenger aircraft)	:	851
Environmentally hazardous	:	yes

IMDG-Code

UN number	:	UN 2735
Proper shipping name	:	AMINES, LIQUID, CORROSIVE, N.O.S. (2-piperazin-1-ylethylamine, 4-nonylphenol, branched)
Class	:	8
Packing group	:	II
Labels	:	8
EmS Code	:	F-A, S-B
Marine pollutant	:	yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	:	UN 2735
Proper shipping name	:	Amines, liquid, corrosive, n.o.s. (2-piperazin-1-ylethylamine, Phenol, 4-nonyl, branched)
Class	:	8
Packing group	:	II
Labels	:	CORROSIVE
ERG Code	:	153
Marine pollutant	:	no

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)
IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

The following substance(s) is/are subject to a Significant New Use Rule:

Phenol, 4-nonyl, branched	84852-15-3	See 40 CFR § 721.10765; Proposed RuleProposed Rule
Phenol, 2-nonyl-, branched	91672-41-2	Proposed Rule

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:
Phenol, 4-nonyl, branched 84852-15-3

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Respiratory or skin sensitization
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

4,4'-isopropylidenediphenol	80-05-7	>= 10 - < 20 %
Phenol, 4-nonyl, branched	84852-15-3	>= 5 - < 10 %

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

⚠ **WARNING:** This product can expose you to chemicals including 4,4'-isopropylidenediphenol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)

Sikagard® WDE Primer Part B

OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA P0 / C	:	Ceiling limit

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 09/18/2026

100000002994
US / Z8