

SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version SDS Number: Date of last issue: -**Revision Date:**

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

SECTION 1. IDENTIFICATION

Product name SikaThorolastic-750 AA smooth ultra deep Formerly MProtect

EL 750AA ultradeep

Product code 000000000051718289

Manufacturer or supplier's details

Company name of supplier Sika MBCC US LLC

Address 201 POLITO AVE

Lyndhurst NJ 07071

Emergency telephone ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use Product for construction chemicals

Restrictions on use Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Specific target organ toxicity : Category 2 (Kidney)

- repeated exposure

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms

Signal Word

Hazard Statements H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements Prevention:

P273 Avoid release to the environment.



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

P260 Do not breathe dust or mist.

Response:

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 20 - < 50
Titanium dioxide	13463-67-7	>= 1 - < 3
ethylene glycol	107-21-1	>= 1 - < 3
zinc oxide	1314-13-2	>= 0.3 - < 1
Poly(oxy-1,2-ethanediyl), .alpha [(1,1,3,3-tetramethylbutyl)phenyl]- .omegahydroxy-	9036-19-5	>= 0.2 - < 0.3
diuron	330-54-1	>= 0 - < 0.1
2-octyl-4-isothiazol-3-ones	26530-20-1	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	>= 0 - < 0.1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

None known.

Notes to physician

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Foam

> Dry powder Water spray

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Product is not explosive.



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Recommended storage tem-

perature

41 °F / 5 °C

Further information on stor-

age stability

Minimum storage temperature:

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylene glycol	107-21-1	TWA value (Vapor frac- tion)	25 ppm	ACGIHTLV
		STEL value (Vapor frac- tion)	50 ppm	ACGIHTLV
		STEL value (Aerosol, inhalable.)	10 mg/m3	ACGIHTLV
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Va- por)	50 ppm	ACGIH



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

		STEL (Inhalable fraction,	10 mg/m3	ACGIH
		Aerosol only)		
		C	50 ppm 125 mg/m3	OSHA P0
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR
				1910.1000
				(Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
zinc oxide	1314-13-2	TWA value	2 mg/m3	ACGIHTLV
		(Respirable fraction)		
		STEL value (Respirable fraction)	10 mg/m3	ACGIHTLV
		REL value (fumes/smok e)	5 mg/m3	NIOSH
		REL value (dust)	5 mg/m3	NIOSH
		STEL value (fumes/smok e)	10 mg/m3	NIOSH
		Ceil_Time (dust)	15 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable par-	2 mg/m3	ACGIH



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

I	ticulate mat-	1	ı
		10 mg/m3	ACGIH
	pirable par-		
	ticulate mat-		
	ter)		
	TWA (Dust)	5 mg/m3	NIOSH REL
		5 mg/m3	NIOSH REL
			NIOSH REL
			NIOSH REL
		5 mg/m3	OSHA Z-1
		15 m a/m 2	OSHA Z-1
	dust) `		
	TWA (respir- able fraction)	_	OSHA Z-1
	TWA (Total dust)	10 mg/m3	OSHA P0
	TWÁ (respir-	5 mg/m3	OSHA P0
	able dust		
	TWA (Fumes)	5 mg/m3	OSHA P0
	STEL (Fumes)	10 mg/m3	OSHA P0
1317-65-3	REL value	5 mg/m3	NIOSH
	REL value	10 mg/m3	NIOSH
	PEL (Respir-	5 mg/m3	29 CFR
	able fraction)		1910.1000
	,		(Table Z-1)
		15 mg/m3	29 CFR
	dust)		1910.1000
	T) A / A	- / 0	(Table Z-1)
		5 mg/m3	29 CFR
			1910.1000 (Table Z-1-A)
		15 mg/m3	29 CFR
		10 mg/mo	1910.1000
	(I Stal dast)		
			I (Table Z-1-A)
	TWA (total	15 mg/m3	(Table Z-1-A) OSHA Z-1
	dust) TWA (respir-	15 mg/m3 5 mg/m3	
	dust) TWA (respirable fraction) TWA (Total	_	OSHA Z-1
	dust) TWA (respirable fraction) TWA (Total dust)	5 mg/m3	OSHA Z-1 OSHA Z-1 OSHA P0
	dust) TWA (respirable fraction) TWA (Total dust) TWA (respiration)	5 mg/m3	OSHA Z-1
	dust) TWA (respirable fraction) TWA (Total dust)	5 mg/m3	OSHA Z-1 OSHA Z-1 OSHA P0
	1317-65-3	ticulate matter) TWA (Dust) TWA (Fumes) ST (Fumes) C (Dust) TWA (Fumes) TWA (total dust) TWA (respirable fraction) TWA (Total dust) TWA (respirable dust fraction) TWA (Fumes) STEL (Fumes) STEL (Fumes) STEL (Fumes) REL value (Respirable) REL value (Total) PEL (Respir-	ter) STEL (Respirable particulate matter) TWA (Dust) 5 mg/m3 TWA 5 mg/m3 (Fumes) 10 mg/m3 C (Dust) 15 mg/m3 TWA 5 mg/m3 TWA 5 mg/m3 (Fumes) 15 mg/m3 TWA (total dust) 15 mg/m3 TWA (respirable dust fraction) TWA (respirable dust (Fumes) 5 mg/m3 TWA (Fumes) 5 mg/m3 TWA (respirable dust fraction) TWA (Respirable) 5 mg/m3 (Fumes) 5 mg/m3 (Total) 15 mg/m3 PEL (Respirable fraction) 5 mg/m3 TWA value (Respirable fraction) 15 mg/m3 TWA value (Respirable fraction) 15 mg/m3



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Revision Date: Version SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

		pirable)	(Calcium carbonate)	
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH

Engineering measures No applicable information available.

Personal protective equipment

Respiratory protection Wear a NIOSH-certified (or equivalent) respirator as neces-

sary.

Hand protection

Remarks The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye wash bottle with pure water Eye protection

Tightly fitting safety goggles

Skin and body protection Impervious clothing

Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Color various colours



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

Odor : ammonia-like, slight odour

Odor Threshold : No data available

pH : neutral to slightly alkaline

Melting point : No applicable information available.

Boiling point : 378 - 401 °F / 192 - 205 °C

Flash point : $> 200.01 \,^{\circ}\text{F} / > 93.34 \,^{\circ}\text{C}$

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

15.3 %(V)

Lower explosion limit / Lower

flammability limit

3.2 %(V)

Vapor pressure : No data available.

Relative vapor density : Heavier than air.

Relative density : 1.2 - 1.4

Density : 1.2 - 1.4 g/cm3 (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

: No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available.

Viscosity, kinematic : No applicable information available.



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified based on available information.



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

Product:

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

zinc oxide:

M-Factor (Acute aquatic tox- : 1

city)

M-Factor (Chronic aquatic : 1



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

toxicity)

diuron:

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

10

10

2-octyl-4-isothiazol-3-ones:

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

Persistence and degradability

No data available

Bioaccumulative potential

Components:

zinc oxide:

Partition coefficient: n-

octanol/water

Remarks: The value has not been determined because the

substance is inorganic.

3-iodo-2-propynyl butylcarbamate:

Partition coefficient: n-

octanol/water

log Pow: 2.81 (77 °F / 25 °C)

Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes

Mobility in soil

Components:

zinc oxide:

Distribution among environ-

mental compartments

Adsorption

Medium: water - soil

log Kd: 1.15

Method: Calculation method Remarks: Not applicable

Other adverse effects

Product:

Additional ecological infor-

mation

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethylene glycol 107-21-1

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, Quartz (SiO2), diuron, formaldehyde, acrylonitrile, which is/are known to the State of California to cause cancer, and

ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020


The ingredients of this product are reported in the following inventories:

TSCA: On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION


Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

1)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

29 CFR 1910.1000 (Table Z- : Short Term Exposure Limit (STEL):

1-A) / STEL value

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL): ACGIHTLV / TWA value : Time Weighted Average (TWA):



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):

NIOSH / REL value : Recommended exposure limit (REL): NIOSH / STEL value : Short Term Exposure Limit (STEL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA P0 / TWA : 8-hour time weighted average OSHA P0 / STEL : Short-term exposure limit

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 11/23/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our com-



SikaThorolastic-750 AA smooth ultra deep Formerly MProtect EL 750AA ultradeep

Version Revision Date: SDS Number: Date of last issue: -

1.0 11/23/2020 000000261413 Date of first issue: 11/23/2020

mitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN