

## PRODUCT DATA SHEET

# Sikalastic® M 200

(formerly MasterSeal® M 200)

POLYURETHANE BASE COAT FOR SIKALASTIC® TRAFFIC 1500 AND 2000 DECK COATING SYSTEMS

### PRODUCT DESCRIPTION

Sikalastic® M 200 is a one-component, moisture-curing polyurethane base coat for use in Sikalastic® Traffic 1500 and 2000 deck coating systems.

### USES

- Stadiums
- Balconies
- Parking Garages
- Commercial Construction
- Building and Restoration
- Plywood Decks/Balconies
- Plaza Decks

### CHARACTERISTICS / ADVANTAGES

- Sikalastic® M 200 has strong adhesion properties
- Easy preparation reduces on-site labor costs
- Available in both self-leveling and flash/sloping

### PRODUCT INFORMATION

<b>Chemical Base</b>	Sikalastic® M 200 is a moisture-curing polyurethane base coat.
<b>Packaging</b>	<ul style="list-style-type: none"> <li>▪ 5 gallon (18.93 L) pails</li> <li>▪ 55 gallon (208 L) drums Self-Leveling Only</li> </ul>
<b>Shelf Life</b>	<p>When properly stored, Sikalastic® M 200 products have the following shelf life:</p> <ul style="list-style-type: none"> <li>▪ 5-Gallon Pail: 1 Year</li> <li>▪ 55-Gallon Drum: 9 Months</li> </ul>
<b>Storage Conditions</b>	Store in unopened containers in a cool, clean, dry area
<b>Color</b>	Grayish in color
<b>Solid content by mass</b>	81%
<b>Viscosity</b>	<p>4,000-9,000 cps</p> <p>Cold temperatures will increase viscosity.</p> <p>See preferred Sikalastic® Deck Coating Solution for system-specific physical</p>

properties and test results.

---

## TECHNICAL INFORMATION

---

Shore A Hardness	60	(ASTM D 2240)
Tensile Strength	752 psi (5.2 MPa)	(ASTM D 412)
	<b>Elongation</b>	
	595%	(ASTM D 412)

---

## SYSTEM INFORMATION

---

Systems	<ul style="list-style-type: none"><li>▪ Sikalastic® Vehicular 1500</li><li>▪ Sikalastic® Vehicular 2000</li><li>▪ Sikalastic® Pedestrian 1500</li><li>▪ Sikalastic® Pedestrian 2000</li></ul>
---------	---

---

## APPLICATION INFORMATION

---

Coverage	See preferred Sikalastic® Deck Coating Solution for total system yield
Cure Time	Sikalastic® M 200 cures in 12–14 hours when tested at 73 °F (23 °C) and 50% relative humidity.

---

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES.**

**SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



**Product Data Sheet**  
**Sikalastic® M 200**  
June 2024, Version 01.01  
02081200000002052

SikalasticM200-en-US-(06-2024)-1-1.pdf

