





PRODUCT DATA SHEET

LaHabra® Color Coat Tint Pack

Powdered pigments for use with LaHabra® Exterior Stucco Color Coat

DESCRIPTION

LaHabra® Color Coat Tint Pack is a powdered pigment for tinting LaHabra® Exterior Stucco Color Coat Tint Bases (100 & 200).

USES

 Tinting LaHabra® Exterior Stucco Color Coat Tint Base 100 or Tint Base 200

CHARACTERISTICS / ADVANTAGES

- Specifically formulated pigments to color Exterior Stucco Color Tint Bases
- 1 Tint Pack creates standard color
- Up to 4 Tint Packs can be added per Exterior Stucco Tint Base 90 lb. bag for increased color depth
- Color Tint Pack 100s color Exterior Stucco Color Coat Tint Base 100
- Color Tint Pack 200s color Exterior Stucco Color Coat Tint Base 200

PRODUCT DATA SHEET LaHabra® Color Coat Tint Pack August 2025, Version 01.01 021810101000000152

PRODUCT INFORMATION

Packaging	16 oz. bag	
Color	Color	Material No.
	Egg Shell (Base 100)	842470
	Crystal White (Base 100)	842461
	Blue Grey (Base 100)	842347
	French Vanilla (Base 200)	842435
	Adobe (Base 100)	842408
	Sandstone (Base 100)	842358
Shelf life	NA	
Storage conditions	Unopened, undamaged, original sealed bag that is properly transported and stored.	
APPLICATION INFORI	MATION	
Mixing ratio	 1 Tint pack per 90 lb. bag of Exterior Stucco Color Coat for standard colo Up to 4 Tint Packs per 90 lb. bag of Exterior Stucco Color Coat for in- 	

creased color depth

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any

products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

MIXING

- Using a mechanical plaster mixer, mix one (1) 90 lb. bag of appropriate stucco tint base with approximately three (3) gallons of potable water to a thin consistency until it is smooth and free of lumps.
- Add all of the color packs (1 per bag for a standard color, a maximum of 4 standard color packs can be added per 90 lb. bag for increased color depth) to be used for one "batch" and mix until color is evenly dispersed, (approximately 1 to 2 minutes).

PRODUCT DATA SHEET

LaHabra® Color Coat Tint Pack August 2025, Version 01.01 021810101000000152





- 3. Thin the mixture with water and then add the remaining bags of stucco base (adjusting water as necessary) to correspond with the number of color packs mixed in step 2. Allow material to mix at a somewhat stiff consistency for approximately 15 minutes. Add the remaining amount of water to achieve the desired consistency, and then disengage the mixing blades for approximately 5 to 10 minutes in order to temper the material. Doing this allows the material to start its initial set. Re-engage the mixing blades for approximately 5 minutes, adjusting the water and mixing only long enough to achieve uniformity. The material is now ready to be removed from the mixer and applied to the wall.
- 4. For additional batches of the same material, thin the remaining mixture with water, then repeat steps 3 & 4. Wash out mixer completely to change colors.

LEGAL NOTES

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service

Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEG-AL THEORY FOR SPECIAL OR CONSEQUENTIAL DAM-AGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at https://usa.sika.com/en/about-us/terms-conditions-of-sale.html or by calling 1-800-933-7452.

LaHabraColorCoatTintPack-en-USLAHABRA-(08-2025)-1-1.pdf

LaHabra® Color Coat Tint Pack August 2025, Version 01.01 021810101000000152

PRODUCT DATA SHEET



