

## Sika® Swellstop® WB Primer Adhesive

### Water Based Primer Adhesive

<b>Description</b>	Sika® Swellstop® Water Based Primer Adhesive is used for adhering Sika® Swellstop® strip-applied waterstop to concrete.
<b>Where to Use</b>	Sika® Swellstop® Water Based Primer is used in conjunction with Sika® Swellstop® strip-applied waterstop in nonmoving joint applications, such as retaining walls, box culverts, penetrations, concrete pipes, vaults, slabs, elevator shafts, etc.
<b>Advantages</b>	<ul style="list-style-type: none"> <li>■ Improved/Extended coverage, approximately 2,400 linear feet per gallon</li> <li>■ Reduced dry time</li> <li>■ Cleans with soap and water while still wet</li> <li>■ Non-hazmat shipping</li> <li>■ Low VOC content/VOC compliant</li> </ul>
<b>Typical Data</b>	
<b>Coverage</b>	Approximately 2,400 linear feet per gallon
<b>Packaging</b>	1 gallon pails
<b>Cure Mechanism</b>	Allow to dry for 15-30 minutes depending on temperature and humidity.

#### Properties

<b>Appearance</b>	Green colored liquid (ASTM D1729)
<b>Form</b>	Watery liquid material when wet, tacky film when dry
<b>Odor</b>	Slight acrylic when wet, none when dry
<b>Specific Gravity</b>	1.01 +/- 0.05 g/cm <sup>3</sup> (ASTM D297)
<b>Viscosity</b>	<50cps (ASTM D2196)
<b>Freezing Point</b>	32°F
<b>Boiling Point</b>	212°F
<b>Solubility in Water</b>	Soluble
<b>pH</b>	6-8 (ASTM E70)
<b>Volatile Content</b>	73% by weight

\*Results may differ based upon statistical variations depending upon temperature, application methods, test methods, actual site conditions, and curing conditions.



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://usa.sika.com/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

# Waterproofing

## How to Use

<b>Surface Prep</b>	Apply only to cured, dry concrete surfaces. Prepare the application area by removing all loose particles and dirt.
<b>Application</b>	<ul style="list-style-type: none"><li>■ Brush apply a 2" wide coat of Sika® Swellstop® Water Based Primer Adhesive along the joint usually 2" wide. Allow to dry for 15-30 minutes depending on temperature and humidity.</li><li>■ Sika® Swellstop® Water Based Primer Adhesive and Sika® Swellstop® Waterstop should be applied on the same day.</li></ul>
<b>Shelf Life</b>	12 months when stored in the unopened, original packaging in warehouse conditions.
<b>Storage</b>	After container has been initially opened, maintain a tight seal at room temperature. Do not freeze.
<b>Conditioning</b>	Store at room temperature.

**KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY**

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

**Sika Greenstreak Sales Office**  
3400 Tree Court Industrial Blvd.  
St. Louis, MO 63122  
Tel: (636) 225-9400  
Fax: (636) 225-2049  
[usa.sika.com](http://usa.sika.com)

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: (201) 933-8800  
Fax: (201) 933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Canada Inc.**  
601, Delmar Avenue  
Pointe-Claire, QC H9R 4A9  
Phone: (514) 697-2610  
Fax: (514) 697-3087  
[can.sika.com](http://can.sika.com)

The Sika logo consists of the word "Sika" in a bold, yellow, sans-serif font, set against a red triangular background. A registered trademark symbol (®) is located to the right of the word.

**PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://USA.SIKA.COM/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.**