

## SikaProof® Patch-200 B

### Self-adhesive Tape for External Jointing of the SikaProof® A Waterproofing System

<b>Description</b>	SikaProof® Patch-200 B is a self-adhesive tape, consisting of a SikaProof® membrane laminated with a Butyl-adhesive that is covered with a release liner.
<b>Where to Use</b>	SikaProof® Patch-200 B is used for post-sealing of joints, penetrations as well as damages outside on the membrane side of the SikaProof® A system.
<b>Advantages</b>	<ul style="list-style-type: none"> <li>■ High watertightness</li> <li>■ Weathering resistant with temporary UV-stability</li> <li>■ High adhesion</li> <li>■ High durability of the Butyl-adhesive</li> <li>■ Easy and fast to install</li> </ul>
<b>Typical Data</b>	
<b>Packaging</b>	1 roll, packed in one cardboard box Dimension Width 200 mm, Length 20 m, Thickness 2.20 mm
<b>Coverage</b>	Width 200 mm, Length 20 m, Thickness 2.20 mm

<b>Appearance:</b>	White release liner over black adhesive on a light yellow membrane.
<b>Dimensions</b>	
<b>Width:</b>	200 mm
<b>Length:</b>	20 m
<b>Thickness:</b>	2.20 mm
<b>System Information</b>	
<b>System Components:</b>	<p>SikaProof® ExTape-150 and SikaProof® Tape-150 A are self-adhesive tapes to adhere joints, connections and details in the SikaProof® A sheet membrane waterproofing system.</p> <p>SikaProof® A-05, membrane in rolls of widths 1.0 or 2.0 m</p> <p>SikaProof® A-08, membrane in rolls of widths 1.0 or 2.0 m</p> <p>SikaProof® A-12, membrane in rolls of widths 1.0 or 2.0 m</p> <p>SikaProof® Ex Tape-150, self-adhesive tape for external jointing, based on butylrubber, in 150 mm width</p> <p>SikaProof® Tape-150 A, self-adhesive tape for internal jointing, based on a polyacrylate-adhesive, in 150 mm width</p>



PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://usa.sika.com/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.

# Waterproofing

## How to Use

### Surface Prep

The contact surface is the light yellow membrane side of the SikaProof® A membrane. It must be dry, clean and free of any materials that could impair the adhesion.

### Application

SikaProof® Patch-200 B is a cold-applied and post-applied self-adhesive tape to seal joints, connections, penetrations and possible damages of the membrane on the outside membrane side of the SikaProof® A system. There is only a pressure roller required, to press the tapes firmly onto the membrane surface. For further more detailed information about the installation method, please refer to the SikaProof® A membrane Product Data Sheet and the Method Statement.

### Limitations

SikaProof® Patch-200 B is approved to seal only the SikaProof® A system. To use SikaProof® Patch-200 B with other materials (such as any synthetics etc.) the compatibility has to be tested.

Not suitable for use in direct contact with PVC, tar, asphalt, hot bitumen, wood preservatives with substances containing oil, solvents or any other de-bonding agents.

Substrate temperature: +41°F / +95°F

Ambient air temperature: +41°F / +95°F

SikaProof® A system must only be installed by trained and approved Sika contractors. SikaProof® A Patch-200 B is not UV stabilized and can not be installed on structures permanently exposed to UV light and weathering. Do not apply the SikaProof® Patch-200 B during continuous or prolonged rainfall.

### Shelf Life

SikaProof® Patch-200 B rolls have a shelf life of 18 months from date of production if stored properly in unopened undamaged original packaging, in a horizontal position, in dry conditions and at temperatures between +41°F and +86°F. The rolls must be protected from direct sunlight, rain, snow and ice, etc. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.

**KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY**

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

**Sika Greenstreak Office**  
3400 Tree Court Industrial Blvd.  
St. Louis, MO 63122  
Tel: (800) 325-9504  
Fax: (636) 225-2049  
[usa.sika.com](http://usa.sika.com)

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: (201) 933-8800  
Fax: (201) 933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Canada Inc.**  
601, Delmar Avenue  
Pointe-Claire, QC H9R 4A9  
Phone: (514) 697-2610  
Fax: (514) 697-3087  
[can.sika.com](http://can.sika.com)

The Sika logo consists of the word "Sika" in a bold, yellow, sans-serif font, set against a red triangular background. A registered trademark symbol (®) is located to the right of the word.

**PRIOR TO EACH USE OF ANY SIKA PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [HTTP://USA.SIKA.COM/](http://USA.SIKA.COM/) OR BY CALLING SIKA'S TECHNICAL SERVICE DEPARTMENT AT 800-933-7452. NOTHING CONTAINED IN ANY SIKA MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTION FOR EACH SIKA PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.**