



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

### SECTION 1. IDENTIFICATION

Product name : SikaGrout®-9600 US

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 1 (Lungs)

#### GHS label elements

Hazard pictograms : 

Signal Word : Danger



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

Hazard Statements : H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H350 May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe dust.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Quartz (SiO <sub>2</sub> ) >5µm	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	>= 50 - < 70
Portland Cement	65997-15-1	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335	>= 30 - < 50
Limestone	1317-65-3		>= 1 - < 5

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

- Most important symptoms and effects, both acute and delayed : Prolonged exposure can cause silicosis.  
Cough  
Respiratory disorder  
Allergic reactions  
Dermatitis  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure.  
Causes severe burns.  
Health injuries may be delayed.  
corrosive effects  
irritant effects  
sensitizing effects
- Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid breathing dust.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE



**SikaGrout®-9600 US**

Revision Date 10/07/2024

Print Date 10/07/2024

- Advice on protection against fire and explosion : Avoid dust formation.  
Provide appropriate exhaust ventilation at places where dust is formed.
  
- Advice on safe handling : Avoid formation of respirable particles.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.
  
- Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.
  
- Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Dangerous when wet  
Flammable solids  
Organic peroxides  
Poisonous liquids  
Spontaneously Combustible Substances
  
- Further information on storage stability : Keep in a dry place.  
No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2) >5µm	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3



**SikaGrout®-9600 US**

Revision Date 10/07/2024

Print Date 10/07/2024

		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m <sup>3</sup>	OSHA CARC
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
Portland Cement	65997-15-1	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup>	ACGIH
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Dust)	50 Million particles per cubic foot	OSHA Z-3
		TWA (Total)	10 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable fraction)	5 mg/m <sup>3</sup>	OSHA P0
Limestone	1317-65-3	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.



**SikaGrout®-9600 US**

Revision Date 10/07/2024

Print Date 10/07/2024

**Particles of nuisance dust**

Form of exposure	Value type	Control parameters	Basis
total dust	TWA	15 mg/m <sup>3</sup>	OSHA Z-3
respirable fraction	TWA	5 mg/m <sup>3</sup>	OSHA Z-3

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
 Wash hands before breaks and immediately after handling the product.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 Wash thoroughly after handling.  
 Avoid breathing dust.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : powder



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

Color	:	gray
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/ range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Density	:	No data available
Bulk density	:	1,800 - 2,400 kg/m <sup>3</sup> (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available





## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

Volatile organic compounds (VOC) content : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : No decomposition if stored and applied as directed.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

Not classified due to lack of data.

#### **Skin corrosion/irritation**

Causes severe burns.

#### **Serious eye damage/eye irritation**

Causes serious eye damage.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

May cause an allergic skin reaction.

##### **Respiratory sensitization**

Not classified due to lack of data.

##### **Germ cell mutagenicity**

Not classified due to lack of data.

##### **Carcinogenicity**

May cause cancer by inhalation.

<b>IARC</b>	Group 1: Carcinogenic to humans Quartz (SiO <sub>2</sub> ) (Silica dust, crystalline)	14808-60-7
<b>OSHA</b>	OSHA specifically regulated carcinogen Quartz (SiO <sub>2</sub> ) (crystalline silica)	14808-60-7
<b>NTP</b>	Known to be human carcinogen Quartz (SiO <sub>2</sub> )	14808-60-7



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

(Silica, Crystalline (Respirable Size))

### Reproductive toxicity

Not classified due to lack of data.

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.  
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.  
Prolonged exposure can cause silicosis.

### Aspiration toxicity

Not classified due to lack of data.

### Further information

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

No data available

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

---

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

The following substance(s) is/are subject to a Significant New Use Rule:

Diutan 595585-15-2 See 40 CFR § 721.2076; Final Rule

No substances are subject to TSCA 12(b) export notification requirements.

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Carcinogenicity

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including Quartz (SiO<sub>2</sub>) >5µm, which is known to the State of California to cause cancer, and Portland Cement, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 10/07/2024



## SikaGrout®-9600 US

Revision Date 10/07/2024

Print Date 10/07/2024

---

10000060322  
US / Z8