

# Sikagard® 7600 HG/VG System Guidelines

## January 2020

BUILDING TRUST



Application	Warranty Length	Sikard® 7600 Build	Primer	Protection Course	Drainage Mat
Liner	5 years	60 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer***		
	10 years	90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer***		
	20 years	120 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		
Foundation Walls*	5 years	60 mils			Sika® Drainage Mat 420
	10 years	90 mils			Sika® Drainage Mat 420
	20 years	90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer	GreenGuard® PB4	Sika® Drainage Mat 420
Split Slab, Pavers**	5 years	60 mils			Sika® Drainage Mat 1000/720
	10 years	90 mils			Sika® Drainage Mat 1000/720
	20 years	120 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 1000
Planter		Floor/Wall			
	5 Years	60/60 mils			Sika® Drainage Mat 420/GRS
	10 Years	90/90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS
	20 Years	120/90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS
Green Roof	10 Years	90/90 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS
	20 Years	120/120 mils	Sikalastic® PF Lo-VOC or Sikalastic® FTP Lo-VOC Primer		Sika® Drainage Mat 420/GRS

\*Some Building Codes may require Drainage Mats depending on the height of the foundation

\*\*Mortar beds supporting pavers must be at least 2 inches thick

\*\*\*Primer required if tank permanently holds liquid.

1. Follow the directions on each product data sheet carefully
2. Speak with your local Sika Representative to receive approval for all warranties
3. Use root barrier where applicable
4. Use Sikalastic FTP Lo-VOC on concrete with up to 6% moisture content.

**Sika Corporation**

**www.usa.sika.com**

201 Polito Avenue

Lyndhurst, NJ 07071

Phone: 201-933-8800