

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

---

### SECTION 1. IDENTIFICATION

Product name : Sikagard P 770 PTB Formerly MSeal P 770 PTB  
Product code : 000000000050543681

#### Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC  
Address : 201 POLITO AVE  
Lyndhurst NJ 07071  
Emergency telephone : ChemTel: +1-813-248-0585

#### Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating  
Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Inhalation - vapour) : Category 4  
Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 2A  
Respiratory sensitization : Category 1  
Skin sensitization : Category 1  
Carcinogenicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Respiratory Tract)  
Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Olfactory organs)

#### GHS label elements

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

---

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs (Olfactory organs) through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P271 Use only outdoors or in a well-ventilated area.  
P260 Do not breathe dust or mist.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P284 In case of inadequate ventilation wear respiratory protection.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
**Response:**  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P314 Get medical advice/ attention if you feel unwell.  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

P405 Store locked up.

### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

### Other hazards

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : isocyanate

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	>= 25 - < 50
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 25 - < 50
diphenylmethane-2,4'-diisocyanate	5873-54-1	>= 1 - < 3
Isocyanic acid, polymethylenepolyphenylene ester, polymer with alpha-hydro-omega-hydroxypoly(oxy-1,2-ethanediy)	57636-09-6	>= 0.3 - < 1

## SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

In case of eye contact : Contact lenses should be removed. Hold eyelids open and

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1	Revision Date: 02/16/2021	SDS Number: 000000764510	Date of last issue: 12/15/2020 Date of first issue: 12/15/2020
----------------	------------------------------	-----------------------------	---

---

- flush with copious amounts of clean, fresh water or a special eyewash solution and seek medical advice.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.  
Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Harmful if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
Suspected of causing cancer.  
May cause damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : Under certain conditions in case of fire other hazardous combustion products may be generated.
- Hazardous combustion products : carbon oxides  
Cyanides  
nitrogen oxides  
isocyanate
- Further information : The degree of risk is governed by the burning substance and the fire conditions.  
If exposed to fire, keep containers cool by spraying with water.  
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.  
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

- Personal precautions, protective equipment and emergency procedures : Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
Wear eye/face protection.  
Use personal protective clothing.  
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Pick up with suitable appliance and dispose of.  
Dispose of absorbed material in accordance with regulations.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : The product is neither self-ignitable, nor an explosion hazard, nor does it promote fires.
- Advice on safe handling : Avoid inhalation of dusts/mists/vapours.  
Avoid skin contact.  
Ensure adequate ventilation.  
No special measures necessary provided product is used correctly.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
- Recommended storage temperature : 50 - 86 °F / 10 - 30 °C
- Further information on storage stability : Characteristics of the product are irreversibly changed below the limit temperature.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	TWA value	0.005 ppm	ACGIHTLV
		REL value	0.005 ppm 0.05 mg/m <sup>3</sup>	NIOSH
		Ceil_Time	0.020 ppm 0.2 mg/m <sup>3</sup>	NIOSH

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
 Date of first issue: 12/15/2020

		CLV	0.02 ppm 0.2 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		CLV	0.02 ppm 0.2 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.005 ppm	ACGIH
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA Z-1
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	OSHA P0
		TWA	0.005 ppm 0.05 mg/m <sup>3</sup>	NIOSH REL
		C	0.02 ppm 0.2 mg/m <sup>3</sup>	NIOSH REL

**Engineering measures** : Provide local exhaust ventilation to maintain recommended P.E.L.

**Personal protective equipment**

Respiratory protection : Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection

Remarks : Chemical resistant protective gloves Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale dust/fumes/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). When using do not eat or drink.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

---

Appearance : viscous liquid

Color : dark brown

Odor : aromatic

Odor Threshold : not determined

pH : unmeasurable

Melting point : No data available

Boiling range : approx. 392 - 662 °F / 200 - 350 °C

Flash point : approx. 403 °F / 206 °C

Evaporation rate : No data available.

Flammability (liquids) : The product is not flammable.

Self-ignition : not self-igniting

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : not determined

Relative vapor density : No data available

Relative density : No data available

Density : approx. 1.01 g/cm<sup>3</sup> (73 °F / 23 °C)

Bulk density : Not applicable

Solubility(ies)

    Water solubility : hydrolyzes

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : unmeasurable

Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1	Revision Date: 02/16/2021	SDS Number: 000000764510	Date of last issue: 12/15/2020 Date of first issue: 12/15/2020
----------------	------------------------------	-----------------------------	---

---

Viscosity  
Viscosity, dynamic : approx. 160 mPa.s (73.40 °F / 23.00 °C)  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : not fire-propagating

Sublimation point : No data available

Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if inhaled.

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.



# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

---

### Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Suspected of causing cancer.

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

May cause damage to organs (Olfactory organs) through prolonged or repeated exposure if inhaled.

### Aspiration toxicity

Not classified based on available information.

### Further information

#### Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### Persistence and degradability

#### Product:

Biodegradability : Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available. Discharge into the environment must be avoided.

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

---

### Components:

#### **Isocyanic acid, polymethylenepolyphenylene ester (P-MDI):**

Bioaccumulation : Remarks: Accumulation in organisms is not to be expected.

#### **Mobility in soil**

No data available

#### **Other adverse effects**

### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Observe national and local legal requirements. Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal selected. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

## SECTION 14. TRANSPORT INFORMATION

### **International Regulations**

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

#### **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

#### **Domestic regulation**

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version 1.1      Revision Date: 02/16/2021      SDS Number: 000000764510      Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

---

### 49 CFR

Not regulated as a dangerous good

---

## SECTION 15. REGULATORY INFORMATION

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Isocyanic acid, polymethylene-polyphenylene ester (P-MDI)	9016-87-9	>= 30 - < 50 %
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 30 - < 50 %

### US State Regulations

#### Pennsylvania Right To Know

Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8
Methylethylketone	78-93-3

#### New Jersey Right To Know

Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8
diphenylmethane-2,4'-diisocyanate	5873-54-1

### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

---

## SECTION 16. OTHER INFORMATION

### Further information

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB




Version  
1.1

Revision Date:  
02/16/2021


SDS Number:  
000000764510

Date of last issue: 12/15/2020  
Date of first issue: 12/15/2020

### NFPA 704:



### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / CLV	: Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-1) / CLV	: Ceiling Limit Value:
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / Ceil_Time	: Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA P0 / C	: Ceiling limit
OSHA Z-1 / C	: Ceiling

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version	Revision Date:	SDS Number:	Date of last issue: 12/15/2020
1.1	02/16/2021	00000764510	Date of first issue: 12/15/2020

Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/16/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU

# SAFETY DATA SHEET

## Sikagard P 770 PTB Formerly MSeal P 770 PTB



Version	Revision Date:	SDS Number:	Date of last issue: 12/15/2020
1.1	02/16/2021	000000764510	Date of first issue: 12/15/2020

---

EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN