



## PRODUCT DATA SHEET

# SikaColor-350 Antiquing Agent

Powder antiquing agent for unsealed stamped or textured concrete and unsealed stamped or textured cementitious overlayers

### PRODUCT DESCRIPTION

SikaColor®-350 Antiquing Agent is a proprietary blend of powders. When SikaColor®-350 Antiquing Agent is mixed with water and properly applied to a stamped or textured cementitious surface, it will impart a secondary color to the surface visually enhancing its appearance. SikaColor®-350 Antiquing Agent can be applied to unsealed new or existing stamped or textured concrete and unsealed new or existing stamped or textured cementitious overlayers. Previously named Perma-Tique® Antiquing Agent and LITHOTIQUE™ Antiquing Agent.

### USES

- Antiques new or existing unsealed stamped or textured concrete and stamped or textured cementitious overlayers
- Adds secondary color to stamped or textured concrete and cementitious overlay applications that utilized SikaCem®-800 Clear Liquid Release
- Ideal for interior and exterior installations

### CHARACTERISTICS / ADVANTAGES

- Easy to use
- Mixes with water
- No dust, providing minimal cleanup

### PRODUCT INFORMATION

Chemical Base	Metal Oxide
Packaging	3 lb. (1.4 kg) fill in 1 gal. (3.8 L) plastic pail
Shelf Life	24 months
Storage Conditions	Store in original, unopened containers, in dry storage
Appearance / Color	Available in 14 standard colors

## APPLICATION INFORMATION

---

Coverage	2,000-3,000 sq. ft. (185.8-278.7 m <sup>2</sup> ) per 3 lb. (1.4 kg) of powder mixed with clean potable water
----------	---

---

### BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

### LIMITATIONS

- SikaColor®-350 Antiquing Agent is not recommended for use on smooth or broom finished cementitious surfaces.
- SikaColor®-350 Antiquing Agent shall be applied within recommended ambient temperatures of 50-90°F (10-32.2°C).
- Existing sealer must be removed from the cementitious substrate prior to application of SikaColor®-350 Antiquing Agent.
- SikaCem®-800 Clear Liquid Release must be scrubbed clean from cementitious substrate prior to application of SikaColor®-350 Antiquing Agent.
- SikaColor®-350 Antiquing Agent must be sealed with a SikaCem® sealer post application.

### ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

### APPLICATION INSTRUCTIONS

Cast a job site mock-up prior to the installation for approval of color and finish. Utilize all materials, tools, and techniques from the actual job in the mock-up. Consistent batching, pouring, finishing, curing, sealing, and preparation techniques, will ensure the uniformity of architectural concrete. Verify adequate wet and dry slip resistance. Maintenance requirements should also be discussed.

### SURFACE PREPARATION

Existing concrete substrates must be profiled to a minimum Concrete Surface Profile of CSP 1. The surface must be clean and free of grease, oil residue, curing or sealing compounds, and any other potential bond breakers.

### MIXING

Add 3/4 cup (6 oz.) of SikaColor®-350 Antiquing Agent per 1 gal. (3.8 L) of clean potable water. Mix vigorously with drill and mixing paddle until all the powder has been incorporated into the water.

**Note:** The amount of SikaColor®-350 Antiquing Agent added to water can be increased or decreased depending on the amount of antiquing that you desire. The maximum amount of SikaColor®-350 Antiquing Agent that can be used is 1.5 cups (12 oz.) per 1 gal. (3.8 L) of water.

### APPLICATION

Wet the cementitious substrate with water prior to the application of SikaColor®-350 Antiquing Agent. Remove any standing water after wetting the surface. During application, the SikaColor®-350 Antiquing Agent slurry will settle and concentrate into the low areas, providing a natural accent color to the stamped or textured surface. Some areas may initially have a whitened appearance. Once dried, the whitening will disappear.

Transfer the mixed SikaColor®-350 Antiquing Agent slurry into a pump up sprayer and apply an even coat to the surface. SikaColor®-350 Antiquing Agent mixed slurry may also be applied by soft bristle brush.

During application, maintain agitation to avoid settling of the mixed slurry.

### SEALING

SikaColor®-350 Antiquing Agent must be sealed. Use SikaCem®-100 Clear Guard®, SikaCem®-100 PRO 350®, or SikaCem® water-based sealers for exterior applications. Use SikaCem® water-based sealers for interior applications. Consult most current local Product Data Sheets for complete SikaCem® sealer Application Instructions.

### MAINTENANCE

Consult most current local Product Data Sheets for complete SikaCem® sealer Maintenance Instructions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



**Product Data Sheet**  
SikaColor-350 Antiquing Agent  
August 2022, Version 01.01  
021405071000000103

SikaColor-350AntiquingAgent-en-US-(08-2022)-1-1.pdf

