



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

### SECTION 1. IDENTIFICATION

Product name : SikaBiresin® G433 (formerly EC-433) Part A

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 1B

#### Other hazards

#### GHS label elements

Hazard pictograms :





## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Signal Word                    | : Danger                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Hazard Statements              | : H315 Causes skin irritation.<br>H317 May cause an allergic skin reaction.<br>H318 Causes serious eye damage.<br>H341 Suspected of causing genetic defects.<br>H350 May cause cancer by inhalation.<br>H360 May damage fertility or the unborn child.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Supplemental Hazard Statements | : Corrosive to the respiratory tract.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Precautionary Statements       | : <b>Prevention:</b><br>P201 Obtain special instructions before use.<br>P202 Do not handle until all safety precautions have been read and understood.<br>P261 Avoid breathing mist or vapors.<br>P264 Wash skin thoroughly after handling.<br>P272 Contaminated work clothing must not be allowed out of the workplace.<br>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.<br><b>Response:</b><br>P302 + P352 IF ON SKIN: Wash with plenty of water.<br>P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.<br>P308 + P313 IF exposed or concerned: Get medical advice/ attention.<br>P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.<br>P362 + P364 Take off contaminated clothing and wash it before reuse.<br><b>Storage:</b><br>P405 Store locked up.<br><b>Disposal:</b><br>P501 Dispose of contents/ container to an approved waste disposal plant. |

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .  
None known.



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures

##### Components

| Chemical name                                                                     | CAS No./Unique ID | Classification                                                                                                                     | Concentration (% w/w) |
|-----------------------------------------------------------------------------------|-------------------|------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| bisphenol-F-(epichlorhydrin) epoxy resin                                          | 28064-14-4        | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Skin Sens. 1; H317                                                                   | >= 15 - <= 40         |
| Trimethylolpropane triglycidylether                                               | 30499-70-8        | Skin Corr. 1C; H314<br>Eye Dam. 1; H318<br>Skin Sens. 1B; H317<br>Muta. 2; H341<br>Repr. 1B; H360                                  | >= 3 - <= 7           |
| 1,4-bis(2,3-epoxypropoxy)butane                                                   | 2425-79-8         | Acute Tox. 4; H302<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Skin Sens. 1; H317 | >= 3 - <= 7           |
| bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) | 25068-38-6        | Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>Skin Sens. 1; H317                                                                   | >= 0.1 - <= 1         |
| Quartz (SiO <sub>2</sub> ) >5µm                                                   | 14808-60-7        | Carc. 1A; H350<br>STOT RE 1; H372<br>STOT SE 3; H335                                                                               | >= 0.1 - <= 1         |

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

|                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                             | Keep eye wide open while rinsing.                                                                                                                                                                                                                                                                                                                                                                                      |
| If swallowed                                                | : Clean mouth with water and drink afterwards plenty of water.<br>Do not induce vomiting without medical advice.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>Obtain medical attention.                                                                                                                                                                    |
| Most important symptoms and effects, both acute and delayed | : irritant effects<br>sensitizing effects<br>toxic effects for reproduction<br>Allergic reactions<br>Excessive lachrymation<br>Erythema<br>Dermatitis<br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye damage.<br>Suspected of causing genetic defects.<br>May cause cancer by inhalation.<br>May damage fertility or the unborn child.<br>Corrosive to the respiratory tract. |
| Notes to physician                                          | : Treat symptomatically.                                                                                                                                                                                                                                                                                                                                                                                               |

---

### SECTION 5. FIRE-FIGHTING MEASURES

|                                                |                                                                                                                                                                                                                           |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                   | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                                 |
| Further information                            | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.                                                                                                                                                          |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

|                                                                     |                                                                                                                                                                                                                                           |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Deny access to unprotected persons.                                                                                                                                                               |
| Environmental precautions                                           | : Do not flush into surface water or sanitary sewer system.<br>If the product contaminates rivers and lakes or drains inform respective authorities.<br>Local authorities should be advised if significant spillages cannot be contained. |



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Pregnant women or women of child-bearing age should not be exposed to this product.  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components                      | CAS-No.    | Value type (Form of exposure)       | Control parameters / Permissible concentration | Basis    |
|---------------------------------|------------|-------------------------------------|------------------------------------------------|----------|
| Quartz (SiO <sub>2</sub> ) >5µm | 14808-60-7 | TWA (Respirable particulate matter) | 0.025 mg/m <sup>3</sup>                        | ACGIH    |
|                                 |            | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup>                         | OSHA Z-1 |
|                                 |            | TWA (respirable)                    | 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2    | OSHA Z-3 |
|                                 |            | TWA (respirable)                    | 250 mppcf / %SiO <sub>2</sub> +5               | OSHA Z-3 |
|                                 |            | TWA (respirable)                    | 0.1 mg/m <sup>3</sup>                          | OSHA P0  |



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

|  |  |                                     |                      |           |
|--|--|-------------------------------------|----------------------|-----------|
|  |  | able dust fraction)                 |                      |           |
|  |  | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH     |
|  |  | PEL (respirable)                    | 0.05 mg/m3           | OSHA CARC |
|  |  | TWA (respirable dust fraction)      | 0.1 mg/m3            | OSHA P0   |
|  |  | TWA (Respirable particulate matter) | 0.025 mg/m3          | ACGIH     |
|  |  | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica) | ACGIH     |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concen-



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

|                  |                                                                                                                                                                                                                                                 |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                  | tration and amount of dangerous substances, and to the specific work-place.                                                                                                                                                                     |
| Hygiene measures | : Avoid contact with skin, eyes and clothing.<br>Wash hands before breaks and immediately after handling the product.<br>Remove contaminated clothing and protective equipment before entering eating areas.<br>Wash thoroughly after handling. |

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                                  |                                          |
|--------------------------------------------------|------------------------------------------|
| Appearance                                       | : paste                                  |
| Color                                            | : gray                                   |
| Odor                                             | : amine-like                             |
| Odor Threshold                                   | : No data available                      |
| pH                                               | : Not applicable                         |
| Melting point/ range / Freezing point            | : No data available                      |
| Boiling point/boiling range                      | : 511 °F / 266 °C                        |
| Flash point                                      | : 201 °F / 94 °C<br>(Method: closed cup) |
| Evaporation rate                                 | : No data available                      |
| Flammability (solid, gas)                        | : No data available                      |
| Upper explosion limit / Upper flammability limit | : No data available                      |
| Lower explosion limit / Lower flammability limit | : No data available                      |
| Vapor pressure                                   | : 0.01 hpa                               |
| Relative vapor density                           | : No data available                      |
| Density                                          | : 1.85 g/cm <sup>3</sup> (68 °F / 20 °C) |
| Solubility(ies)                                  |                                          |
| Water solubility                                 | : soluble                                |
| Solubility in other solvents                     | : No data available                      |



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

|                                          |   |                                            |
|------------------------------------------|---|--------------------------------------------|
| Partition coefficient: n-octanol/water   | : | No data available                          |
| Autoignition temperature                 | : | No data available                          |
| Decomposition temperature                | : | No data available                          |
| Viscosity                                |   |                                            |
| Viscosity, dynamic                       | : | No data available                          |
| Viscosity, kinematic                     | : | > 20.5 mm <sup>2</sup> /s (104 °F / 40 °C) |
| Explosive properties                     | : | No data available                          |
| Oxidizing properties                     | : | No data available                          |
| Volatile organic compounds (VOC) content | : | Not applicable                             |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |                                                             |
|------------------------------------|---|-------------------------------------------------------------|
| Reactivity                         | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : | The product is chemically stable.                           |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions.                |
| Conditions to avoid                | : | No data available                                           |
| Incompatible materials             | : | No data available                                           |
| Hazardous decomposition products   | : | No decomposition if stored and applied as directed.         |

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### bisphenol-F-(epichlorhydrin) epoxy resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

##### Trimethylolpropane triglycidylether:

Acute oral toxicity : LD50 Oral (Rat): 3,398 mg/kg

##### 1,4-bis(2,3-epoxypropoxy)butane:





## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

Acute oral toxicity : LD50 Oral (Rat): 1,163 mg/kg

**bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700):**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified due to lack of data.

**Germ cell mutagenicity**

Suspected of causing genetic defects.

**Carcinogenicity**

May cause cancer by inhalation.

|             |                                         |            |
|-------------|-----------------------------------------|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans         |            |
|             | Quartz (SiO <sub>2</sub> )              | 14808-60-7 |
|             | (Silica dust, crystalline)              |            |
| <b>OSHA</b> | OSHA specifically regulated carcinogen  |            |
|             | Quartz (SiO <sub>2</sub> )              | 14808-60-7 |
|             | (crystalline silica)                    |            |
| <b>NTP</b>  | Known to be human carcinogen            |            |
|             | Quartz (SiO <sub>2</sub> )              | 14808-60-7 |
|             | (Silica, Crystalline (Respirable Size)) |            |

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure**

Corrosive to the respiratory tract.

**STOT-repeated exposure**

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified due to lack of data.



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

### Further information

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **Trimethylolpropane triglycidylether:**

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 9 mg/l  
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50 (Daphnia magna (Water flea)): 3.7 mg/l  
Exposure time: 48 d

##### **bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h  
  
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
Exposure time: 48 h

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
May be harmful to the environment if released in large quantities.  
Water polluting material.



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

- UN/ID No. : UN 3082
- Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
- Class : 9
- Packing group : III
- Labels : Miscellaneous
- Packing instruction (cargo aircraft) : 964
- Packing instruction (passenger aircraft) : 964
- Environmentally hazardous : yes

##### IMDG-Code

- UN number : UN 3082
- Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
- Class : 9
- Packing group : III
- Labels : 9
- EmS Code : F-A, S-F
- Marine pollutant : yes

#### Domestic regulation

##### 49 CFR Road

Not regulated as a dangerous good

DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant.

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

### CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.


**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Germ cell mutagenicity  
Carcinogenicity  
Reproductive toxicity  
Skin corrosion or irritation  
Serious eye damage or eye irritation

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

### California Prop. 65

 **WARNING:** This product can expose you to chemicals including Quartz (SiO<sub>2</sub>) >5µm, which is known to the State of California to cause cancer, and Oxirane, (chloromethyl)- Epichlorohydrin, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



## SikaBiresin® G433 (formerly EC-433) Part A

Revision Date 03/24/2025

Print Date 03/31/2025

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

|                 |   |                                                                                  |
|-----------------|---|----------------------------------------------------------------------------------|
| ACGIH           | : | USA. ACGIH Threshold Limit Values (TLV)                                          |
| OSHA CARC       | : | OSHA Specifically Regulated Chemicals/Carcinogens                                |
| OSHA P0         | : | USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)               |
| OSHA Z-1        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts               |
| ACGIH / TWA     | : | 8-hour, time-weighted average                                                    |
| OSHA CARC / PEL | : | Permissible exposure limit (PEL)                                                 |
| OSHA P0 / TWA   | : | 8-hour time weighted average                                                     |
| OSHA Z-1 / TWA  | : | 8-hour time weighted average                                                     |
| OSHA Z-3 / TWA  | : | 8-hour time weighted average                                                     |

#### Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 03/24/2025

100000035707  
US / Z8