

PRODUCT DATA SHEET

Sikafloor®-100 CLN Pronto

(formerly MTop SRS 100CLN)

METHYL-METHACRYLATE BASED CLEANER

PRODUCT DESCRIPTION

Sikafloor®-100 CLN Pronto is an inhibited methyl-methacrylate (MMA) based cleaner. Sikafloor®-100 CLN Pronto does not contain any polymers or accelerators that promote polymerization.

USES

Sikafloor®-100 CLN Pronto is intended to be used only for the following purposes:

- Cleaning tools and equipment that have been used to apply Sikafloor® Pronto reactive acrylic resins and systems.
- Cleaning and softening an existing Sika floor in preparation for the application of fresh Sikafloor® Pronto material.

CHARACTERISTICS / ADVANTAGES

- Reactivates an existing MMA floor prior to re-coat
- Extends the life of tools as a fast acting MMA cleaner

PRODUCT INFORMATION

Packaging	38 lb pails and 430 lb drums
Shelf Life	24 months
Storage Conditions	Store material in original, unopened container in a cool and dry place out of direct sunlight. Do not store near open flame or ignition source.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

Sikafloor®-100 CLN Pronto has a high potential for misuse due to the mistaken perception that it will "cure" when exposed to the same hardener powder (BPO) that is used to catalyze Sikafloor® Pronto reactive acrylic resins. Sikafloor®-100 CLN Pronto contains an inhibitor that prevents it from polymerizing (curing). While this adds to the product's performance for the uses listed in the "uses" section above, it will have a detrimental effect on Sikafloor® Pronto systems if they are contaminated with Sikafloor®-100 CLN Pronto. Following are common misuses of Sikafloor®-100 CLN Pronto:

- Using Sikafloor®-100 CLN Pronto as a trowel aid. This will contaminate the surface being troweled with MMA monomer that will remain uncured. This will cause a slow deterioration or bubbling of the surface.
- Using Sikafloor®-100 CLN Pronto as a thinner or diluent in Sikafloor® Pronto resins. This will interfere with the resin's ability to fully cure and develop desirable "finished" performance properties.
- Leaving visible puddling of Sikafloor®-100 CLN Pronto on a prepared surface. Use only enough Sikafloor®-100 CLN Pronto to wipe surface clean, not enough to puddle. Leaving excess Sikafloor®-100 CLN Pronto on a surface to be re-coated will undermine the cure of the new MMA flooring.

Sikafloor®-100 CLN Pronto is a flammable liquid in its uncured state (as provided). All sources of ignition should be removed from the work area before handling this product. No smoking, open flames, or sparks should be permitted in and around the work area. Workers should wear protective clothing including goggles and impermeable gloves. If allowable exposure limits are exceeded, organic vapor respirators should be worn. All on-site personnel should become familiar with the SDS.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS**

**PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT
OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD
BY OTHERS.**

Sale of SIKA products are subject to the Terms and
Conditions of Sale which are available at
<https://usa.sika.com/en/group/SikaCorp/termsandconditions.html>
or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Sikafloor®-100 CLN Pronto
January 2025, Version 04.01
020816210010000047

Sikafloor-100CLNPronto-en-US-(01-2025)-4-1.pdf

